

भारतीय राष्ट्रीय राजमार्ग प्राधिकरण

(सड़क परिवहन और राजमार्ग मंत्रालय, भारत सरकार)

National Highways Authority of India (Ministry of Road Transport and Highways, Government of India) क्षेत्रीय कार्यालय, मदुरे / Regional Office, Madurai दूसरा व तीसरा तल, विजय कृष्णा प्लाजा, सं. 1, लेक एरिया, मेलुर मैन रोड, माहुतावनी, मदुरे - 625107 2nd & 3rd Floor, Vijay Krishna Plaza, No. 1, Lake Area, Melur Main Road, Mattuthavani, Madurai - 625107 दूरमाष / Tele: +91-452-2588999 वेब / Website: www.nhai.gov.in ई.मेल / E-mail: romadurai@nhai.org



NHAI/15018/4.5/01/2025/RO Madurai/E-275071/492

19th March, 2025

INVITATION OF PUBLIC COMMENTS

विषय: भाराराप्रा - क्षे.का. मदुरे- पकाई, नागरकोइल - Issue of NOC for laying of IOCL Gas pipeline along Madurai - Kanyakumari stretch of NH-44 - Laying of 10.75" steel pipe and 89mm OD HDPE pipe along with OFC from Km 133/349 to Km 148/038 (RHS), Km 148/038 to Km 159/422 (LHS),125mm Dia MDPE pipeline from Km 158.740 to Km 159.342(BHS), Km 144/238 to Km 150/038(RHS), Km 148/038 to Km 150.438(LHS), 8.625" OD Steel pipeline with OFC from Km 148/038 to km 150/000 (RHS), 4.5" steel pipe with OFC from Km 157/010 to Km 157/341 (RHS), Km 158/740 to Km 159/342(RHS),10.75" OD steel pipeline with OFC across NH-44 at Km 148/038, 125mm Dia MDPE pipeline with OFC at Km 148/038 & Km 158/740, 4.5" steel pipe across NH-44 at Km 138/478, Km 157/341, Km 158/740 as a part of City Gas Distribution(CGD) project in Tuticorin District, Tamilnadu-Invitation of Public Comments - Reg.

प्रसंगः PD, Nagercoil Lr. NHAI/PD/PIU/NGL/NH-44/IOCL/2025/385 dated 17.02.2025.

The Proposal is regarding permission for laying of gas pipe lines by M/s IOCL - SRPL laying of 10.75" steel pipe and 89mm OD HDPE pipe along with OFC from Km 133/349 to Km 148/038 (RHS), Km 148/038 to Km 159/422 (LHS),125mm Dia MDPE pipeline from Km 158.740 to Km 159.342(BHS), Km 144/238 to Km 150/038(RHS), Km 148/038 to Km 150.438(LHS), 8.625" OD Steel pipeline with OFC from Km 148/038 to km 150/000 (RHS), 4.5" steel pipe with OFC from Km 157/010 to Km 157/341 (RHS), Km 158/740 to Km 159/342(RHS),10.75" OD steel pipeline with OFC across NH-44 at Km 148/038, 125mm Dia MDPE pipeline with OFC at Km 148/038 & Km 158/740, 4.5" steel pipe across NH-44 at Km 138/478, Km 157/341, Km 158/740by using HDD method in Madurai - Kanyakumari stretch of NH-44 in the State of Tamil Nadu by Senior Manager (CGD), SRPL, Tuticorin has been submitted to this office by the PD, Nagercoil Lr. NHAI/PD/PIU/NGL/NH-44/IOCL/2025/385 dated 17.02.2025 in accordance with Ministry's latest guidelines dated 22.11.2016.

2. The alignment proposed by Senior Manager (CGD), SRPL, Tuticorin for laying of gas pipe lines by M/s IOCL - SRPL 10.75" steel and 89mm OD HDPE pipe along with OFC from Km 133/349 to Km 148/038 (RHS), Km 148/038 to Km 159/422

my

Page 1 of 4

NHAI/15018/4.5/01/2025/RO Madurai/E-275071/492

19th March, 2025

(LHS),125mm Dia MDPE pipeline from Km 158.740 to Km 159.342(BHS), Km 144/238 to Km 150/038(RHS), Km 148/038 to Km 150.438(LHS), 8.625" OD Steel pipeline with OFC from Km 148/038 to km 150/000 (RHS), 4.5" steel pipe with OFC from Km 157/010 to Km 157/341 (RHS), Km 158/740 to Km 159/342(RHS),10.75" OD steel pipeline with OFC across NH-44 at Km 148/038, 125mm Dia MDPE pipeline with OFC at Km 148/038 & Km 158/740, 4.5" steel pipe across NH-44 at Km 138/478, Km 157/341, Km 158/740 by using HDD method in Madurai - Kanyakumari stretch of NH-44 is as detailed under:

Length (m)	Dia of pipe	Available ROW (m)	Remarks
1,4689	10.75" Dia steel pipe with 6.4mm		*
11384	OD pipe for OFC		a
1962	OD steel pipe with 6.4mm		
331	4.5" Dia steel pipe with 6.4mm		
602	thickness & 89mm OD pipe for OFC	60	Laying of pipe line along the extreme edge of ROW at a
1204			distance of 1.0m from ROW edge.
5800	pipe & 89mm OD		
2400	pipe for OFC		
	(m) 14689 11384 1962 331 602 1204	14689 10.75" Dia steel pipe with 6.4mm thickness & 89mm OD pipe for OFC 1962 8.625" Dia OD steel pipe with 6.4mm thickness & 89mm OD pipe for OFC 331 4.5" Dia steel pipe with 6.4mm thickness & 89mm OD pipe for OFC 1204 1204 1204 125mm Dia MDPE pipe & 89mm OD pipe for OFC	(m) Dia of pipe (m) 14689 10.75" Dia steel pipe with 6.4mm thickness & 89mm OD pipe for OFC 1962 8.625" Dia OD steel pipe with 6.4mm thickness & 89mm OD pipe for OFC 331 4.5" Dia steel pipe with 6.4mm thickness & 89mm OD pipe for OFC 1204 5800 125mm Dia MDPE pipe & 89mm OD pipe for OFC

Short

Page 2 of 4

NHAI/15018/4.5/01/2025/RO Madurai/E-275071/492

19th March, 2025

Across NH - 38: Km 148/038	60	10.75" Dia Carbon steel pipe with 6.4mm thickness & 89mm OD HDPE pipe for OFC	60	Laying of pipe line
Km 138/478	60	4.5" Dia Carbon		across by HDD Method at minimum depth of 1.5 m from top of the
Km 157/341	60	steel pipe with 6.4mm thickness &89mm OD HDPE		subgrade.
Km 158/740	60	pipe for OFC		

- The Right of Way is 60 m in the aforesaid stretch. Senior Manager (CGD), SRPL, Tuticorin has proposed for laying of gas pipe lines by M/s IOCL SRPL 10.75" steel and 89mm OD HDPE pipe along with OFC from Km 133/349 to Km 148/038 (RHS), Km 148/038 to Km 159/422 (LHS),125mm Dia MDPE pipeline from Km 158.740 to Km 159.342(BHS), Km 144/238 to Km 150/038(RHS), Km 148/038 to Km 150.438(LHS), 8.625" OD Steel pipeline with OFC from Km 148/038 to km 150/000 (RHS), 4.5" steel pipe with OFC from Km 157/010 to Km 157/341 (RHS), Km 158/740 to Km 159/342(RHS),10.75" OD steel pipeline with OFC across NH-44 at Km 148/038, 125mm Dia MDPE pipeline with OFC at Km 148/038 & Km 158/740, 4.5" steel pipe across NH-44 at Km 138/478, Km 157/341, Km 158/740 by using HDD method in Madurai- Kanyakumari section of NH-44 in the State of Tamil Nadu which is in conformity with Ministry's guidelines dated 22.11.2016.
- 4) Senior Manager (CGD), SRPL, Tuticorin has furnished an Undertaking to the effect that the applicant will move the laid gas pipeline in future if required by NHAI at any time for expansion of the NH at their own cost without claiming any compensation from NHAI. Further, mentioned that Senior Manager (CGD), SRPL, Tuticorin will also undertake that laying of gas pipeline will not have deleterious effects on any of the bridge components and roadway safety for traffic.
- 5) As per the guidelines issued by the Ministry vide letter No.RW/NH-33044/29/2015/ S&R(R) dated 22.11.2016 the proposal submitted by the applicant will be made available for public comments and the comments is invited within 30 days from the day of uploading.

NHAI/15018/4.5/01/2025/RO Madurai/E-275071/ 492

19th March, 2025

In view of the above, comments of the public on the above proposal is invited to the below mentioned address:

Regional Officer,
National Highways Authority of India,
No.2nd &3rd Floor, Vijay Krishna Plaza,
No.1, Lake Area, Melur Main Road, Mattuthavani,
Madurai - 625 007.

भवदीय

(आर.मुरुगप्रकाश | R .Murugaprakash)

उप महाप्रबंधक(तक)|Dy.General Manager (Tech)

क्षे.का. मदुरै |RO-Madurai

संलग्न: As above

प्रतिलिपि:

1. The NIC, New Delhi - for uploading in the Ministry's website.

2. The PD, Nagercoil- for information.

CHECK - LIST

Guidelines for Project Directors for processing the proposal of laying 10.75", 8.625" & 4.5" Carbon Steel Natural gas pipeline along with 125mm MDPE and 89mm HDPE pipes for OFC by IOCL Pipelines division in the land along National Highway NH-44 vested with NHAI.

Relevant circulars

0

0

0

0

1) MoRTH Circular No: RW/NH-33044/29/2015/S&R(R) Dated 22.11.2016

2) MoRTH Circular No: NH-36094/01/2022-S&R(P&B) Dated 17.04.2023

Check list for getting approval for laying of 10.75" Carbon steel Natural Gas Pipelines along with 125mm MDPE and 89mm HDPE pipes for OFC on NHAI land.

SI. No.	ltem	Information/ Status	Remarks	Page No
1	General Information			
1.1	Name and Address of the Applicant	Sh. Ranjith Kumar N Senior Manager (CGD)	Authoriza tion	
		Indian Oil Corporation Limited, Southern Region Pipelines, City Gas Distribution (CGD)	attached	
		Project Office 1st Floor, JJ Center, No. 4/7/5, Ettayapuram Road, Sankaraperi Village,		
-		Thoothukudi – 628002.		
1.2	National Highway Number	NH-44		
1.3	State	Tamilnadu		
1.4	Location	Tirunelveli KTC Nagar flyover to Chandra fuels (k.kailasapuram), Gangaikondan		
1.5	(Chainage in km)	Increasing Chainage from KM 133/349 to KM 159/442		
1.6	Length in Meters	26,093		
1.7	Width of available ROW			
	(a) Left side from center line towards increasing Chainage/km direction	30 metres		
	(b) Right side from center line towards increasing chainage/km direction	30 metres		
1.8	Proposal to lay underground Gas Pipeline along with OFC			
	(a) Left side from center line towards increasing chainage/ km direction	Increasing Chainage from KM 148/038 to KM 159/442	10.75" OD Steel pipe	
	(b) Right side from center line towards increasing chainage/ km direction	1. Increasing Chainage from KM 133/349 to KM 148/038	10.75" OD	
	€	2. Increasing Chainage from KM 148/038 to KM 150/000	8.625" OD	

Senior Manager

IOCL CGD Thoothukudi

SRPL

SI. No.	Item	Information/ Status	Remarks	Page No
		3.Increasing Chainage from KM 157/010 to KM 157/341, Increasing Chainage from KM 158/740 to Km 159/342	4.5" OD	
1.9	Proposal to acquire land			
	(a) Left side from center line	NA		
	(b) Right side from center line	NA		
1.10	Whether proposal is in the same side where land is not to be acquired	Yes		
	If not, then where to lay the Pipeline	NA		
1.11	Details of already laid services, if any, along the proposed route	3 OFC Cables		53- 78
1.12	Number of lanes (2/4 / 6/8 lanes) existing	4 Lanes		
1.13	Proposed Number of lanes (2 lane with paved shoulders/4 / 6/8 lanes)	NA		
1.14	Service road existing or not	YES		
	If yes, then which side			
	(a) Left side from center line	5.45- 6.70m (Shown in Strip Plan)		53- 78
	(b) Right side from center line	5.45 - 6.70m (Shown in Strip Plan)		53- 78
1.15	Proposed Service Road	NA		
	(a) Left side from center line	NA		
	(b) Right side from center line	NA		
1.16	Whether proposal to lay pipe is after the service road or between the service road and main carriageway	It is proposed to lay the pipeline after the service road and in the Utility Corridor. i.e, within 2m from ROW.		
1.17	Whether carrying of sewage/gas pipeline has been proposed on highway bridge If "Yes", then mention the methodology proposed for the same.	No. Bridges and Structures encountered shall be crossed through HDD Technique		
1.18	Whether carrying of sewage/gas pipeline has been proposed on the parapet/any part of the bridge. If "Yes", then the methodology proposed for the same.	No. Bridges and Structures encountered shall be crossed through HDD Technique		
1.19	If crossing of the road involved If "Yes", then it shall be encased in pipes or through the structure or conduit specially built for that purpose at the expense of agency owning the line.	Yes, 4.5" OD pipe along with 89mm M.S conduit crossing NH-44 at Ch km 138/478, km 157/341, Ch. km 158/740, 10.75" OD pipe along with 89 mm MS conduit crossing at Ch. Km 148/038 through horizontal directional drilling (HDD) Technique.	5 locations	
	a) whether existing structure allowed to carry sewage/gas pipeline	NA		

SRPL

0.0000

0

 \bigcirc

0

0

0

0

0

0

0

0

0

O

0

O

 \bigcirc

what is the distance of crossing the age/gas pipeline from the existing structure ising should not be too near to existing cture on National Highway, the minimum ance should be 15 meters the casing pipe (or conduit pipe in the case electric cable) carrying the utility line shall all, cast iron or reinforce cement concrete having adequate strength and be large ugh to permit ready withdrawal of carrier electric type of casing and of the casing/conduit shall be sealed in the outside, so that it does not act as	Noted for compliance Not applicable, as crossing will be executed through HDD Technique Not applicable	2	
age/gas pipeline from the existing structure ising should not be too near to existing cture on National Highway, the minimum ance should be 15 meters the casing pipe (or conduit pipe in the case electric cable) carrying the utility line shall I, cast iron or reinforce cement concrete having adequate strength and be large ugh to permit ready withdrawal of carrier electric type of casing and of the casing/conduit shall be sealed	Not applicable, as crossing will be executed through HDD Technique	2	
he casing pipe (or conduit pipe in the case electric cable) carrying the utility line shall I, cast iron or reinforce cement concrete having adequate strength and be large ugh to permit ready withdrawal of carrier electric cable. Intion type of casing casing cand of the casing/conduit shall be sealed	executed through HDD Technique		
nd of the casing/conduit shall be sealed	Not applicable		
nage path	Not applicable		
The casing/conduit should, as minimum ended minimum drain to drain curs and toes ope in the fills	Not applicable		
the top of the casing/conduit should be at t 1.2 meters below the surface of the road ect to being at least 0.3meter below the n invert.	Not applicable		
Mention the methodology for crossing of d for the proposed sewage/gas pipeline. ssing shall be by boring machine (HDD) ENCHLESS TECHNOLOGY], specially, where existing road pavement is of cement crete or dense bitumen concrete type.	Through HDD Technique. HDD of gas pipeline shall be carried out without casing/conduit pipe following the safety precautions and codes mentioned in Annexure -II of MoRTH Circular No: NH-36094/01/2022-S&R(P&B) Dated 17.04.2023	Safety precautio n and HDD plan enclosed	31- 46
e casing/conduit pipe shall be installed with even bearing throughout its length and in a manner as to prevent the formation of erway along it	Not applicable, as crossing will be executed through HDD Technique		
ument / Drawings enclosed with the posal	Enclosed		
ss section showing the size of trench for n trenching method (Is it normal size of m deep X 0.3m wide) Should not be greater than 60cm wider than the outer diameter of pipe. Located as close to the extreme edge of the	Underground pipe trenches cross section showing steel, MDPE and HDPE pipes is attached. a) Noted & Complied b) It is proposed to lay the underground gas pipeline in the 2 mtr corridor from the	V4	90
n Sl th	deep X 0.3m wide) hould not be greater than 60cm wider than he outer diameter of pipe. becated as close to the extreme edge of the OW as possible but not less than 15 meters om the centre lines of the nearest carriage ray.	deep X 0.3m wide) hould not be greater than 60cm wider than ne outer diameter of pipe. becated as close to the extreme edge of the OW as possible but not less than 15 meters om the centre lines of the nearest carriage ray. HDPE pipes is attached. a) Noted & Complied b) It is proposed to lay the underground gas pipeline in the 2 mtr corridor from the edge of NHAI ROW. c) Noted & complied.	deep X 0.3m wide) hould not be greater than 60cm wider than a) Noted & Complied he outer diameter of pipe. hocated as close to the extreme edge of the OW as possible but not less than 15 meters hom the centre lines of the nearest carriage ray. HDPE pipes is attached. a) Noted & Complied b) It is proposed to lay the underground gas pipeline in the 2 mtr corridor from the edge of NHAI ROW.

0

0

(")

0

0

 \bigcirc

0

0

0

0

Ö

0

0

 \bigcirc

 \bigcirc

0.

APORA

SRPL

SI. No.	Item	Information/ Status	Remarks	Page No
	national highway when the road formation is situated in double cutting, nor shall be laid over existing culverts and bridge. d) It should be laid so that their top is at least 0.6 meter below the ground level so as the obstruct of the road land.	d) Minimum 1.2 mtr Pipe cover is proposed.		
2.2	Cross section showing the size of pit and location of cable for HDD method	Enclosed		79- 89
2.3	Strip plan/ Route Plan showing the natural gas pipeline, Chainage, width of ROW, distance of proposed, cable from the edge of ROW, important mile stone, intersections, cross drainage works etc.	Enclosed		53- 78
2.4.1	Methodology for laying of pipe Open trenching method. (May be allowed in utility corridor only where pavement is neither cement concrete nor dense bituminous concrete type.) If yes, what is the methodology of refilling of trench.	Excavate the area 1.6m (Depth) x 1.0m(Width), place the pipe inside and refill the trench with the excavated soil in layers not exceeding 150mm and compaction will be done		
	a) The trench width should be at least 30cm, but not more than 60cm wider than outer diameter of the pipe.	Yes, noted for compliance		
	b) For the filling of the trench, bedding should be to a depth of not less than 60cm. It shall consist of granular material, free of lumps, clods and cobbles and graded to yield a firm surface without sudden change in the bearing value. Unsuitable soil and rock edged should be excavated and replace by selected material	Yes, noted for compliance		
	c) The backfill shall be completed in two stages side fill to the level of the top of the pipe and overall, to the bottom of the road crust.	Yes, noted for compliance		
	d) The side fill shall consist of granular material laid in 15cm layer each consolidated by mechanical tampering and controlled addition to moisture to 95% of the proctor's density. Overfill shall be compacted to the same density as material has been removed. Consolidation by saturation or pounding will not be permitted.	Yes, noted for compliance		
	e) The road crust shall be built to the same strength as existing crunch of either side of the trench. Care shall be taken to avoid formation of dip at trench.	Yes, noted for compliance		

Ó

SRPL TUTICORIN

SI. No.	ltem	Information/ Status	Remarks	Page No
	f) The excavation shall be protected by flagman, signs, and barricades, and red-light during night hours.	Noted for compliance		
	g) If required, diversion shall be constructed at the expenses of agency owing utility line.	Noted for compliance		
2.4.2	Horizontal Directional Drilling (HDD) Method	Total 600m (approx) for crossing roads, Pipeline/concrete Culverts. Cross Section drawing attached.		79- 89
2.4.3	Laying Natural gas pipeline through CD works and method of laying. In case where the carrying of natural gas pipeline on bridge becomes inescapable.	NA		
3	Draft License Agreement signed by two witnesses	Enclosed		1-7
4	Performance Bank guarantee in favor of NHAI must be obtained at Rs.100/- per running meter (parallel to NH) and Rs. 1, 00,000/-per crossing of NH, for period of one year initially (extendable if require till satisfactory completion of work) as a security for ensuring/making good, excavated trench for laying gas pipeline/duct filling and compaction, clearing debris/loose earth produced due to execution of trenching at least 50m away from the edge of ROW. No payment shall be payable by NHAI to the licensee for clearing debris/loose earth. Performance BG as per above is to be obtained.	Security amount to be deposited in the form of Performance BG is calculated as per MoRT&H policy guidelines dt/.22.11.2016 and attached herewith.		14, 21- 30
4.1	Confirmation of BG has been obtained as per NH guidelines	Noted for compliance		
5	Affidavit / Undertaking from the Applicant for the following is to be furnished			
5.1	Not to Damage to other utility, if damaged then to pay the losses either to NH or to the concerned agency	Undertaking enclosed		9
5.2	Renewal of Bank Guarantee	Undertaking enclosed		4
5.3	Confirming all standard condition of NH's guideline and ministry circular	Undertaking enclosed		
5.4	Shifting of Natural gas pipeline as and when required by NHAI	Undertaking enclosed		4
5.5	Shifting of Natural gas pipeline due to 6 lanning / widening of NHAI	Undertaking enclosed		4
5.6	Indemnity against all damages and claims clause (xxiv)	Undertaking enclosed	*	13
5.7	Traffic movement during laying of Natural gas pipeline to be managed by the applicant.	Undertaking enclosed		5,6
5.8	If any claim is raised by the Concessionaire, then the same has to be paid by the applicant	Undertaking enclosed		9

O

RPORA

SRPL TUTICORIN

ltem	Information/ Status Remarks	Page No
Prior approval of NHAI shall be obtained before taking any work of installation, shifting or repair or alternative to Natural gas pipeline/any other utility located in national Highway ROW	Undertaking enclosed	5,8
Expenditure, if any, incurred by NHAI for repairing any damage cause to NH by the laying, maintenance or shifting of Natural gas pipeline borne by applicant agency owning the line.	Undertaking enclosed	9
If NHAI consider it necessary in future to move the utility line for any work of improvement or repairs to the road, it will be carried out as desired by the NHAI at the cost of agency owning utility line.	Undertaking enclosed	4,9
Certificate from applicant in following format 1. Laying of Natural gas pipeline will not having any deleterious effect on any of the bridge component and roadway safety of traffic. 2. "We do undertake that I/we will relocate	Enclosed	12
service road/approach road/utility at my own cost notwithstanding the permission granted within such time as will be stipulated by "NHAI" for future six laning or any other development work		
	Senior Manager (CGD) Thoothukudi	
Power of Attorney to sign the agreement is available or not.	Yes, enclosed	16
Certificate of conforming all standard condition issued vide Ministry of Road Transport and Highway, Circular no. NHAI-III/P/66/76 DATED 18/19.11.1976, RW/NH-III/P/66/76 DATED 11.05.1982, RW/NH-11037/1/86 DOI (ii) DATED 28.07.1993, RW/NH/34066/2/95/S&R DATED 25.10.1999 and Circular no. RW/NH-34066/7/2003/S&R(B) DATED 17.09.2003	Enclosed	12
Certificate from PD in following format a) "It is certified that any other location of the Natural gas pipeline would be extremely difficult and unreasonably costly and installation of Natural gas pipeline within ROW will not adversely affect the design, stability &traffic safety of the highway nor the likely future improvement such as widening the carriage way, easing the curve etc.	Yes	12
	Prior approval of NHAI shall be obtained before taking any work of installation, shifting or repair or alternative to Natural gas pipeline/any other utility located in national Highway ROW Expenditure, if any, incurred by NHAI for repairing any damage cause to NH by the laying, maintenance or shifting of Natural gas pipeline borne by applicant agency owning the line. If NHAI consider it necessary in future to move the utility line for any work of improvement or repairs to the road, it will be carried out as desired by the NHAI at the cost of agency owning utility line. Certificate from applicant in following format 1. Laying of Natural gas pipeline will not having any deleterious effect on any of the bridge component and roadway safety of traffic. 2. "We do undertake that I/we will relocate service road/approach road/utility at my own cost notwithstanding the permission granted within such time as will be stipulated by "NHAI" for future six laning or any other development work Who will sign the agreement on behalf of Natural gas pipeline agency Power of Attorney to sign the agreement is available or not. Certificate of conforming all standard condition issued vide Ministry of Road Transport and Highway, Circular no. NHAI-III/P/66/76 DATED 11.05.1982, RW/NH-11037/1/86 DOI (ii) DATED 18/19.11.1976, RW/NH-11037/1/86 DOI (ii) DATED 18.07.1993, RW/NH/34066/2/95/S&R DATED 11.05.1982, RW/NH-34066/2/95/S&R DATED 15.00.2003 Certificate from PD in following format a) "It is certified that any other location of the Natural gas pipeline would be extremely difficult and unreasonably costly and installation of Natural gas pipeline within ROW will not adversely affect the design, stability &traffic safety of the highway nor the likely future improvement such as widening the carriage way, easing the curve	Prior approval of NHAI shall be obtained before taking any work of installation, shifting or repair or alternative to Natural gas pipeline/any other utility located in national Highway ROW Expenditure, if any, incurred by NHAI for repairing any damage cause to NH by the laying, maintenance or shifting of Natural gas pipeline borne by applicant agency owning the line. If NHAI consider it necessary in future to move the utility line for any work of improvement or repairs to the road, it will be carried out as desired by the NHAI at the cost of agency owning utility line. Certificate from applicant in following format 1. Laying of Natural gas pipeline will not having any deleterious effect on any of the bridge component and roadway safety of traffic. 2. "We do undertake that I/we will relocate service road/approach road/utility at my own cost notwithstanding the permission granted within such time as will be stipulated by "NHAI" for future six laning or any other development work Who will sign the agreement on behalf of Natural gas pipeline agency Power of Attorney to sign the agreement is available or not. Certificate of conforming all standard condition issued vide Ministry of Road Transport and Highway, Circular no. NHAI-III/P/66/76 DATED 11.05.1932, RW/NH-110371/86 DOI (ii) DATED 28.07.1993, RW/NH-110371/86 DOI (ii) DATED 28.07.1993, RW/NH-110371/86 DOI (ii) DATED 28.07.1993, RW/NH-13076/67/67 DATED 11.05.1993 and Circular no. RW/NH-14066/7/2003/S&R(B) DATED 17.09.2003 Certificate from PD in following format a) "It is certified that any other location of the Natural gas pipeline within ROW will not adversely affect the design, stability &traffic safety of the highway nor the likely future improvement such as widening the carriage way, easing the curve

0

0

0

O

0

Ō

Ó

0

0

O

SRPL TUTICORIN

Project Director NHAI, Nagercoil

T. Yelgt

SI. No.	Item	Information/ Status	Remarks	Page No
	 i. Where feasibility is available "I do certify that there will be no hindrance to proposed 6-laning based of feasibility report considering proposed structures at the said location". ii. In case of feasibility not available "I do certify that sufficient ROW is available at site for accommodating proposed 6-laning" 			
8	If NH section proposed to be taken up by NHAI on BOT basis - a clause in para 17 to be inserted in the agreement. "The permitted Highway on which Licensee has been granted the ROW to the concessionaire under the concession agreement for up-gradation of (Section from Kmto Kmof NH NoOn Build, Operate and Transfer Basis) and therefore, the licensee shall honor the same."	Noted for compliance		
9	Who will supervise the work of laying Natural gas pipeline?	Control Manager (CCD) Through India		
	a) On behalf of applicant b) On behalf of NHAI	Senior Manager (CGD) Thoothukudi PIU/AE/IE		
10	Who will ensure that the defects in road portion after laying of Natural gas pipeline are corrected and if not corrected then what action will be taken. a) On behalf of applicant b) On behalf of NHAI	Yes Senior Manager (CGD) Thoothukudi PIU/AE/IE		
11	Who will pay the claims for damages done/disruption in the working of Concessionaire if asked by the Concessionaire?			
	On behalf of applicant	Senior Manager (CGD) Thoothukudi		
12	A certificate from PD that he will enter the proposed permission in the register of records of the permissions in the prescribed proforma (copy enclosed)	Enclosed		12
13	If any previous approval is accorded for laying of Natural gas pipeline, then Photocopy of register of records of permissions accorded as maintained by PD (copy enclosed).	NA		

RPORA

SRPL



SRPL TUTICORIN

^{அ'}**ளா**த்திகுளர் - 628 907

AGREEMENT FOR LAYING OF UNDERGROUND 10.75" OD STEEL, 125 MM MDPE AND HDPE PIPE ALONG WITH OFC ALONG NATIONAL HIGHWAY - NH -44 FROM CHAINAGE KM 133/349 TO KM 148/038 (RHS) AND FROM CHAINAGE KM 148/038 TO KM 159/442 (LHS), 8.625" OD STEEL PIPELINE WITH OFC FROM CHAINAGE KM 148/038 TO KM 150/000 (RHS), 4.5" STEEL PIPE WITH OFC FROM CHAINAGE KM 157/010 TO KM 157/341 (RHS) AND FROM KM 158/740 TO KM 159/342 (RHS), 10.75" OD STEEL PIPELINE WITH OFC ACROSS NH-44 AT CHAINAGE KM 148/038 AND 4.5" OD STEEL PIPELINE WITH OFC ACROSS NH-44 AT CHAINAGE KM 138/478, KM 157/341 AND KM 158/740 FOR INDIAN OIL CORPORATION LIMITED, CITY GAS DISTRIBUTION PROJECT, SOUTHERN REGION PIPELINES, THOOTHUKUDI

Agreement to lay Underground 10.75" Steel, 125mm MDPE and 89mm OD HDPE pipe along with OFC National Highway NH -44 from Chainage KM 133/349 to KM 148/038 (RHS) and from Chainage M 148/038 to KM 159/442 (LHS), 8.625" Steel Pipe With OFC from Chainage KM 148/038 to KM 150/000 km, 4.5" Steel Pipe With OFC From Chainage KM 157/010 to KM 157/341 (RHS) and from KM 158/740 to KM 159/342, 10.75" OD Steel Pipeline with OFC Across NH-44 at Chainage KM 148/038, and 4.5" Steel Pipe across NH-44 at Chainage KM 138/478, KM 157/341 and KM 158/740 for Indian Oil Corporation Limited, Southern Region Pipelines Thoothukudi City Gas Distribution project, by Open Cut method and HDD Technique wherever applicable.

AN AGREEMENT made this...... day of.....month of..... Between the NATIONAL HIGHWAYS AUTHORITY OF INDIA (hereinafter called the "Authority" which expression shall, unless excluded by or repugnant to the context, include his successors in office and assigns of the one part and INDIAN OIL CORPORATION LIMITED, SOUTHERN REGION PIPELINES, THOOTHUKUDI (hereinafter called the 'Licensee' which expression shall, unless excluded by or repugnant to the context, include his successors/ administrator assignees on the second Part.

WHEREAS, the Authority is responsible, inter-alia, for development and maintenance of lands in increasing Chainage KM 133/349 to KM 148/038 (RHS) and from Chainage Km 148/038 to Km 159/442 (LHS).

WHEREAS, the licensee proposes to lay 10.75" Steel, 8.625" Steel, 4.5" Steel & 125mm MDPE and 89mm HDPE Pipelines along with OFC cable referred to as utility services in subsequent paras. Whereas the licensee has applied to the Authority for permission to lay 10.75" OD Steel Pipe along NH-44 Chainage KM 133/349 to KM 148/038 (RHS) and from Ch. KM 148/038 to KM 159/442 (LHS), 8.625" OD Steel pipe along NH-44 from Chainage KM 148/038 to KM 150/000 (RHS), 4.5" Steel Pipe With OFC From Chainage KM 157/010 to KM 157/341 (RHS) and from Chainage KM 158/740 to KM 159/342 (RHS), 10.75" OD steel pipeline with OFC across NH-44 at chainage km 148/038 and 4.5" Steel pipe across NH-44 at Chainage KM 138/489, KM 157/341 and KM 158/740 for City gas distribution (CGD) project.

AND WHEREAS, the Authority has agreed to grant such permission for way leave on the NH RoW as per terms and conditions hereinafter mentioned.

0

0

Ō

0

0

0

0

0

Ó

0

0

0

Now this Agreement witness that, in consideration of the conditions hereinafter contained and on the part of the Licensee to be observed and performed, the Authority hereby grants to the licensee permission to lay utility services (underground Natural gas steel pipeline for City gas distribution network) as per the approved drawing attached hereto subject to the following conditions,namely;-

- 1. RoW permissions are only enabling in nature. The purpose of extending the way leave facility on National Highway RoW is not for enhancing the scope of activity of a utility service provider, either by content or by intent. Further, enforceability of the permission so granted shall be restricted only to the extent of provisions/scope of activities defined in the license agreement and for the purpose for which it is granted.
- 2. No licensee shall claim exclusive right on the Row and any subsequent user will be permitted to use the RoW, either above or below or by side of the utilities laid by the first user subject to technical requirements being fulfilled. Decision of the Authority in relation to fulfillment of technical requirements shall be final and binding on all concerned parties. In case any disruption/damage is caused to any existing user by the subsequent user, the Authority shall not be held accountable or liable in any manner.
- 3. The Licensee shall be responsible for undertaking all activities including but not limited to site identification, survey, design, Engineering, arranging finance, Project Management, obtaining regulatory approvals & necessary clearances, supply of equipment, material, construction, erection, testing and commissioning, maintenance and operation and all other activities essential or required for efficient functioning of their own utility/industrial infrastructure facilities.
- 4. The licensee shall pay license fees @ Rs_____/sqm/Month to the Authority. The license fee shall become payable from the date of handing over of RoW land the Licensee, for laying of utilities/ Cables/Conduits/pipelines for infrastructure/service provider. As regards Tariff and Terms and conditions for providing common utility ducts along National highways, there shall be separate agreement regime.

TUTICORIN

- 5. Fee shall have to be paid in advance for the period for which permission is granted for entering in to a license agreement. In case of renewal, rate prevailing at the time of renewal shall be charged. Delay in deposition of fee shall attract interest @ 15% per annum compounded annually.
- 6. Present policy of the MoRT&H is to provide a 2.00m wide utility corridor on either side of the extreme edge of RoW. In cases where utility ducts with sufficient space are already available along NH, The utility services shall be laid in such ducts subject to technical requirements being fulfilled.

0

0

0

0

0

0

0

0

0

0

Ö

0

0

Ō

Ö

0

Ō

0

0

1

0

- 7. The utility services shall be laid at the edge of the RoW. In case of restricted width of RoW, which may be adequate only to accommodate the carriage way, central verge, shoulders, slopes of embankment, drains, other road side furniture etc: the utility services shall be laid beyond the toe line of the embankments and clear of the drain.
- 8. The Licensee shall make his own arrangement for crossing of cross drainage structures, rivers, etc. below the bed. In case this is not feasible, the utility services may be carried outside the railings/parapets and the bridge superstructure. The fixing and supporting arrangement with all details shall be required to be approved in advance from the concerned Highway Administration. Additional cost on account of fixing and supporting arrangement as assessed by the Authority shall be payable by the licensee.
- 9. In exceptional case where RoW is restricted the utility services can be allowed beneath the carriage way of the service road if available, subject to the condition that the utility services be laid in concrete ducts, which shall be designed to carry traffic on top. The width of the duct shall not be less than one lane. In such cases, it is also needs to ensure the maintenance of the utility services shall not interfere with the safe and smooth flow of traffic. The cost of operation and maintenance will have to be borne by the Licensee.
- 10. It is to be ensured that at no time there is interference with drainage of the road land and maintenance of the National Highways. Towards this the top of the utility services shall be at least 0.6 meter below the ground level. However, any structure above ground shall be aesthetically provided for /landscaped with required safety measures as directed by the concerned authority.
- 11. The utility services shall be permitted to cross National Highways wither through structure or conduits specially built for that purpose. The casing/ conduit pipe should, as minimum extend from drain to drain in cuts and toe of slope to toe of slope in the fills and shall be designed in accordance with the provision of IRC and executed following the specifications of Ministry.
- 12. Existing drainage structures shall not be allowed to carry the lines across.

SRPL

- 13. The top of the casing/conduit pipe containing the utility services to cross the road shall be at least 1.2m below the top of the subgrade or the existing ground level whichever is lower subject to being at least 0.3m below the drain inverts. A typical sketch showing the clearances is given in the attachment-I.
- 14. The utility services shall cross the National Highway preferable on a line normal to it or as nearly as practicable.

- 15. The casing/conduit pipe for crossing the road may be installed under the road embankment either by boring or digging a trench. Installation by boring method shall be preferred.
- 16. In case of trenching the sides of the trench should be done as nearly vertical as possible. The trench width should be at least 30cm but not more than 60cms wider than the outer diameter of pipe. Filling of the trench shall conform to the specifications contained herein below or as supplied by the Highway Authority.

0

0

0

0

0

0

0

0

0

0

Ö

0

0

O

Ó

O

0

- a. Bedding shall be to a depth not less than 30 cm. It shall consist of granular material free of lumps clods and cobbles and graded to yield a firm surface without sudden change in the bearing value. Unsuitable soil and rock edges should be excavated and replaced by selected material.
- b. The backfill shall be completed in two stages (1) side fill to the level of the top of the pipe (2) overfill to the bottom of the road crust.
- c. The side fill shall consist of granular material laid in 15cm. Layers each consolidated by mechanical tamping and controlled addition of moisture to 95% of Proctor density. Overall shall be compacted to the same density as a material that has been removed consolidation by saturation or ponding will not be permitted.
- d. The road crust shall be built to the same strength as the existing crust on either side of the trench or to thickness and specifications stipulated by the highway authority
- 17. The licensee shall ensure making good the excavated trench for laying utility services by the proper filling and compaction, so as to restore the land in to the same condition as it was before digging the trench, clearing debris/ loose earth produced due to execution of trenching at least 50m away from the edge of the right of way
- 18. All required restoration work subsequent to laying of the cable shall be required to be undertaken by the licensee at its cost either by itself or through its authorized representative in consultation with the authority as per predetermined time schedule and quality standards.
- 20. In case, the Performance Bank Guarantee is invoked as mentioned above, the Licensee shall be required to replenish and reinstate the required Performance Bank Guarantee within one month of such invoking. In case the work contemplated herein is not completed to the satisfaction of the Authority, which has granted the permission, within a period of one year from the date of issue of the Bank Guarantee, the licensee shall either furnish a fresh guarantee or extend the guarantee for a further period of one year. Notwithstanding this, the licensee shall be liable to pay full compensation to the aggrieved Authority/ its designated agency for any damage sustained by them by reason of the exercise of the RoW facility.

SRPL

TUTICORIN

21. The licensee shall shift the utility service within 90days (or as specified by the respective Authority) from the date of issue of the notice by the concerned authority to shift/ relocate the utility services, in case it is so required for the purpose of improvement/ widening of the road/ route/ highway or construction of flyover/ bridge and restore the road/ land to its original conditions at his own cost and risk.

0

0

0

0

0

0

0

0

0

0

Ö

0

0

0

0

Ō

0

0

Ō

£ ...

0

Ō

0

- 22. The Licensee shall be responsible to ascertain from the respective agency in coordination with Authority, regarding the location of other utilities/ underground installations/ facilities etc. The Licensee shall ensure the safety and security of already existing underground installations/ utilities/ facilities etc. before commencement of the excavation/ using the existing cable ducts. The Licensee shall procure insurance from a reputed insurance company against damages to already existing underground installations/ Utilities/ facilities etc.
- 23. The Licensee shall be solely responsible/ liable for full compensation/ indemnification of concerned agency/ aggrieved Authority for any direct, indirect or consequential damage caused to them/ claims or replacements sought for, at the cost and risk of the Licensee. The concerned agency in coordination with Authority shall also have a right make good such damages/ recover the claims by forfeiture of Bank Guarantee.
- 24. If the Licensee fails to comply with any condition to the satisfaction of the Authority, the same shall be executed by the Authority at the cost and risk of the Licensee.
- 25. Grant of License is subject to the Licensee satisfying (a) minimum disruption of traffic and (b) no damage to the highways. As far as possible, the Licensee should avoid cutting of the road for crossing highway, and other roads and try to carry out the work by trenchless technology. In case any damage is caused to the road pavement in this process, the Licensee will be required to restore the road to the original condition at its cost. If due to unavoidable reasons the road needs to be cut for crossing or laying utility services, the Licensee has to execute the restoration work in a time bound manner at its cost either by itself or through its authorized representative in consultation with the Authority as per predetermined time schedule and quality standards. In case of the Licensee failing to discharge the obligation of making good of the damages caused by excavation, at the cost of the Licensee and recover the amount by forfeiture of the Bank Guarantee.
- 26. The Licensee shall inform/ give a notice to the concerned agency designated by the authority atleast 15day in advance with route details prior to digging trenches, for fresh or maintenance/ repair works. A separate Performance Bank Guarantee for maintenance/ repair works shall have to be furnished by the licensee.
- 27. Each day the extent of digging the trenches should be strictly regulated so that utility services is laid and trenches filled up before the close of the work that day. Filling should be completed to the satisfaction of the concerned agency designated by the authority.
- 28. The Licensee shall indemnify the concern agency in coordination with Authority against all damages and claims if any due to the digging of trenches for laying cables/ ducts.
- 29. The Permission for laying utility services is granted maximum for 5 years at a time, which can thereafter be considered for renewal. On payment of additional fee at the time of renewal, the permission shall automatically be renewed, unless default exits. In case of renewal, rate prevailing

SRPL TUTICORIN

- at the time of renewal shall be charged. Delay in deposition of fee shall attract interest @15% per annum compounded annually.
- 30. The permission shall be valid only for the period it is issued and fee deposited. However, the Authority also has a right to terminate the permission or to extend the period of Agreement.
- 31. That the Licensee shall not undertake any work of shifting, repairs or alterations to the utility services without prior written permission of the concerned agency in coordination with the Authority.
- 32. The permission granted shall not in any way be deemed to convey to the Licensee any ownership right or any interest in route/ road/highway land/ property, other than what is herein expressly granted. No use of NH RoW will be permitted for any other than that specified in the Agreement.
- 33. During the subsistence of this Agreement, the utility services located in highway land/ property shall be deemed to have been constructed and continued only by the consent and permission of the Authority so that the right of the licensee to the use thereof shall not become absolute and indefeasible by lapse of time.
- 34. The Licensee shall bear the stamp duty charged on this agreement.

0

0

0

0

0

0

0

0

0

0

0

0

0

0

0

- 35. Three copies of "as laid drawings" of the utilities (hard and soft copies) with geo-tagged photographs and geo-tagged video recordings of laying of cables in the trench (with respect to NH) and after complete restoration shall be submitted to the Authority for verification and record within a month of completion of works.
- 36. The Licensee shall allow the free access to the Site at all times to the authorized representatives of Authority to inspect the project facilities and to investigate any matter within their Authority, and upon reasonable notice, shall provide reasonable assistance necessary to carry out their respective duties and functions.
- 37. The utility services shall not be made operational by the Licensee unless a completion certificate to the effect that the utility services has been laid in accordance with the approved specifications and drawings and the trenches have been filled up to the satisfaction of the concerned agency in coordination with the Authority has been obtained. Notwithstanding anything contained herein, this agreement may be cancelled at any time by the Authority for the breach of any condition of the same and the Licensee shall neither be entitled to any compensation for any loss caused to it by such cancellation not shall it be absolved from any liability already incurred
- 38. The Licensee shall ensure adherence to relevant Indian Standards and follow the best industry practices, methods and standards for the purpose of ensuring the safe, efficient and economic design, construction, commissioning, operation, repair and maintenance of any part of the utility lines/Industrial infrastructure facilities and which practices, methods and standards shall be adjusted as necessary to take account of
 - a) Operation, repair and maintenance guidelines given by the manufacturers,
 - b) The requirements of Law

SRPL

TUTICORIN

- c) The physical conditions at the site and
- d) The Safety of operating personnel and human beings.
- 39. The Licensee shall have to provide safety measures like barricading, danger lighting and other necessary caution boards while executing the work.

- 40. While laying utility services, at least one lane of road shall be kept open to traffic at all times. In case of single lane roads, a diversion shall be constructed. If any traffic diversion works are found necessary during the working period such diversion shall be provided at the cost of the Licensee.
- 41. After the termination /expiry of the agreement, the Licensee shall remove the utility services within 90 days and the site shall be brought back to the original condition failing which the Licensee will lose the right to remove the utility services. However before taking up the work of removal of the utility services the Licensee shall furnish a Bank guarantee to the Authority for a period of one year for an amount assessed by the Authority as a security for making good the excavated trench by proper filling and compaction, clearing debris, loose earth, produced due to excavation of trenching at least50m away from the edge of the RoW.

0

0

0

00000000

2.

- 42. Any disputes in interpretation of the terms and conditions of this agreement or their implementation shall be referred to the redress mechanism prevailing in the Ministry and the decision of the redress mechanism shall be final and binding on all.
- 43. For PPP projects, in case of any loss incurred by the respective project concessionaries due to such laying/shifting of utility services by the licensee, compensation for the same shall be required to be borne by the licensee in mutual agreement with the respective project concessionaries. MoRT&H/NHAI/implementing authorities for the project shall not be liable to the concessionaire in any way in this regard.

This agreement has been made in duplicate on a stamp paper, Each party to this agreement has retained one stamped copy each.

IN WITNESS WHEREOF THE PARTIES HERETO HAVE CAUSED THIS AGREEMENT TO BE EXECUTED THROUGH THEIR RESPECTIVE AUTHORISED REPRESENTATIVES THE DAY AND THE YEAR FIRST ABOVE WRITTEN.

SIGNED SEALED AND DELIVERED FOR ON BEHALF OF AUTHORITY.

BY SHRI	
SIGNED ON BEHALF OF M/s INDIA OIL CORPORATION LIMITE BY SHRI RANJITH KUMARIN	ED (LICENSEE) PANJÎTH KUMAR N बरिष्ठ प्रबंचक क्षांजींडी) / Senior Manager (CGD) इंडियन ऑयल कॅापोरेशन लिमिटेड Indian Oil Corporation Limited Southern Region Pipelines City Gas Distribution Project, 1st Floor (South) J.J.Centre, 4/7/5, Ettayapuram Road, Tuticorin - 628 002. TN
HOLDER OF GENERAL POWER OF ATTORNEY DATED	4///5, Ettayapuran Troat, Totalorin 555 555
EXECUTED IN ACCORDANCE WITH RESOLUTION NO	DATED
PASSED BY THE BOARD OF DIRECTORS IN THE MEETING HEI	LD ON
IN THE PRESENCE OF (WITNESS):	2



தமிழ்நாடு तमिलनाडु TAMILNADU 11 DEC 2024 EY 217122
பா. கீவானந்தம்
முத்திரைத்தாள் விற்பனையாளர்
உரிமம் எண். 11/தூழ்/2008
பாக்கிகளம் - 628 907

UNBERTAKING FOR LAYING OF UNDERGROUND 10.75" OD STEEL, 125 MM MDPE AND HDPE PIPE ALONG WITH OFC ALONG NATIONAL HIGHWAY – NH -44 FROM CHAINAGE KM 133/349 TO KM 148/038 (RHS) AND FROM CHAINAGE KM 148/038 TO KM 159/442 (LHS), 8.625" OD STEEL PIPELINE WITH OFC FROM CHAINAGE KM 148/038 TO KM 150/000 (RHS), 4.5" STEEL PIPE WITH OFC FROM CHAINAGE KM 157/010 TO KM 157/341 (RHS) AND FROM KM 158/740 TO KM 159/842 (RHS), 10.75" OD STEEL PIPELINE WITH OFC ACROSS NH-44 AT CHAINAGE KM 148/038 AND 4.5" OD STEEL PIPELINE WITH OFC ACROSS NH-44 AT CHAINAGE KM 138/478, KM 157/341 AND KM 158/740 FOR INDIAN OIL CORPORATION LIMITED, CITY GAS DISTRIBUTION PROJECT, SOUTHERN REGION PIPELINES, THOOTHUKUDI

Indian Oil Corporation Limited, Pipelines Division, City Gas Distribution, Thoothukudi shall be responsible for safety of all other underground facilities, such as electric lines, pipe of water supply and gas sewage lines etc., during trenching.

- The Indian Oil Corporation Limited, Pipelines Division, City Gas Distribution, Thoothukudi shall inform the concerned officer of NHAI appointed at least 15 days in advance before starting of work.
- 2. The Indian Oil Corporation Limited, Pipelines Division, City Gas Distribution,
- Thoothukudi shall not, without the prior permission in writing to the concerned officer of NHAI undertake any work of shifting, repairs, or alternations to the laid utilities.



- 3. NHAI shall not be responsible for any damage caused to the underground CGD pipeline or by any activity of NHAI on the permitted highway. The parties are agreed that the Indian Oil Corporation Limited, Pipelines Division, City Gas Distribution, Thoothukudi is laying underground CGD Natural Gas pipeline across the permitted highway at its own cost.
- 4. The Indian Oil Corporation Limited, Pipelines Division, City Gas Distribution, Thoothukudi shall make good, excavated trench for laying underground CGD Natural Gas pipeline by proper filling and compaction, so as to restore the land in the same condition as it was before digging trench and shall clear the debris /loose earth produced from the execution of trenching to the satisfaction of NHAI.
- 5. In any accident that occurs during the execution or completion of work by the agency, the complete responsibility will be fully on the head or agency.
- 6. The Indian Oil Corporation Limited, Pipelines Division, City Gas Distribution, Thoothukudi agrees to abide by the directions of the concerned officer of NHAI appointed in accordance with the National Highways act 1956 and rules in force.
- 7. We do undertake that we will relocate service/ approach road/ utilities at our own cost notwithstanding the permission granted within such times as will be stipulated by NHAI.
- 8. Indian Oil Corporation Limited, Pipelines Division, City Gas Distribution, Thoothukudi agrees not to damage to other utility. If damages, then to pay losses either to NHAI or to the concerned agency.
- 9. We do indemnity against all damages.

0

0

- 10. We do if any claim is raised by the concessionaire, then the same has to be paid by the applicant.
- 11. We do expenditure, if any incurred by NHAI for repairing any damage caused to the NHAI by the laying, maintenance or shifting of the underground CGD Natural Gas pipeline will be borne by the agency owning the line.
- 12. Indian Oil Corporation Limited, Pipelines Division, City Gas Distribution, Thoothukudi agrees if the NHAI considers it is necessary in future to move the utility line for any work of improvement or repairs to the road, it will be carried out as desired by the NHAI at the cost of the agency owning the utility line within a reasonable time (not exceeding 60 days) of the intimation given.

TUTICORIN

- 13. Laying of underground CGD Natural Gas pipeline will not have deleterious effects of any of the bridge components and roadway safety for traffic.
- 14. For 6-laning "we do undertake that I will relocate service road/approach road /utilities at my own cost notwithstanding the permission granted within such time as will be stipulated by NHAI for future six laning or any other development".

0

0

0

0

Ō

0

- 15. All the restoration work will be carried out by Indian Oil Corporation Limited, Southern Region Pipelines, City Gas Distribution, Thoothukudi up to the satisfaction of NHAI.
- 16. The Licensee shall make his own arrangement for crossing of cross drainage structures, rivers, etc. below the bed. In case this is not feasible, the utility services may be carried outside the railings/parapets and the bridge superstructure. The fixing and supporting arrangement with all details shall be required to be approved in advance by the concerned Highway Administration. Additional cost on account of fixing and supporting arrangement as assessed by the Authority shall be payable by the licensee.

ORPORA

SRPL

(Ranjith Kumar N) enior Manager (CGD), Thoothukudi



தமிழ்நாடு तमिलनाडु TAMILNADU 9 1 DEC 2024

EY 217112

பா. கீவானந்தம் முத்திரைத்தாள் விற்பகையாளர் உரிமம் எண். 11/தூடி/2008 இது சிராத்திதளம் - 628 907

UNDERTAKING FOR LAYING OF UNDERGROUND 10.75" OD STEEL, 125 MM MDPE AND HDPE PIPE ALONG WITH OFC ALONG NATIONAL HIGHWAY – NH -44 FROM CHAINAGE KM 133/349 TO KM 148/038 (RHS) AND FROM CHAINAGE KM 148/038 TO KM 159/442 (LHS), 8.625" OD STEEL PIPELINE WITH OFC FROM CHAINAGE KM 148/038 TO KM 150/000 (RHS), 4.5" STEEL PIPE WITH OFC FROM CHAINAGE KM 157/010 TO KM 157/341 (RHS) AND FROM KM 158/740 TO KM 159/342 (RHS), 10.75" OD STEEL PIPELINE WITH OFC ACROSS NH-44 AT CHAINAGE KM 148/038 AND 4.5" OD STEEL PIPELINE WITH OFC ACROSS NH-44 AT CHAINAGE KM 138/478, KM 157/341 AND KM 158/740 FOR INDIAN OIL CORPORATION LIMITED, CITY GAS DISTRIBUTION PROJECT, SOUTHERN REGION PIPELINES, THOOTHUKUDI

We here by undertake that we will pay necessary fees/rent as and when required by the NHAI as per their Circular No 33044 / 29 / 2015 /S&R(R) dated 22.11.2016 without any delay.

(Ranjith Kumar N) Senior Manager (CGD), Thoothukudi

Page | 11



தமிழ்நாடு तमिलनाडु TAMILNADU

EY 217119

day oil Contertificate DEC 2024

பா. சிவானந்தம்

Name of the Work: Laying of Underground 10.75" Steel, 125mm MDE and solling of Underground 10.75" Steel, 125mm MDE and solling of Mary / 2008. HDPE pipe along with OFC National Highway NH -44 from Chainage RM 123/349 to RM 2008. 148/038 (RHS) and from Chainage KM 148/038 to KM 159/442 (LHS), 8.225 to seel 628 907 pipeline with OFC from Chainage KM 148/038 to KM 150/000 (RHS), 4.5" Steel Pipe With OFC From Chainage KM 157/010 to KM 157/341 (RHS) and from KM 158/740 to km 159/342 (RHS), 10.75" OD steel pipeline with OFC across NH-44 at chainage KM 148/038 and 4.5" Steel Pipe across NH-44 at Chainage KM 138/478, KM 157/341 and KM 158/740 for Indian Oil Corporation Limited, City Gas Distribution project, Southern Region Pipelines Thoothukudi, by Open Cut method and HDD Technique wherever applicable.

This proposal when implemented will not affect the design, stability and traffic safety of Highway.

- 1. This proposal if implemented now will not affect any likely further improvement to Geometric.
- 2. The proposal is in accordance with the Specification laid down by the Ministry of Surface Transport, vide Lr. No. RW/ NH-33041/17/2000 SNR /dated 29.09.2000 without making any inconvenience for the traffic through the road.
- 3. Certificate to effect that they have inspected the site and there will not be any hindrance for the NH Road for further Developments.

(Ranjith Kumar N) Semor Manager (CGD), Thoothukudi



தமிழ்நாடு तमिलनाड् TAMILNADU

டு तमिलनाडु TAMILNADU

1 1 DEC 2024 பா. ஃவானந்தம்
முத்திரைத்தாள் விற்பனையாளர்
முத்திரைத்தாள் விற்பனையாளர்
மூற்றி கண்ட 11/தூடி/2008 **** வாக்கிகளம் - 626** 907

INDEMNITY BOND

Name of the Work: Laying of Underground 10.75" Steel, 125mm MDPE and 89mm OD HDPE pipe along with OFC National Highway NH -44 from Chainage KM 133/349 to KM 148/038 (RHS) and from Chainage KM 148/038 to KM 159/422 (LHS), 8.625" OD steel pipeline with OFC from Chainage KM 148/038 to KM 150/000 (RHS), 4.5" Steel Pipe With OFC From Chainage KM 157/010 to KM 157/341 (RHS) and from KM 158/740 to km 159/342 (RHS). 10.75" OD steel pipeline with OFC across NH-44 at chainage KM 148/038 and 4.5" Steel Pipe across NH-44 at Chainage KM 138/478, KM 157/341 and KM 158/740 for Indian Oil Corporation Limited, City Gas Distribution project, Southern Region Pipelines, Thoothukudi.

Indemnity against all damages and Claims

We Indian Oil corporation, Pipelines division, Thoothukudi or in do hereby Indemnity Project director, NHAI, PIU, binding ourselves to the all the losses and claims in respect of laying 10.75" Steel, 8.625" Steel, 4.5" Steel, 125mm MDPE, 89mm HDPE pipes along with OFC pipeline by IOCL along NH-44

Or maintenance, thereof and against all claims, proceedings damages, Costs, Charges and expenses whatsoever in respect thereof, in relation there to, failing such payments of claims in the above work, we abide in accepting for recovery of such claims affected from any of our assets.

> TICOR (Ranjith Kumar N) Senior Manager (CGD), Thoothukudi.

Page | 13

l		
	fomance BG calculated in line with the MoRT&H policy guidelines dt/.22.11.2016 for 26.073 km stretch	along/arross NH44 from Chainage 133/349 to 159/422 as detailed below:
	Perf	
	int as	
	urity Amou	
	Secu	

S No Description From Eron Chainage To Total Rate per m in ₹ Amount in Amount on account of Restoration (in ₹) Amount in Amount on account of Restoration (in ₹) Amount in Amount on account of Restoration (in ₹) Amount in Amount on account of Restoration (in ₹) Amount in Amount on account of Restoration (in ₹) Amount in Amount on account of Restoration (in ₹) Amount in Amount on account of Restoration (in ₹) Amount in Amount on account of Restoration (in ₹) Amount in Amount on account of Restoration (in ₹) Amount in Amount on account of Restoration (in ₹) At 1.332.280.00 At 1.333.28.80.00 At 1.333.28.80.00 At 1.333.28.80.00 At 1.333.28.80.00 At 1.333.28.8			5					
NH44 - Ch. 133/349 (M/s NH44 - Ch. 159/422 (NH-138 & Along the Road Annual Indian Oil Petrol NH44 - Ch. 159/422 (NH-138 & Along the Road Annual Indian Oil Petrol NH44 - Ch. 159/000 (Near NH44 - Ch. 138/038 (Near NH44 - Ch. 157/010 (Near Along the Road Sankar Nagar) NH44 - Ch. 157/010 (Near Along the Road Annual Petrol NH44 - Ch. 157/010 (Near Along the Road Flyover towards Sivalaperi Road) NH44 - Ch. 158/740 (Near Sivalaperi Road) NH44 - Ch. 158/740 (Near Sivalaperi Road) NH44 - Ch. 158/740 (NH-138 NH44 - Ch. 158/740 (NH-138 NH44 - Ch. 158/740 (NH-138 NH44 NH44	1		Cha	inage	Moll	Total	Rate per m	# C:
Along the Road NH44 - Ch. 139/429 (W/5 NH44 - Ch. 159/422 (NH+138 & Nh44 - Ch. 139/429 (NH+138 & Nh44 - Ch. 148) (NH+44 Junction Point Near KTC Nh44 - Ch. 148) (Nh44 - Ch. 157) (Nh44 - Ch. 148) (Nh44	2 140	Describtion	From	То	OOIN	Length	in₹	
Along the Road Chandru Indian Oil Petrol NIH-44 Junction Point Near KIC Meter 26,093 1000 Along the Road Bunk, Gangaislondan Nagar, Tirunelveli NH44 - Ch. 132/0000 (Near NH44 - Ch. 157/0010 (Near NH44 - Ch. 158/740 (Near NH44 NH44 Ch. 158/740 (Near NH44 C			NH44 -Ch. 133/349 (M/s	NH44 - Ch. 159/422 (NH-138 &			9	
Along the Road NH44 - Ch. 148/038 (Near Thalaiyuthu Roundabout) NH44 - Ch. 148/038 (Near Along the Road Sankar Nagar) Thalaiyuthu Roundabout) NH44 - Ch. 157/010 (Near Road) Phyover towards Sivalaperi Road) NH44 - Ch. 158/740 (Near Road) Road) NH44 - Ch. 158/740 (NH4 - Ch. 159/342 (Near Road) NH44 - Ch. 158/740 (NH44 + Ch. 158/341 (NH 44 towards Tirunelveli) Meter 60 100 Across the Road At Ch. 158/740 (NH+138 & NH+44 Junction Point towards NH44 NH44 Punction Point towards NH44 NH44	Н	Along the Road	Chandru Indian Oil Petrol Bunk, Gangaikondan)	NH-44 Junction Point Near KTC Nagar, Tirunelveli)	Meter	26,093	100	₹ 26,09,300.00
Along the Road Sankar Nagar) Thalaiyuthu Roundabout) Meter 1,362 100 Along the Road Flyover towards Sivalaperi Riyover towards Sivalaperi Meter 60 100 Across the Road At Ch. 148/038(NH-44 towards Sankarankovil) Meter 60 100 Across the Road At Ch. 157/341 (NH 44 towards Sankarankovil) Meter 60 100 Tirunelvell) Tirunelvell) Amount towards total running meter (in ₹) Charges for Crosing NH-44 @ 138/478, 148/038, 157/341, 158/740 (in ₹) Contage Charges @ 23.5.% (in ₹) Total Amount on account of Restoration including Centage Charges (in ₹) Total Amount on account of Restoration including Centage Charges (in ₹) Total Amount on account of Restoration including Centage Charges (in ₹) Total Amount on account of Restoration including Centage Charges (in ₹) Total Amount on account of Restoration including Centage Charges (in ₹) Total Amount on account of Restoration including Centage Charges (in ₹) Total Amount on account of Restoration including Centage Charges (in ₹) Total Amount on account of Restoration including Centage Charges (in ₹) Total Amount on account of Restoration including Centage Charges (in ₹) Total Amount on account of Restoration including Centage Charges (in ₹) Total Amount on account of Restoration including Centage Charges (in ₹) Total Amount on account of Restoration including Cen			NH44 -Ch. 148/038 (Near	NH44 - Ch. 150/000 (Near				
Along the Road Rivover towards Sivalaperi Riyover towards Sivalaperi Road Road Road Road Road Road Road Road Road Across the Road At Ch. 138/478(M/s Deepam Agencies, Indian Oil Petrol Bunk, Meter 60 100 Across the Road At Ch. 148/038(NH-44 towards Tirunelveli) Meter 60 100 Across the Road At Ch. 158/740 (NH-138 & NH-44 Junction Point towards Tirunelveli) Across the Road At Ch. 158/740 (NH-138 & NH-44 Junction Point towards Tirunelveli) Across the Road At Ch. 158/740 (NH-138 & NH-44 Junction Point towards Tirunelveli) Across the Road At Ch. 158/740 (NH-138 & NH-44 Junction Point towards Tirunelveli) Across the Road At Ch. 158/740 (NH-138 & NH-44 Junction Point towards Total Amount on account of Restoration (in ₹) Charges for Crosing NH-44 @ 138/478, 148/038, 157/341, 158/740 (in ₹) Charges for Crosing NH-44 @ 138/478, 148/038 & (in ₹) Charges for Crosing NH-44 @ 23.5 % (in ₹) Charges Carage Charges (in ₹) Charges Carage Charges (in ₹) Charge Charges (in ₹) Charges (in ₹) Charge Charges (in ₹) Charges (in ₹) Charge Charges (in ₹) Charge Charges (in ₹) Charges (in	7	Along the Road	Sankar Nagar)	Thalaiyuthu Roundabout)	Meter	1,962	100	₹ 1,96,200.00
Along the Road Flyover towards Sivalaperi Road) Road Road Road At Ch. 138/478(M/s Deepam Agencies, Indian Oil Petrol Bunk, Gangaikondan) Across the Road At Ch. 148/038(NH-44 towards Tirunelveli) Meter 60 100 Across the Road At Ch. 157/341 (NH 44 towards Sankarankovil) Meter 60 100 Across the Road At Ch. 158/740 (NH-138 & NH-44 Junction Point towards Meter 60 100 Across the Road At Ch. 157/341 (NH 44 towards Sankarankovil) Meter 60 100 Across the Road At Ch. 158/740 (NH-138 & NH-44 Junction Point towards Tirunelveli Amount towards total running meter (in ₹) Across the Road At Ch. 158/740 (NH-138 & NH-44 Junction Point towards Total Amount towards total running meter (in ₹) Charges for Crosing NH-44 @ 138/478, 148/038, 157/341, 158/740 (in ₹) Centage Charges @ 23.5 % (in ₹)			NH44- Ch. 157/010 (Near	NH44- Ch. 157/341 (Near				
Road) Road NH44-Ch. 158/740(Near NH44-Ch. 159/342(Near Road Flyover towards Sivalaperi Flyover towards Sivalaperi Flyover towards Sivalaperi Road Houser towards Sivalaperi Flyover towards Sivalaperi Road At Ch. 138/478(M/s Deepam Agencies, Indian Oil Petrol Bunk, Meter 60 100	m	Along the Road	Flyover towards Sivalaperi	Flyover towards Sivalaperi	Meter	331	100	₹ 33,100.00
Across the Road Road At Ch. 138/740(Near Gangaikondan) Road At Ch. 138/478(M/s Deepam Agencies, Indian Oll Petrol Bunk, Gangaikondan) Meter Good 100 Across the Road At Ch. 148/038(NH-44 towards Tirunelveli) Meter Good 100 Across the Road At Ch. 157/341 (NH 44 towards Sankarankovil) Meter Good 100 100 Across the Road At Ch. 157/341 (NH 44 towards Sankarankovil) Meter Good 100 1			Road)	Road)				
Along the Road Flyover towards Sivalaperi Road of Road) Across the Road At Ch. 138/478(M/s Deepam Agencies, Indian Oil Petrol Bunk, Meter 60 100 Across the Road At Ch. 148/038(NH-44 towards Tirunelveli) Meter 60 100 Across the Road At Ch. 157/341 (NH 44 towards Sankarankovil) Meter 60 100 Across the Road At Ch. 157/341 (NH 44 towards Sankarankovil) Meter 60 100 Across the Road At Ch. 158/740 (NH-138 & NH-44 Junction Point towards Sankarankovil) Amount towards total running meter (in ₹) Charges for Crosing NH-44 @ 138/478, 148/038, 157/341, 158/740 (in ₹). Charges for Crosing NH-44 @ 138/478, 148/038, 157/341, 158/740 (in ₹). Charges Charges Charges @ 23.5 % (in ₹) Contage Charges Charges (a 23.5 % (in ₹)			NH44- Ch. 158/740(Near	NH44- Ch. 159/342(Near				
Across the Road At Ch. 138/478(M/s Deepam Agencies, Indian Oil Petrol Bunk, Gangalkondan) Meter 60 100 Across the Road At Ch. 148/038(NH-44 towards Tirunelveli) Meter 60 100 Across the Road At Ch. 157/341 (NH 44 towards Sankarankovil) Meter 60 100 Across the Road At Ch. 158/740 (NH-138 & NH-44 Junction Point towards Tirunelveli) Meter 60 100 Across the Road At Ch. 158/740 (NH-138 & NH-44 Junction Point towards total running meter (in ₹) Amount towards total running meter (in ₹) Charges for Crosing NH-44 @ 138/478, 148/038, 157/341, 158/740 (in ₹) Total Amount on account of Restoration including Centages (in ₹)	4	Along the Road	Flyover towards Sivalaperi Road)	Flyover towards Sivalaperi Road)	Meter	602	100	₹ 60,200.00
Across the Road At Ch. 138/478(M/s Deepam Agencies, Indian Oil Petrol Bunk, Gangaikondan) Meter 60 100 Across the Road At Ch. 148/038(NH-44 towards Tirunelveli) Meter 60 100 Across the Road At Ch. 157/341 (NH 44 towards Sankarankovil) Meter 60 100 Across the Road At Ch. 158/740 (NH-138 & NH-44 Junction Point towards Sankarankovil) Meter 60 100 Across the Road At Ch. 158/740 (NH-138 & NH-44 Junction Point towards Sankarankovil) Amount towards total running meter (in ₹) 60 100 Tirunelveli) Amount towards total running meter (in ₹) Centage Charges Ga 23.5 % (in ₹) Centage Charges (in ₹) Centage Charges (in ₹)								
Across the Road At Ch. 148/038(NH-44 towards Tirunelveli) Meter 60 100 Across the Road At Ch. 157/341 (NH 44 towards Sankarankovil) Meter 60 100 Across the Road At Ch. 158/740 (NH-138 & NH-44 Junction Point towards Tirunelveli) Meter 60 100 Across the Road At Ch. 158/740 (NH-138 & NH-44 Junction Point towards Trunelveli) Amount towards total running meter (in ₹) 60 100 Charges for Crosing NH-44 @ 138/478, 148/038, 157/341, 158/740 (in ₹), Total Amount on account of Restoration including Centage Charges (in ₹)	5	Across the Road	At Ch. 138/478(M/s Deepam / Ganga	gencies, Indian Oil Petrol Bunk, kondan)	Meter	09	100	₹ 6,000.00
Across the Road	9	6 C C C C C C C C C C C C C C C C C C C	A+ Ch 149/038/NH	(iloulounit phacina)	70+04	0.9	007	00 000 9 #
Across the Road At Ch. 157/341 (NH 44 towards Sankarankovil) Meter 60 100 Across the Road At Ch. 158/740 (NH-138 & NH-44 Junction Point towards Amount towards total running meter (in ₹) Charges for Crosing NH-44 @ 138/478, 148/038, 157/341, 158/740 (in ₹), Total Amount on account of Restoration including Centage Charges (in ₹)	D	Acioss tile noau	At CII: 140/030(IVIII-	+ (Owalus III dileiveii)	אובובו	00	001	00.000.00
Across the Road At Ch. 157/341 (NH 44 towards Sankarankovil) Meter 60 100 At Ch. 158/740 (NH-138 & NH-44 Junction Point towards Amount towards total running meter (in ₹) Charges for Crosing NH-44 @ 138/478, 148/038, 157/341, 158/740 (in ₹), Total Amount on account of Restoration including Centage Charges (in ₹)		2						
Across the Road Across the Road Across the Road Tirunelveli) Amount towards total running meter (in ₹) Charges for Crosing NH-44 @ 138/478, 148/038, 157/341, 158/740 (in ₹), Total Amount on account of Restoration (in ₹) Centage Charges @ 23.5 % (in ₹) Total Amount on account of Restoration including Centage Charges (in ₹)	∞	Across the Road	At Ch. 157/341 (NH 44	towards Sankarankovil)	Meter	09	100	₹ 6,000.00
Amount towards total running meter (in ₹) Charges for Crosing NH-44 @ 138/478, 148/038, 157/341, 158/740 (in ₹), Total Amount on account of Restoration in ₹) Centage Charges @ 23.5 % (in ₹) Total Amount on account of Restoration including Centage Charges (in ₹)	c	14 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	At Ch. 158/740 (NH-138 & I	JH-44 Junction Point towards	,	3	,	C C C C C H
	u u	Acioss tile road	Tirut	ielveli)	Mere	00	OT TO	₹ 6,000.00
			Amount towards	total running meter (in ₹)			-	₹ 29,22,800.00
			Charges for Crosing NH-44 @ 13	8/478, 148/038, 157/341, 158/74	0 (in ₹),			₹ 4,00,000.00
			Total Amount on a	ccount of Restoration (in ₹)				₹ 33,22,800.00
			Centage Ch	arges @ 23.5 % (in ₹)				₹ 7,80,858.00
			Total Amount on account of Res	toration including Centage Charg	es (in ₹)			₹ 41,03,658.00

CORPORALIS SRPL

	Licence fee calculation	alculation	
N.	S.No Description	Licence Fee	Reference
_	Laying of Underground 10.75" Steel, 125mm MDPE and 89mm OD HDPE pipe along with OFC National Highway NH -44 from Chainage KM 133/349 to KM 159/422 (LHS), 4.5" Steel Pipe With OFC From Chainage 157/010 to KM 157/341 (RHS), 8.625" OD Steel Pipeline with OFC Across NH-44 at Chainage KM 150/005, 6.625" OD steel pipeline with OFC across NH-44 at chainage km 144/338 and 4.5" Steel Pipe across NH-44 at Chainage KM 133/349, KM 157/341 and KM 159/422 for Indian Oil Corporation Limited, City Gas Distribution project, Southern Region Pipelines Thoothukudi	Not applicable	Clause III.2.b of the MoU signed Between IOCL and NHA! dated 08.06.2022 (MoU Enclosed)

0. A.C.

Shirt (Taighin-R)

RANJITH KUMAR N Serior Manager (CGD) SRPL, Tuticorin.



इंडियन ऑयल कॉपोरिशन लिमिटेड

दक्षिणी क्षेत्र पाइपलाइन्स हाउस ऑफ फोर फ्रेम्स

6/13. व्हीट क्राफ्ट रोड, नुंगमबाक्कम, चैन्नै - 600 03

दूरभाष : 044-2824 3129 / 3144



पाइपलाइन्स प्रभाग Pipelines Division

Indian Oil Corporation Limited Southern Region Pipelines

House of Four Frames 6/13, Wheat Croft Road,

Nungambakkam, Chennai - 600 034.

Tel: 044-2824 3129 / 3144

SRPL/CONST/GEN

11.07.2023

TO WHOMSOEVER IT MAY CONCERN

Sub: Authorized Signatory

This is to certify that Mr. N Ranjith Kumar, Senior Manager (CGD), GA In-charge, Tuticorin, Southern Region Pipelines, is authorized on behalf of Indian Oil Corporation Ltd., Southern Region Pipelines for signing of agreements, lease deeds, applications etc related to land, crossing permissions, renting of space and statutory clearances for City Gas Distribution at Tuticorin.

Specimen Signature:

N Ranjith Kumar

Senior Manager (CGD)

(Shailesh Tiwari)

Executive Director

Southern Region Pipelines, Chennai

1161

पंजीकृत कार्यालय : इंडियन ऑयल भवन, जी- 9, अली यावर जोग मार्ग, वान्द्रा (पूर्व), मुम्बई - 400 051. महाराष्ट्र (भारत) Regd. Office : Indian Oil Bhavan, G- 9, Ali Yavar Jung Marg, Bandra (East) Mumbai - 400 051. Maharashtra (India) CIN No.: L23201MH1959GOI011388

Government of India Ministry of Road Transport and Highways (Highway Administration Cell)

Transport Bhavan, I, Parliament Street, New Delhi — 110 001 No. NH-36094/01/2022-S&R(P&B) Dated: 17th April, 2023

To

0000

0

- 1. The Chief Secretaries of all the State Governments/UTs
- 2. The Principal Secretaries/ Secretaries of all States/ UTS Public Works Department dealing with National Highways, other centrally sponsored schemes.
- 3. All Engineers-in-Chief and Chief Engineers of Public Works Department of States/ UTs dealing with National Highways, other Centrally Sponsored Schemes.
- 4. The Director General (Border Roads), Seema Sadak Bhawan, Ring Road, New Delhi 110 010.
- 5. The Chairman, National Highways Authority of India, G-5 & 6, Sector-10, Dwarka, New Delhi-110 075.
- 6. The Managing Director, NHIDCL, PTI Building, New Delhi-110001
- 7. ROs, ELOs and PIUs of the MoRTH.

Subject- Accommodation of Public and Industrial Utility Services along and across National Highways- Policy guidelines; Clarifications regarding OFC/Telecom cables.

Sir,

Following amendments are issued herewith with reference to Ministry's policy circular no RW/NH-33044/29/2015-S&R(R) dated 22.11.2016 regarding permission for laying of underground OFC/telecom cables in NH ROW with immediate effect:

Clause	Existing provision	Amendments
3.1	The utility services shall be permitted to cross the National Highway either through structure or conduits specially built for that purpose. The casing / conduit pipe should, as minimum, extend from drain to drain in cuts and toe of slope to toe of slope in the fills and shall be designed in accordance with the provision of IRC and executed following the Specifications of the Ministry.	The utility services shall normally be permitted to cross the National Highway either through structure or conduits specially built for that purpose. The casing / conduit pipe should, as minimum, extend from drain to drain in cuts and toe of slope to toe of slope in the fills and shall be designed in accordance with the provision of IRC and executed following the Specifications of the Ministry. Alternatively, for crossing of NH by pipelines for petroleum products, Horizontal Directional Drilling (HDD) method may be used

cons_

		without casing/ conduit pipe following the safety precautions and Codes as given in Annexure II.
5.	Charges for granting licence for use of highway land: For the purpose of license fee/lease rentals, the utilities have been divided into two categories; i) Public utilities and b) Industrial utilities as per the details given in Annexure I. License Fee/lease rentals described below is for Industrial utilities. The	of highway land: For the purpose of license fee/lease rentals, the utilities have been divided into two categories; i) Public utilities and b) Industrial utilities as per the details given in Annexure I.
	license fee for Public utilities shall be 33% of the fee prescribed for Industrial utilities.	
5.1	The following methodology shall be followed for license fees/lease rental determination for utility service lines other than localized infrastructure facilities like towers, repeaters and junction boxes).	shall be equal to utilized NH land area X Prevailing Circle Rate of land per
	License Fees (Rs/sq m/ month) = (Utilized NH land area X Prevailing Circle Rate of land per unit area) / (10 X 12) where,	including area of support system / tower. License fee for total term of license
	Utilized NH land area = Outer diameter/width of the concerned utility line X length	(up to maximum of 5 years) shall be deposited in advance.
5.2	The following methodology shall be followed for license fees/lease rental determination for utility services such as towers/repeaters junction boxes etc. License Fees (Rs/sq m/ month) =	equal to utilized NH land area X
	(Utilized NH land area X Prevailing Circle Rate of land per unit area) / (10 X 12) where,	Utilized NH land area shall include area of support system / tower but not include projection of utility on ground.

Utilized NH land area = Projection of There shall be no license fee for OFC utility on the ground including area of cables crossing the NH through HDD support system/tower.

method.

However, for public utilities, area License fee for total term of license below the support system/tower shall (up to maximum of 5 years) shall be only be charged.

deposited in advance.

2. This issues with the approval of competent authority.

Yours faithfully

(Rakesh Prakash Singh)

Superintending Engineer (HA)

Copy to:

- 1. AS/ JS/CEs in MoRTH
- 2. Director, IAHE
- 3. The Secretary General, Indian Roads Congress
- 4. Technical circular file of S&R(P&B) Section and Road Safety Engineering Cell
- 5. NIC-for uploading on Ministry's website under "What's new"

Copy for information to:

- 1. PS to Hon'ble Minister (RT&H)/ PS to Hon'ble MOS (RT&H)
- 2. Sr. PPS to Secretary (RT&H)/ Sr. PPS to AS(H)/ Sr. PPS to AS&FA
- 3. Sr. PPS to DG (RD) & SS/ Sr. PPS / PPS /PS to ADG-I/II/III/IV

(Rakesh Prakash Singh)

Superintending Engineer (HA)

19

A. Codes/ publications for guidance on design of Horizontal Directional Drilling crossing for Petroleum Pipelines

- a) Oil Industry Safety Directorate Code: IOSD Code-141.
- b) American Gas Association PR-227-9424 "Installation of Pipelines by Horizontal Directional Drilling an Engineering Design Guide".
- c) American Society of Civil Engineering Practice No.89 "Pipeline Crossings Handbook".
- d) Directional Crossing Contractors Association publications "Guidelines for a Successful Directional Crossing Bid Package", "Directional Crossing Survey Standards" and "Guidelines for Successful Mid-Sized Directional Drilling Projects."
- B. Safety precautions and plan to be submitted along with the proposal for HDD crossings:
- a) Before taking up the HDD work, area to be scanned by suitable methods like GPR to locate all underground utilities. Accordingly, crossing plan and profile drawings to be developed showing all pipelines, utilities, cables and structures that cross the drill path, are parallel to and within 30m of the drill path and that are within 30m of the drilling operation, including mud pits and bore pits.
- b) Damage prevention plan to reduce or avoid the likelihood of damage to adjacent underground facilities, including pipelines, utilities, cables and other subsurface structures considering the accuracy of the method in locating existing structures and in tracking the position of the pilot string during drilling. Consideration should be given to having an auxiliary location system to include manual excavation to ensure that the drilling bit or reamer is following the projected path and does not encroach upon crossing or parallel lines. The damage prevention plan should include provision for sending notification to all affected parties.
- c) Safety plan to include contingency plans in the event the drilling string impacts subsurface facilities and identify facilities and resources to be utilized in the event of an emergency or any personnel injuries. The safety plan shall be reviewed on site with all construction personnel prior to the commencement of drilling operations.
- d) Plan for containment and disposal of drilling fluids, if used.
- e) Hydrostatic test plan that should consider pretesting of the fabricating string(s) prior to installing the crossing.
- f) Testing plan be agreed upon the measures like Cathodic protection, periodic inspection be outlined and Supplementary extra thickness of pipe be ensured to compensate for corrosion.
- g) Pipeline laying agencies to submit annual certificates of inspection after laying.

20

Ö

0

0

17/4/23



INDIA NON JUDICIAL

Government of National Capital Territory of Delhi

e-Stamp

Certificate No.

Certificate Issued Date

Account Reference

Unique Doc. Reference

Purchased by

Description of Document

Property Description

Consideration Price (Rs.)

First Party

Second Party

Stamp Duty Paid By

Stamp Duty Amount(Rs.)

IN-DL43131039471235U

07-Jun-2022 11:13 AM

IMPACC (SH)/ dlshimp17/ SUPREME COURT/ DL-DLH

SUBIN-DLDLSHIMP1770917717202787U

INDIAN OIL CORPORATION LIMITED

Article 5 General Agreement

Not Applicable

0

(Zero)

INDIAN OIL CORPORATION LIMITED

Not Applicable

INDIAN OIL CORPORATION LIMITED

(One Hundred only)



Please write or type below this line MEMORANDUM OF UNDERSTANDING

BETWEEN

INDIAN OIL CORPORATION LIMITED

AND

NATIONAL HIGHWAY AUTHORITY OF INDIA (NHAI)

Page 1 of 10

the vibral of this Stramp distribution is good by verificable for version section of or using either strain and a App of Stock Hooking His reportion in the details on this Certificate and occurring on the website infection approximation of the Rig

This Memorandum of Understanding (hereinafter referred to as "MoU") made at NHAI, G-3, Sector-10, Dwarka, New Delhi on this 8th of June 2022 ("Effective Date"),

by and between:

INDIAN OIL CORPORATION LIMITED, a company duly incorporated under the Companies Act, 1956 and having its registered office at G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051 (hereinafter referred to as "IOCL" which expression shall, unless repugnant to the context or meaning thereof, be deemed to include its successors and permitted assigns) of the First Part.

And

NATIONAL HIGHWAY AUTHORITY OF INDIA (hereinafter called NHAI) an autonomous Authority constituted by Act of Parliament, having its registered office at Sector 10. Dwarka, New Delhi - 110075, India, which expression shall, unless the context required otherwise, include its legal successors and permitted assigns (hereinafter referred to as "NHAI") of the Second Part.

IOCL and NHAI are individually referred to as "Party" and collectively as "Parties".

RECITALS:

WHEREAS; IOCL, a Maharatna Central Public Sector Undertaking under the administrative control of Ministry of Petroleum and Natural Gas (MoPNG), Government of India and is India's flagship national oil company with business interests straddling the entire hydrocarbon value chain - from refining, pipeline transportation and marketing of petroleum products to natural gas and petrochemicals.

WHEREAS; NHAI, is an autonomous agency of the Government of India under the Ministry of Road Transport and Highways (MoRTH) for development, maintenance, and management of National Highways across the country.

WHEREAS; In ever expanding networks of cross-country pipelines of IOCL and National Highways of NHAI, interfacing of these two structures and many locations is unavoidable.

Page 2 of 10

WHEREAS: Parties are desirous of simplification of the process of obtaining crossing permissions, optimization of the expenditure on the crossings and bringing about uniformity of such proceedings across the country.

WHEREAS; in furtherance of the same, NOW THEREFORE, it is understood between the parties as under:

- I. SCOPE AND APPLICABILTY: The terms and conditions mentioned in this MoU will be applicable for complete network of NHAI's National Highways in National Highways Right of Way and IOCL's gas/ petroleum pipeline(s) across the country.
- II. DESCRIPTION OF PURPOSE: This MOU is an understanding between the parties to express the mutual interest of the parties, within the framework of this MoU for amicable mutual interface for laying of gas/ petroleum pipeline(s) along and across National Highways Corridors and vice versa.

III. OBLIGATIONS, DUTIES AND UNDERTAKINGS OF NHAI

1. In respect of already laid gas/ petroleum pipeline(s):

0

000

- a. Wherever, the alignment of a National Highway ("NH") crosses an already laid gas/petroleum pipeline(s) (i.e., pipeline(s) existing prior to declaration of said National Highway vide relevant Notification), NHAI shall either construct portal structure(s) over the existing pipeline (as per **Annexure-A**) or cause shifting of such operating pipeline(s) at NHAI's cost under supervision of IOCL.
- b. NHAI will inform IOCL regarding upcoming alignment of National Highways over IOCL's existing gas/ petroleum pipeline(s) as soon as NHAI becomes aware of such operating pipeline(s) to expedite the interface related formalities. However, NHAI may explore possibilities of expediting the information to IOCL regarding crossing of National Highways to IOCL's existing gas/ petroleum pipeline(s) during the land acquisition stage to expedite the crossing related formalities.

23

Page 3 of 10

- c. NHAI will try to maximize the crossing angle i.e., near to 90 Deg to IOCL's gas/ petroleum pipeline(s).
- d. For crossing length exceeding 30m, NHAI to provide rectangular vent of minimum size, 3ft x 3ft in the RCC portal structure.
- e. NHAI will extend all possible support to IOCL during any exigency in IOCL's gas/ petroleum pipeline(s).
- f. Wherever, the alignment of an existing National Highway ("NH") crosses an already laid gas/ petroleum pipeline(s) (i.e., pipeline(s) laid after declaration of said National Highway vide relevant Notification), NHAI will allow IOCL to either shift or take suitable measures to protect its pipeline(s) at IOCL's cost within mutually agreed period of time upon receipt of notice from NHAI, if such pipeline obstructs the upgradation of the National Highway(s).

2. In respect of laying of new gas/ petroleum pipeline(s):

- a. NHAI will issue NOC to IOCL for laying gas/ petroleum pipeline(s) along and across National Highways in National Highways land (Right of Way) in 60 days period from the date of formal application by IOCL. Beyond this period of 60 days, it is understood by both the parties that the NOC stands issued.
- b. NHAI shall not levy any charges from IOCL and its agencies for laying new gas/ petroleum pipeline(s) along or across National Highways in National Highways Right of Way.
- c. NHAI will obtain Performance Security from IOCL before issuance of permission for laying gas/ petroleum pipeline(s) along and across National Highways in National Highways land (Right of Way).
- d. NHAI will extend all possible support during any exigency in IOCL's gas/ petroleum pipeline(s) at crossing location of NHAI to IOCL.

OBLIGATIONS, DUTIES AND UNDERTAKINGS OF IOCL IV.

1. In respect of already laid gas/ petroleum pipeline(s):

Wherever, the alignment of a National Highway ("NH") crosses an already laid gas/

24

Page 4 of 10

petroleum pipeline(s) (i.e., pipeline(s) existing prior to declaration of said National Highway vide relevant Notification), IOCL will allow NHAI to either construct portal structures over the existing pipeline (as per **Annexure-A**) or cause shifting of such operating pipeline(s) at NHAI's cost under supervision of IOCL.

Cou

- b. Wherever, the alignment of an existing National Highway ("NH") crosses an already laid gas/ petroleum pipeline(s) (i.e., pipeline(s) laid after declaration of said National Highway vide relevant Notification), IOCL to either shift or take suitable measures to protect its pipeline(s) at IOCL's cost within mutually agreed time period upon receipt of notice by NHAI, if such pipeline obstructs the upgradation of the National Highway(s).
- c. IOCL will not levy any charges on NHAI for constructing National Highways over their already laid gas/ petroleum pipeline(s).
- d. IOCL will obtain Insurance Cover from NHAI before allowing construction of National Highways over their already laid gas/ petroleum pipeline(s).
- e. IOCL will issue NOC to NHAI whenever under construction National Highway crosses over an already laid gas/ petroleum pipeline(s) (i.e. pipeline(s) existing prior to declaration of said National Highway vide Notification) in 60 days period from the date of formal application by NHAI. Beyond this period of 60 days, it is understood by both the parties that the NOC stands issued.
- f. IOCL will extend all possible support during any exigency in NHAI's National Highways in National Highways Right of Way at crossing location of IOCL to NHAI.

2. In respect of laying of new gas/ petroleum pipeline(s):

- a. IOCL, while laying gas / petroleum pipeline(s) across already constructed National Highways, will adopt Trenchless method throughout National Highways land (Right of Way) with the depth of topmost point of pipeline being at-least 1.5m below ground level/ bottom of any National Highway structure/ facility.
- b. IOCL shall bear all cost for laying of new pipeline along or across existing NH land (Right of Way).

25

Page 5 of 10

- c. IOCL will try to maximize the crossing angle i.e., near to 90 Deg to NHAI's National Highways in National Highways Right of Way.
- d. IOCL will inform NHAI regarding crossing of IOCL's pipeline to National Highways during the land acquisition stage to expedite the crossing related formalities.
- e. IOCL will extend all possible support during any exigency in NHAI's National Highways in National Highways Right of Way at crossing location of IOCL to NHAI.

V. DEFINITIVE AGREEMENT:

- 1. The Parties may enter into separate agreement(s) in terms of this MoU on specific work association of the parties for crossing permissions and shall identify inter alia the methodology of crossing, division of their individual scope of work, division of responsibilities and respective liabilities, expenses etc.
- Such definitive agreements would be binding on the parties and would be entered into generally as per the understanding contained in this MoU, upon approval by competent authorities of the parties.
- 3. In case of any contradiction/ discrepancy in any of the clauses of MoU and the definitive agreement(s), the definitive agreement shall prevail. However, clauses of the definitive crossing agreement (s) to be made in line with this MoU conditions for both the parties.

VI. NON-EXCLUSIVITY:

The understanding between the Parties under this MoU shall be initially on non-exclusive basis. However, the understanding shall be on exclusive basis contingent upon parties entering into definitive agreement as stipulated above.

VII. BINDING UNDERSTANDING:

1. The Parties undertake to act in good faith with respect to each other's rights and obligations under the objectives of this MoU,

26

Page 6 of 10

- 2. The Parties recognize the impracticality of providing for every contingency, which may arise during or after the expiry of the MoU and hereby agree to operate fairly and without detriment to the interests of either of them,
- 3. Subject to any definitive agreements entered into, this MoU is binding in nature, and is a definite expression and record of the purpose and intention of the Parties concerned.

VIII. TRANSFER AND ASSIGNMENT

- 1. None of the Parties shall assign or transfer this MoU or any of its respective rights or obligations hereunder, to any other third party without the prior written consent of the other.
- 2. This consent requirement shall not apply in the event that a Party shall change its corporate name.

IX. DISPUTE RESOLUTION AND GOVERNING LAW:

- 1. This MoU will be construed and governed by the laws of India.
- Any dispute arising out of this MoU shall be amicably resolved in first instance, through
 discussions in good faith with a view to expeditiously resolve such differences or
 disputes in a spirit of mutual understanding and cooperation.
- 3. In the event of any dispute or difference relating to the interpretation and application of the provisions of this agreement, such dispute or difference shall be taken up by either party for resolution through AMRCD as mentioned in DPE OM No. 4(1)/2013-DPE (GM)/FTS-1835 dated 22.05.2018 issued by Ministry of Heavy Industries and Public Enterprises.

X. DURATION AND TERMINATION OF THIS MOU:

- 1. This MoU shall enter into force on the Effective Date.
- 2. This MoU shall remain in force for a period of three (3) years from the Effective Date (i.e. the date on which this MoU is signed).
- 3. The Parties may elect to extend the period of this MoU for an additional period of time or multiple periods of time as may be mutually agreed upon by the Parties in writing.
- 4. Each party has a right to terminate the MoU at any time during the validity of this MoU,

Page 7 of 10

27

.

in writing, with at least one (1) month notice of such intention to the other party. However, the termination of this MoU shall not affect the actions that may have been formalized during its operation.

XI. CONFIDENTIALITY

- The Parties hereto agree that they will not at any time during the Term of this MoU, without the prior written consent of the other Party, disclose the existence of, or the terms and conditions set forth in this MoU unless otherwise required by law or regulation.
- 2. Only those individuals and representatives of the Parties, and their respective legal and financial advisors, with a need to know and for the sole basis of advising the respective Parties concerning the transactions contemplated hereby, shall be permitted to receive knowledge of the information contained herein.

XII. AMENDMENT

- 1. This MoU may be amended in writing by mutual agreement between the Parties.
- 2. Any such amendment shall enter into force from the date agreed to by the Parties.

XIII. NOTICES

- 1. Notices in connection with this MOU must:
 - a) Be in writing, in the English language.
 - b) All notices or other information required or deemed necessary to be given to:

i. For NHAI:

Name: Chairperson, NHAI

Address: NHAI 2nd Office Building, G-3, Sector-10, Dwarka, New Delhi-110075

Email Id: chairman@nhai.org, chairperson@nhai.org

28

4

Page 8 of 10

ii. For IOCL

Name: Executive Director (Operations), PLHO

Address: Indian Oil Bhavan, A-1, Udyog Marg, Sector 1, Noida (UP)-201301

Email Id: edoplho@indianoil.in

c) Notices shall be delivered by courier or hand or sent by email to the respective addresses and email which are specified above or if the addressee specifies another address or email, in writing, then to that address or email.

XIV. COUNTER PARTS

This MoU shall be executed in two counterparts. Both Parties shall each have one counterpart of this MoU. Both counterparts shall constitute one and the same MoU.

In witness whereof, the undersigned being duly authorized thereto, by their respective parties, have signed this MoU.

Signed at NHAI, G-3, Sector 10, Dwarka, New Delhi on 8th June 2022 in two originals text in English language.

Signature...

Signed by: Udeep K Singhal

General Manager (Tech.) & Regional Officer, Delhi

For and on behalf of;

National Highway Authority of India

Signature.

Signed by: Rajesh Gupta

Executive Director (Const.)

PLHO, Noida

For and on behalf of;

Indian Oil Corporation Limited

Witnesses:

Signature...


29

Signature...

Page 9 of 10

PLHO Norda

Annexure A



PROPOSED RCC PORTAL STRUCTURE ACROSS IOCL'S ROU

Note:

- i. EGL- Existing Ground Level
- ii. Clearance of minimum 1.5 meter to be kept from outside edges of Pipeline and OFC as shown above
- iii. In case of multiple pipelines in the same ROU, single portal or more than one portal as per site condition can be built with minimum distance of 1.5-meter from outside edges of Pipeline and OFC as shown above

30

Page 10 of 10







Document No. TPL/IOCL/TE/TC/WP003

Project	Laying of 3LPE Coated Steel Pipeline Network & Associated Works in Group – TC- Thoothukudi GA
Project No.	Works 2318
Client	Indian Oil Corporation Limited
PMC	Tractebel Engie
Contractor	Taurant Projects Limited

PROCEDURE FOR HORIZONTAL DIRECTIONAL DRILLING

				TPL PREPARED &	Tractebel/IOCL REVIEWED &
0	27.07.2024	For Review & Approval	Name & Sign		
				E (National)	

31

Page 1





TRACTEBEL





Document No. TPL/IOCL/TE/TC/WP003

S.No	DESCRIPTION	PAGE NO.
1.0	PURPOSE	3
2.0	SCOPE OF WORK	3
3.0	REFERENCE	3
4.0	RESPONSIBLITIES	3
5.0	EQUIPMENT DETAIL	4
6.0	PRE-CONSTRUCTION SURVEY	4
7.0	DESIGN AND ENGINEERING	4
8.0	CONSTRUCTION	6
9.0	DOCUMENTATION	11
10.0	HEALTH, SAFETY AND ENVIRONMENT	12

32











Document No. TPL/IOCL/TE/TC/WP003

1.0 PURPOSE

The purpose of this procedure is to provide a frame work for TPL to plan and develop guidelines and requirements to establish a method to carry out HDD crossing work.

2.0 SCOPE OF WORK

The Purpose of this procedure is to define the methodology equipment and safety precautions to be taken in the Laying of 3LPE Coated Steel Pipeline Network & Associated Works in Group — TC- Thoothukudi GA by Horizontal Directional Drilling (HDD) technique and associated Works in Tamil Nadu State. The work shall be carried out in accordance with the !OCL specifications and the permissions from concerned authorities.

3.0 REFERENCE DOCUMENT

Following documents in totality or in part shall form the reference documents:

- IOCL Standard specification / AFC drawings.
- Alignment sheets & crossing drawing No. as Per tender by IOCL and route survey by TPL.
- Design and construction for cross country Hydrocarbon pipeline Doc. No. OISD- 141
- ASME B 31.4 & ASME B31.8
- Provision made by statutory authorities in permissions.
- Contract Document.

4.0 RESPONSIBILITIES

- HDD Engineer / Foreman is responsible for implementing this method statement at site. To Coordinate with QC Inspectors and crews during pipe line HDD activities and also to ensure all HSE and Quality requirements mentioned in the contract & project specifications are implemented.
- Surveyor is responsible for follow all the underground movements of the headpiece.
- Operators (Side Boom) are responsible for safe operations of side boom cranes and also for safe handling of pipe line sections with instructions from Engineers/ Foreman.
- QC Inspector is responsible to ensure all welding, Coating, NDT activities are strictly carried out as
 per approved procedures and project specifications and also to coordinate with construction team
 for related inspections. All records to be prepared and maintained.
- HSE Officer is responsible to ensure HSE plan is implemented during HDD activities particularly safe disposal of bentonite mud/slurry.
- Contractor at his own cost and initiatives shall arrange access to site from the nearest road,
 additional ROW for placing equipment's etc., including temporary storage yard.

33

0.16

Page 3 New Delhi







Document No. TPL/IOCL/TE/TC/WP003

5.0 EQUIPMENTS DETAILS:

- The drilling rig of required/approved capacity and support equipment shall consist.
- Rig Power unit and control Panel
- Support Equipment
- Crane (1 nos; 12-20T)
- Welding generator (As Required)
- Diesel Generator set (As Required)
- Mud mixing unit with a pumps
- Rubber Rollers (Load Bearing capacity 6T) as per requirement
- Tractor trolley or trucks 1 nos (as required to mobilize the drilling rig and allied equipment)

6.0 PRE CONSTRUCTION SURVEY

- TPL will carry out the pre-construction survey.
- ✓ After completion of Pre-construction survey a detail drawing & design calculation will be prepared with relevant data such as elevations, levels etc. and will be submitted to IOCL for approval.

7.0 DESIGN & ENGINEERING

- The minimum requirements of limits of each crossing shall be defined in the approved drawings.
 Slight changes can be made to suit the equipment and installation technique meeting the contract specification.
- Within the entire limits crossing as defined in the approved profile drawings, the cover shall be maintain as defined in the profile drawing as a minimum. With Approval only from IOCL.
- The entry and Exit points of pipeline at ground level shall not come within the limits of the crossing
 as defined for individual crossings. The entry and exit angle of pipeline at ground level shall generally
 be in range of 8° to 12° as defined in crossing drawings.
- Lateral allowance of calculated or theoretical exit point 0.5% of crossing length or 3.0 m whichever
 is less.
- Longitudinal allowance max 2% of the approved crossings length.

341

D.MC









Document No. TPL/IOCL/TE/TC/WP003

Minimum Cover Requirements for Pipe

The minimum top cover to the pipeline from the road top level, lowest bed level of canal/drain bed shall be between 10m as indicated in approved profile drawings and a min. of 15m cover to be maintained for major river crossings.

All the minimum cover requirement are as stated in typical drawing CONTRACTOR shall provide additional cover to pipeline in areas identified in the drawings.

- The pipe cover shall be as per approved drawings for all Road, Rail, Drain/Canal or river crossings which are crossing through HDD.
- Design calculations submitted to IOCL duty for the maximum permissible overburden on pipe, to
 check that the empty pipeline is safe from collapse at any point along the drilled crossing section.
 Drilled hole shall be checked against collapse / caving under overburden and pipe shall be
 checked against buckling / collapse under axial tension and bending stress.
- Design calculation has been carried out to ensure total maximum longitudinal stress in the
 pipeline due to tension and bending shall not exceed 95% of SMYS of the pipe material. In order
 to check this requirement, evaluate the maximum tension forces to which the pipeline is
 subjected at any phase of its installation during the pulling operation.
- The required pipeline configuration shall be ensured in order to allow smooth pull in the crossing entry point and admissible stress in the supported pipeline string. Total maximum longitudinal stress in the pipeline due to tension and bending at any location shall not exceed 75% of the SMYS of the pipe material.
- After installation the pipeline shall be hydrostatically tested at a pressure stipulated in the special
 conditions of the contract. During hydrostatic testing the combined equivalent stress in the
 pipeline and test pressure shall not exceed 95% of the SYMS of pipe material.
- Minimum allowable radius of curvature = Elastic radius + Drilling in auxiliaries (or) (Elastic radius x
 1.05)
- Permissible value of pipeline maximum equivalent stress during service shall be governed by the requirements of ASME B31.8/31.4/31.3, as applicable.
- The Required pipeline configuration along the supported string before entry point shall be calculated. The number of required roller supports shall be used specified along with the description of the supports, their coordinates and the capacity in metric tons. The distance between each roller shall also be specified.
- Based on the results of design and engineering profile construction drawing are generated and approved by IOCL for each HDD crossing. Construction drawing shall indicate the levels furnished at sufficient intervals for proper control during construction. Other relevant details like entry and exit angles, radius of bend etc., shall also be indicated.
- Calculations are made to determine the total length of pipeline required as well as the maximum tension required on the pull head of the rig.

All construction works shall be carried out in accordance with approved construction drawings.

35







Document No. TPL/IOCL/TE/TC/WP003

8.0 CONSTRUCTION:

Site Visit and Site preparation

- Prior to the commencement of any crossing with HDD, the profile of crossing shall be inspected and all underground third party crossings shall be marked.
- Row shall be clear and grade the length as required for installation of on land portion and drilled crossing for ensure safe construction.

> String Preparation:

 Complete pipe string shall be proposed as a single string for pulling. Stringing of pipes with various thickness shall be made ready as per contract specifications and the alignment sheet for each crossing.

Welding:

- Welding of pipeline shall be in accordance with the approved welding procedure.
- All the welded joints shall be subjected to 100% visual & NDT (X-Ray)

Pre- Hydro Test

- Section of pipeline subjected to hydro testing as per SCC during the test TPL will check all welds for leakage. Failure if any during the test shall be specified by the contractor. If failure on account of any cause other than defect in IOCL supplies materials. The repairs shall be done at free of cost & defect in IOCL material shall be jointly inspected and agreed upon.
- Actual length of crossing between hook-up point with mainline on both sides shall not vary more than ± 5% of the length indicated in the contract unless and until specifically allowed by owner due to site conditions.
- The pipe strings shall be tested for 6 hours.
- Pre- Hydrotest shall be carried out only after getting 100% NDT clearance

> Field Joint Coatings:

 The complete field joint coating shall be blast cleared to near white metal finished to Swedish standard |SISO55900 Grade SA 2 1/2. The coating edges shall be suitably roughed and chamfered to provide smooth transition. The joint coating material shall be Berry Plastic

36

p.mgc

VUMAR N







Document No. TPL/IOCL/TE/TC/WP003

"DIRAX" or other IOCL approved equivalent. The method of application shall be strictly prior to use. Coating of field weld joints shall be carried out after pre-hydro test.

- Radiographic inspection of joints & joint coating of the string shall be performed in accordance with specifications included in the contract.
- Visual and Holiday checks of entire section shall be carried out prior to insertion.

Installation:

> The installation of each pipe string shall be done as per approved design calculations and HDD profile drawings.

A) Pilot or Steering:

- Installation of the entire drilled crossing shall be accomplished in a single operation.
- Pilot hole shall be done by 6.5" Bit (Depending on strata).
- Appropriate tracking system like Mag shall be used during drilling to ensure that the drilled path is as per approved HDD profile.
- The lateral offset of the actual exit point of the Pilot hole from the calculated and theoretical exit point shall not exceed 0.5% of the length of the crossing or 3.0m whichever is less. However for the parallel pipelines the minimum distance between the each line shall be maintained as per alignment sheet/ construction drawings. The length tolerance shall not exceed 1% of the approved crossing length, subject to the condition that actual exit point shall not be within the limits of crossing as defined in the drawings.
- the ground level differences on the cross section, the distance between the machine and the pipe to be guided should be drawn on a graph paper by marking.
- Details of bentonite to be used, it velocity & pressure to be maintained during/reaming, disposed methodology for bentonite slurry.

B) Back Reaming:

- Back reaming shall be done separately from the pipeline pulling operation. The size of the back reamed hole shall be adequate (1.5 times of line pipe size or as per IOCL specs) to allow enough clearance for smooth pull back of the pipeline.
- The reaming shall be done in accordance with the Dia" of Main pipe, However the HDD crew on site
 will finally decide the reaming sequence depending on the soil strata encountered during pilot and
 each reaming pass.
- In order to optimize the crossing design in terms of pipeline stresses and equipment requirement, shall be derived from these parameters:-
- i) Back reamed hole size.
- ii) Bentonite density.

O.M.

Page 77
New Delhi M

37







Document No. TPL/IOCL/TE/TC/WP003

- lii) Pipeline submerged weight in bentonite.
- Maximum shear stress in the pipeline coating will result from above parameters shall not exceed the permissible.
- Subjected to maximum shear stress in pipeline coating results from these set of parameters.
- Reamers of reputed make like in rock (make) shall be used.
 - a) On the normal ground clayey and sandy ground:
 - If the length of crossing is 50m and below then the reamed hole should be at least 10% wider or if the hole is between 100-150 m. then should be at least 30% wider than the diameter of the pipe.
 - The diameter of hole will be determined according to the composition of the ground if it is composed of loose material and /or consisting debris.
 - The size of the final reamed hole (with or without MS Conduit for OFC) shall be adequate (approximately 10 inch more than diameter of the pipe and pipe bundle up to carrier pipe size of 24" OD

b) If the ground has a stony or rocky composition:

- If the length to be crossed is up to 50m, then the hole should be at least 20% wider than the diameter of the pipe or if the length to be crossed is above 50m, then the hole should be at least 30% wider than the diameter of the pipe.
- Size of back reamed hole is approximately 1.5 times of the diameter of pipeline to allow enough clearance for a smooth pull back of the pipeline.

B) Pulling:

- Depending on the composition of the route the pipe to be guided the density mud weight to make the best excretion will be maintained after ascertained by viscosity cup.
- During pulling operation the buoyancy of the pipeline shall be controlled by suitable approved methods so as to maintain the buoyancy as close possible to zero during pull back in order to reduce friction forces of the pipeline in the hole.
- Liquid polymers shall be added into the more homogenous mud in order to increase its viscosity and into the drilling mud so as to prevent the swell and spill of clay.
- Bentonite slurry of specified viscosity shall be pumped into the hole, preventing the wall from collapsing and protecting the pipeline coating.
- In order to decrease e rotation torque and circulation pressure to the least, to increase the clearness of the hole and core percentage to drill the water in sensitive formation and to form drilling mud, modified cellulosic polymers suspension is added.

38

p.m.

Page 8 New Defini

Senior Manager (CGD)
SRPL Tuticorin.







Document No. TPL/IOCL/TE/TC/WP003

- Calculations of maximum pulling force on the rig and recommended maximum pulling velocity shall be submitted.
- To prevent clay materials stuck in the reamer and in the pipes due to the pressure differentiations and high cohesion and to make the dug material carried out faster along the tunnel in shale formations where the surface tension of the drilling liquid will be reduced, insoluble progressing rate improver will be used.
- Specially formulated inorganic and unfermented material with pull fiber and easily dissolved leakage control is used.
- By Channel grading in the route of the pine to be guided, the installation of the pipe without any damage on the tunnel walls will be maintained.
- Completing procedures listed above, a funnel shaped headpiece resistant to the pulling strength (in order not to collect the chemicals deposited before during the regression) will be welded to the pipe.
- Prepared drilling mud, lubricant chemicals and chemicals increasing the insulation of the pipe will be added.
- Inspection shall be carried out at all the stages of construction.
- Depth of the drilled pipe shall measure by suitable equipment like pipeline mapper which shall be duly witnessed/verified by iOCL site Engineer.
- The pipe before this stage been already placed on rollers on the ground and held by a crane or backhoe /excavator at the rear end, in order to minimize the friction and to ensure its smooth entry down the drilled hole. Rollers are bell shaped and lined with rubber/PU/Teflon coating approx. 10mm thick. Roller spacing shall be as per the roller spacing design in the design calculations submitted. The crossing length divided by the roller span shall give the number of rollers required at the crossing.
- Holiday activity of the carrier pipe will be carried out simultaneously during pulling. The pipe string is then pulled back from the exit end and towards the entrance end by the drill jig.
- The pulling force shall be recorded at every drill rod, which will show in the gauge fixed to drill machine.
- After pulling the pipeline across the drilled crossing cut the extended portion of the pipeline at the entry and the exit points, thereafter the drilled portion of the pipeline shall be cut at suitable location/ depth and extended on either side by installing a bend with minimum bend radius of 6 times of pipe diameter unless specified otherwise and a straight pipe length (1 Joint) Such that the top of the pipeline is minimum 1.5mtr to 2.0 mtr below the natural ground level.
- The method of pipeline coating inspection after pulling operation shall be as following:
 - Pulling the pipe to the extent possible with normal rig-up at the exit point.
 - Excavating the adjacent portion up to and including the first field selection.

391

o.me:







Document No. TPL/IOCL/TE/TC/WP003

- The Pipeline and joint coating shall be examined visually and with holiday detector for defect. The length to be inspected shall as a minimum be one pipe length and one joint coating. In case any coating damage / holiday detected in the first pipe length / joint, the subsequent pipe length / joint shall be exposed and coating integrity checks shall be made. If Found acceptable by IOCL, the first pipe length / joint shall be repaired and / or replaced as per instruction by IOCL.
- If the coating of second pipe length/joint is also found damaged shall be repaired as per approved coating procedure and in case of any coating issue, suitable TCP/CP shall be additionally provided for resolution.
- Coating integrity test:-
- After pull back operation in order to ensure the integrity of pipe coating megger test of the coating shall be carried out in accordance with the following steps:
- ✓ Measure the natural potential of the HDD pipe at both ends.
- ✓ Set up the temporary impressed current system with position the test electrode/anode a far (not closer than 10 meters) from the HDD pipe.
- ✓ Impress a current into the HDD pipe start at Zero amp. And increase slowly until the HDD pipe potential is depressed to 1.5 V with respect to the reference electrode.
- Place the reference electrode at remote end (opposite to impressed current system) to monitor the HDD pipe potential.
- ✓ The desirable value calculated current density should be less than 95 micro ampere per square meter of drilled pipe surface in contact with the soil.
- Arrangements shall be made for safe disposal of all surplus soil and bentonite slurry so as to
 avoid any harm to the environment /occupants at locations approved by authorities and
 pollution control boards having jurisdiction and or as instructed. The bentonite slurry will be
 shifted by septic Tank and disposed at safe unpopulated area.

C) Gauging Test (Before Final Hydro Test): (As Required)

- After completion of HDD the pipe strings shall be cleaned and gauging shall be carried out by
 passing a gauge plate consisting of two discs with a diameter equal to 95% of the nominal
 diameter of the pipe connected rigidly together at a distance equal to 300mm. If the gauging
 fails due to any reasons (buckling, dents or ovality) the pipe or pipe section shall be replaced
 and re-gauging shall be carried out.
- D) Final Hydro Test:

40

p.M.









Document No. TPL/IOCL/TE/TC/WP003

- After acceptance of gauging the pipe sections shall be post- hydro tested for 24 hour and recorded by man thermograph at specified test pressure given in the scope of work.
- The hydrostatic test shall be considered positive if pressure has kept a constant value throughout the test duration except for changes due to temperature effects meeting hydro test specification and there is no abrupt pressure drop throughout the test duration.
- The test pressure shall be 1.4 times of MAOP as per SCC.
- The hydro testing shall be carried out in accordance with approved procedures.
- If the test section fails to maintain specified test pressure then HDD shall be abandoned

9.0 DOCUMENTATION

- a) DURING HDD EXECUTION (Record all the below but not limited to the following)
 - Measurement of mud pressure, mud flow rate, pulling force, X-Y coordinates of the dial head.
 - ✓ Standoff operations.
- b) AFTER HDD EXECUTION (but not limited to following)
 - Quality of mud used.
 - ✓ Mud pressure.
 - ✓ Density of drilling fluid & soil cutting.
 - ✓ Location of storage site for waste from the drilling operation and measures taken to comply with environmental constraints.
- c) DURING DRILLING OPERATION
 - ✓ Maximum force applied.
 - ✓ Time duration for assembling 2 drill pipe elements.
 - ✓ Drill head position in X-Y coordinate.
 - Deviation compared to the required position.
- d) DURING PIPE PULL BACK
 - ✓ Pull back duration per element.
 - ✓ Maximum pulling force per elements.
- e) ALIGNMENT SHEET WITH LENGTH PROFILE
 - ✓ Showing locations of each weld joints & then X-Y-Z coordinates
 - ✓ Location of entry and exit points & angles of entry and exit points.
 - ✓ Locations of Pipeline markers.
- (F) Permits from authorized

41

O. A. Page 41







Document No. TPL/IOCL/TE/TC/WP003

- (G) Records of hydro test NDT of welds (with digitization).
- (H) Clearance certificate (NOC) from land owners/ Authorities.

For construction the documents /records shall be submitted to IOCL as following:

- During the execution of crossing detailed drill hole data.
 - a) Torque / Reaming bore log with
 - *Torque and pull force
 - * Pumping rate
 - b) Permits obtained from authorities having jurisdiction for the various works.
 - c) Plan and profile of the drilled hole along with the water level variations.
 - d) Mechanical clearance with pipe book log for pre hydro test and Post hydro test.
- After completion of crossing the following minimum information shall be furnished in the As-build drawing:
 - a) Actual profile of the crossing after completion of pipeline installed and the depth of cover to top of pipe at regular intervals.
 - b) Location of entry and exit points and angles of entry and exit along with lateral offset of exit point from the original pipeline alignment.
 - c) Location of angle of field bends. Joining the mainline hookup
 - d) Location of surrounding details enrooting the pipeline to be mentioned.

10.0 Health, safety and Environment

The HDD technique will be expedited in the shortest time frame possible.

- 2. In case of trench less crossing are adopted when man entry is required inside the pipe following additional safety means shall be taking care.
- 3. All workers should have mandatory PPEs and regular tool Box Talk should be given to workers.
- Width of excavated pit to be maintained as >5 m and steps should be provided.
- Clear and safe access must be maintained continuously while the workers are in confined space.
- 6. Adequate lighting shall be provided at all access and egress points (use only 24 volts/ torch also be used)
- First Aid box to be maintained at site.
- 8. Standby persons and vehicle (In case of emergency)
- 9. Whistle to be provided to worker going under the road (use in case of emergency)
- Warning display board to be installed in English and Regional language. (Work in Progress)
 (Deep Excavation)
- 11. All machine tools & tackles to be maintained as a tested, certified, validated.
- Continuously efficient dewatering system must be in operation.

0.0

Page 12
New Boild

42



spe fic requests from the authomies will be adopted by TPL and will form part of the

ENGIE

Document No. TPL/IOCL/TE/TC/WP003

- 14. Provision will be given for the continuation of normal traffic during the activity.
- 15. Construction entrances /exit locations will be constructed to the minimum width and length with consideration to existing topography, change in road edge height, existing soil geography including compaction characteristics right of way constraints etc.
- Safe disposal of bentonite slurry mud with consent of concerned authorized Person/authority 16. shall be ensured.

Note: In case of any conflict between the requirements of this procedure and contract specification, drawings, EIC instruction shall govern.

43









Document No. TPL/IOCL/TE/TC/WP003

Owne	r: M/S	India	n Oil Corporation	n Limited					
			RACTEBEL ENGIE						
Contr	actor :	M/S T	aurant Projects l	Limited				5	
Doc N	lo: TP	L/IOCL	/TE/TC/WP003/I	R01				A - 24- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	
		AN HOL		INSPECTION REPOR	T FOR PILOT	HOLE DRILL	LOG SHEET		
	Crossii	_				lot Dia :		at No. 01	
	Specifi	cation	1:-			pe OD& THK	: Repo	rt No:	
From		DOD	me to	To:		lot Length :	DOTATION	Drawn Data	Remark
S.NO	DATE	NO	Pitch (Angle)	Distance from Entry pt. to Exit Pt.(Mtrs)	Depth from NGL Level (Mtrs)	Push force (KN)	ROTATION TORQUE	Pump Rate (L/Min)	Kemark
			(1						
									ck
								Mary 1	
Rem	arks (If	any):							
				CHE	CKED AND VER	RIFIED BY			
			FOR	TPL		F	OR TRACTEB	EL/Gallocu	_
SIGN					SIGN:				
NAM					NAME:				
DATE					DATE:				

44

p.mf.

Rage 14

Rage 14

W Delhi

M







Document No. TPL/IOCL/TE/TC/WP003

Project La	aying of 3	LPE Coated Steel	Pipeline Netw	ork & Associat	ted Works in Gro	oup – TC- Th	oothukudi
Owner: M	/S Indian	Oil Corporation Limit	ed				- E
Consultant	: M/S TRA	CTEBEL ENGIE					
		rant Projects Limited					
Dac No :	TPL/IOCL/T	E/TC/WP003/IR02					
			INSPECTIO	N REPORT FOR			Section 2
HDD Cross					eamer Size :		at No 02
PIPE Speci	ification :-				pe OD & THK:		ort No:
From :-	-		0:		eaming Length:	Date:	
S.NO	DATE	ROD NO	Length From	RIG Output L		Pump Rate	Remarks
			Entry Side (Mtrs)	Push/Pull Force (KNm)	Torque Force/ Rotation Load (KNm)	(L/M)	
-							
			<u> </u>				
	7						
Remarks ((If any): -						
				ED AND VERIF			
FOR TPL	-			FOR TRACTEBE	L/Quil TOCL		
SIGN: NAME:				SIGN : NAME :			
DATE:				DATE:			
			N.	271,27			

45

0.MG

Page 15







Document No. TPL/IOCL/TE/TC/WP003

Project	:- Layi	ng of 3LPE Coated :	Steel Pipeline Net	twork & Assoc	iated Works in G	roup – TC- T	hoothukudi
GA							
Owner	: M/S I	ndian Oil Corporation I	imited				
Consul	tant: M/	'S TRACTEBEL ENGIE					
Contra	ctor: M	/S Taurant Projects Lir	mited				
Doc No	: TPL/I	OCL/TE/TC/WP003/IRO)3				
			INSPECTION	ON REPORT FO			
		Name :-			Reamer Size:		et No. 03
	pecifica	tion :-			Pipe OD & THK:		ort No:
From:			To:		Reaming Length:	Date:	
S.NO	DATE	ROD NO	Length From			Pump Rate	Remarks
			Exit Side (Mtrs)	Pull Force (mPA/Psi)	Rotation/ Torque Force Load (KNm)	(L/M)	
						, V	
				-			
Remai	rks (If ar	ıy): -					
			CUTC	KED AND VERIE	HED BY		
FOR T	D)		CHEC		EL/Gail TOCL		
SIGN:				SIGN:		= 16	
NAME				NAME:		8	
DATE	:			DATE:			

46

p.ngc

Page 16 New Delhi







Document No. TPL/IOCL/TE/TC/WP004

Project	Laying of 3LPE Coated Steel Pipeline Network & Associated Works in Group – TC- Thoothukudi GA
Project No.	Works 2318
Client	Indian Oil Corporation Limited
PMC	Tractebel Engie
Contractor	Taurant Projects Limited

PROCEDURE FOR HAZARD IDENTIFICATION AND RISK ASSESSMENT

47

Page 1 of 6

p.M.

IOCL THOOTHUKUDI PROJECT

STEP	Activity	Hazard	Risk		4. IF	3	5. Control Measures& Controls	6 Responsible		7. F	≀R
			Physical Injuries Physical Injuries Personnel Injury Personnel	0							
		Use of regular riggers as Helpers for erection/installation of Boring machine		3	4	Н	allowed to operate the equipment The HSE personnel Operator and task supervisor shall conduct a pre job safety meeting/TBT prior to installation and erection of HDD/Boring machine which will include the HIRAs, Standard Operating Procedures, types of potential hazards, and actual hazards present and controls for those hazards All employees assigned for this		2	3	
		Personal/ Pedestrian movement		3	4	Н	Area of operation shall be barricaded Supervisors shall monitor that entry of unauthorized person is		2	2	
	Assemblin g of HDD/ Boring machine	Use of Hand tools	Injury Ergonomics	3	4	Н	working condition. Use the correct tool for the task. Avoid "knuckle-banging" (i.e., pay attention to direction of torqued tool slips) and wear leather gloves when possible. • Lift heavy objects using the legs		2	3	
		Striking of Overhead electrical line or object during equipment erection	Electrocutio n/Dame to Overhead electrical cable	3	3	H	Necessary precautions shall be	Task Supervisor Site In-Charge	2	2	P

481

Page 2 of 6

Senior Manager (CGD)
SRPL, Tuticorin.

IOCL THOOTHUKUDI PROJECT

2.	HDD Drilling	Generating High noise level	Damage to Hearing due to High sound Fatigue	3	4	н	shall be avoided by maintaining necessary distance from the operation zone when not required Noise monitoring to be done as per HSE plan. Fitness certificate of HDD machine and attached JIB crane to be ensure before executing work at site.	1	3	L
		Inhalation of hazardous dust	Chest pain Lung disease	3	4	Н	Water mist may be sprayed to settle dust from blowing away Dust mask shall be provided and worn by all involve in the activity Task Supervisor / Site In-Charge	2	2	M
		Overheating of machineries	Fire	3	4	Н	Overheating of machinery to be avoided Coolant and water level wherever necessary shall be checked frequently Necessary lubrication to be done on all moving parts of the machineries	2	2	B/A
		Exposure with moving parts of machineries	Physical injury from moving parts of machinery, including change out of drill pipe and core barrel	3	4	н	Maintain safe distance from moving parts of machinery Keep fingers, hands, and arms away from rotating drill head near the top (connection to drive) or near the bottom (hole entrance). Wear leather gloves when handling objects, and steel-toed boots and hard hat at all times. Keep hands away from hydraulic clamps when activated. Keep fingers away from pinch points when screwing pipe joints together. Keep all drill bits secured when not in use, to prevent rolling off the rig or other movement.	2	2	M
		Hoisting Cable	Physical injury from cables under tension that suddenly	3	4	Н	Do not come near cables under tension, such as those lifting drill Site In-Charge Do not come near cables under tension, such as those lifting drill Site In-Charge	2	2	M

IOCL THOOTHUKUDI PROJECT

		release				for signs of damage and wear.				
	Removing cores from core barrel	Hanging core barrel can swing and potentially knock someone on ground	4	3	н	When core barrel is not in use, it should be secured to prevent movement. When loosening material inside the core barrel, position yourself at safe place to avoid being struck by potential deflection of Hammer	Task Supervisor 7 Site In-Charge	2	2	ELTON
Sample	Inhalation of dirt or dust during work activities.	Chest pain Lung disease	3	4	Н	 To avoid inhalation of dust, wear a fit-tested half-face respirator with appropriate cartridges for particles and other potential contaminants, including radio nuclides. Wear rubber or latex gloves to prevent contact with hands and arms. To avoid inhalation or dermal contact from dirt and dust that can accumulate on clothing, wear coveralls or suits that protect regular work clothes, boots, and hair from exposure to dust and dirt. Remove work clothes, including 	Task Supervisor / Site In-Charge	2	2	7
Sample Collection: Soil or Groundwat er.	Contact of dirt or dust after work activities.	Dermatitis	2	4	Н	boots, before entering environments outside of the work site Use leather gloves when handling hot soil cores from the sonic rig. If collection of a soil sample from the core is required, allow the core to cool before handling, or wear decontaminated insulated rubber	Task Supervisor / Site In-Charge	2	2	N
	Splashing water and mud	Eye Injury	2	4	Н	gloves. If water is present in the core barrel above the soil, the person collecting the soil into a plastic sleeve should remove the soil sleeve before all soil is collected, stand back, and allow remaining soil and water to eject from the core barrel. Protect your face with face shield used by grinders to avoid injury	Task Supervisor / Site In-Charge	2	2	N

50

onfe

Page 4 of 6

IOCL THOOTHUKUDI PROJECT

	ā	J	OCL T	H	OO'	ΓH	UKUDI PROJECT				
Nigh Worl	1 1 034/ \/10	sibility	Personnel Injury Conflict with the Villagers	3	3	н •	No work to be done after dark unless necessary permission is obtained from Client/consultant Sufficient light arrangement to be done to maintain proper illumination Permission from local residence to be obtained as drilling sound may be a nuisance for some villagers	/ Site In-Ch		2	2
		reduce damage facilitie	or avoid the like to adjacent ur es, including pi	celih derg pelin	ood of ground	belo	We will lay down the pipe line ow existing utilities in presence of ities holder.	Task Supervisor / Site In- Charge	11		
	HDD WOOK	consider method structure position drilling given to location manual the dril	ering the accuration of the pilot stands of th	isting tring to sho ciliar lude ensu	he during ould be y re that	the furt	n case of damage, we will rectify utilities then and there before we her carry on the our drilling work. Add manual trenching will be done ocate other utilities in the corridor	Task Supervisor / Site In- Charge			
		Personnel Injury Visibility Conflict 3 3 3	and	While Carrying out HDD, drilling piloting shall be tracked to avoid age to other utilities	Task Supervisor / Site In- Charge						
		injuries reviewe constru	. The safety placed on site with a ction personnel	an sh all I pric	all be or to			Task Supervisor / Site In- Charge			

	b) Damage prevention plan to reduce or avoid the likelihood of damage to adjacent underground facilities, including pipelines, utilities, cables and other	1. We will lay down the pipe line below existing utilities in presence of utilities holder.	Task Supervisor / Site In- Charge
	subsurface structures considering the accuracy of the method in locating existing structures and in tracking the position of the pilot string during drilling. Consideration should be	2. In case of damage, we will rectify the utilities then and there before we further carry on the our drilling work.	
	given to having an auxiliary location system to include manual excavation to ensure that		Task Supervisor / Site In- Charge
HDD WOOK	the drilling bit or reamer is following the projected path and does not encroach upon crossing or parallel lines. The damage	3. Add manual trenching will be done to locate other utilities in the corridor	
	prevention plan should include provision for sending notification to allc) Safety plan to include contingency plans in the event the drilling string impacts subsurface facilities and identify facilities and resources to be utilized in the event of an emergency or any personnel injuries. The safety plan shall be	4. While Carrying out HDD, drilling and piloting shall be tracked to avoid damage to other utilities	Task Supervisor / Site In- Charge
	reviewed on site with all construction personnel prior to the commencement of drilling		Task Supervisor / Site In- Charge

IOCL THOOTHUKUDI PROJECT


			RISK MAT	RIX		
		Severity				
		l. Minor No or Minor Injury	2 Moderate Off Site Medical Treatment	3 Serious Serious Injury & LTI	4. Major More than One LTI	5. Significant Permanent Disability and Fatality
Probability (Likelihond of the Occurance)	5. Will Occur in present state	5	10	15	20	26
	4. More likely to occur than not	4	8	12	(10)	20
	3. Possible 50/50 chance		6	9	12	
	2. Unlikely Could occur less than 50/50 chance		4	6	8	10
	1. Very Unlikely little or no chance of occurrence				4	5


	1-3	Low Risk	Managed by routine procedures May be acceptable, however review to see if risk can be reduced further
	1-6	Modrate Risk	Task should only proceed with appropriate management authorisation
	8-12	High Risk	Task needs further review and consultation with specialists and where possible the task should be re-defined to take account of the hazards involved or the risk should be reduced to further before the task is allowed to commence
The state of	15-25	Extreme Risk	Task should not proceed


[52]


RANJITH KUMARN *
Senior Manager (CGD)
SRPL, Tuticorin.


Page 6 of 6


































































NHAI, PIU, Nagercoil









TITLE: Proposed Steel Gas Pipeline
CROSS SECTION DRAWING OF RAILWAY CROSSING AT NIH-44 KM 150/554 BY HDD METHOD
CLET AS DESERVATION LIMITED
CLET AS DESERVATION LIMITED
CLET AS DESERVATION ASSESSED.
Phones No. STATO-24468848 Assessed Senior Manager (CGD) SRPL, Tuticorin. 79 OF 90 RANJITH KUMAR I 0 3 3 2 (2m X MZ.I INDIAN OIL CORPORATION LIMITED CITY GAS DISTRIBUTION ENGINEER, PROJECT, PROGRESSION GA. PROJECT SPACES NO. 91-120-2448844,1448888. Exit Pit PROJECT DIRECTOR NHAI, PIU, Nagercoil 10.75" dia Carbon steel Pipe (API 5L-X 52 grade) 6.4 mm wall thickness 1. ALL DIMENSIONS ARE IN METER
2. ONLY WRITTEN DIMENSIONS SHALL BE FOLLOWED.
DO NOT SCALE THE DRAWING
3. DRAWING NOTTO SCALE HDD CROSSING LENGTH SECTION A-A M 0.8 NIM 89 mm OD HDPE OFC Cable AUTHORITE SIGNATORY FOR INDIAN OIL CORPORATION LIMITED Entry Pit (2m 🛪 Proposed Steel Gas P/L Ground Profile NH ROW ωS 5 regends:

0 TITLE: Proposed Steel Gas Pipeline CROSS SECTION DRAWING OF ROAD CROSSING AT NH44 BY SHDD METHOD -10.75" dia Carbon steel Pipe (API 5L-X 52 grade) 6.4 mm wall thickness INDIAN OIL CORPORATION LIMITED CITY GAS DISTRIBUTION RIGHEST, PROPERTY REPORT PROPERTY OF THE G Exit Pit (2m X 2m) m2.1 nim PROJECT DIRECTOR NHAI, PIU, Negercoil -Surface Course 50mm Holmix pavement shown without stabilization is 9-To be verified by Engineer after formation Provide Subgrade improvement as directed On site. 1. ALL DIMENSIONS ARE IN METER
2. ONLY WRITTEN DIMENSIONS SHALL BE FOLLOWED.
DO NOT SCALE THE DRAWING
3. DRAWING NOT TO SCALE SHDD CROSSING LENGTH SECTION A-A ROAD WIDTH M 0.E NIM NOTES: Sub Base 1 Course 200mm,40 F.C.R - Base Course, 20mm F.C.R V V LIM TUTICORIN 89 mm OD HDPE OFC Cable SEPL AUTHORITE SIGNATORY FOR INDIAN OIL CORPORATION LIMITED Entry Pit (2m X 2m) Proposed Steel Gas P/L mS.1 nim Ground Profile G Legends:

SHEET NO. 81 OF 90 TITLE: Proposed Steel Gas Pipeline cRoss section Drawing of NH-44 ROAD crossing AT KM 159422 BY HDD METHOD $\frac{\Gamma}{E_{X}}$ Exit Pit (2m X 2m) MC'Į RUW INDIAN OIL CORPORATION LIMITED CITY GAS DISPAIGNTON PROJECT, PHONN NO. 91-120-246864, 2448888. METTI LIMITE CORPORATION TUTICORIN) SRPL -Surface Course SOmm Hotmix PROJECT DIRECTOR BY NHAI, PIU, Nagercoil 710 4.50" dia Carbon steel Pipe (API 5L-X 52 grade) 6.4 mm wall thickness pavement shown without stabilization is 9-toTo be verified by Engineer offer fornation
Provide Subgrade improvement as directed in site. Approved Subgrade -Mn C.b.r 1. ALL DIMENSIONS ARE IN METER
2. ONLY WRITTEN DIMENSIONS SHALL BE FOLLOWED.
DO NOT SCALE THE DRAWING
3. DRAWING NOT TO SCALE. HIGHWAY ROW WIDTH 60,00m CARRIAGE WIDTH 33.00m P HDD CROSSING LENGTH CRUSSING SECTION A-A F.C.R Base 1 Course 200mm,4M -Base Course, 20mm F.C.R NOTES: 89 MM OD HDPE OFC Cable— V DRAWING AUTHORITE SIGNATORY FOR INDIAN OIL CORPORATION LIMITED SECTION E Entry Pit (2m X 2m) Proposed Steel Gas P/L Ground Profile NHROW RDW 1'24 占 Legends:

SHEET NO. 82 OF 90 TITLE: Proposed Steel Gas Pipeline cRoss section brawns of NH-44 ROAD cRossing AT KM 157/341 BY HDD METHOD Exit Pit (2m X 2m) J'2W RUW INDIAN OIL CORPORATION LIMITED CITY GAS DISPRISHTON PROJECT, PROFING & PROFING CAN PROFING CAN PROFINE CAN PAGE 1, 220-2448844, 2448888. LIMITED METHILL (TUTICORIIN) CORPORATIO SRPL 710 -Surface Course 50mm Hotmix PROJECT DIRECTOR BY NHAI, PIU, Nagercoil 4.50" dia Carbon steel Pipe (API 5L-X 52 grade) 6.4 mm wall thickness povement shown without stabilization is 9-toTo be verified by Engineer after formation provide Subgrade improvement as directed In site. Approved Subgrade -Mn C.b.r Required for 157 I. ALL DIMENSIONS ARE IN METER
2. ONLY WRITTEN DIMENSIONS SHALL BE FOLLOWED.
DO NOT SCALE THE DRAWING
3. DRAWING NOT TO SCALE. HIGHWAY RDW WIDTH 60,00m <u>├</u> CARRIAGE WIDTH 25,00m HDD CROSSING LENGTH SECTION A-A 0.E NIM Sub Base 1 Course 200mm,492 F.C.R -Base Course, 20mm F.C.R NOTES: RIMAD 89 mm OD HDPE OFC Cable— AUTHORITE SIGNATORY FOR INDIAN OIL CORPORATION LIMITED SECTION E Entry Pit (2m X 2m) Proposed Steel Gas P/L **Ground Profile** NHROW ROM 15 님 Legends

SHEET NO. 83 OF 90 TITLE: Proposed Steel Gas Pipeline cROSS SECTION DRAWING OF NH-44 ROAD CROSSING AT KM 150/005 BY HDD METHOD Exit Pit (2m X 2m) J'2W RDW INDIAN OIL CORPORATION LIMITED CITY GAS DISPILIUMING MOLECT, PROPRIED SANGER (2448888).

Phone No. 91-120-2448844 (2448888). LIMITED METHO TUTICORIN CORPORA SRPL qq= 710 N -Surface Course 50mm Hotmlx PROJECT DIRECTOR NHAI, PIU, Nagercoil BY 10.75" dia Carbon steel Pipe (API 5L-X 52 grade) 6.4 mm wall thickness 148/038 pavement shown without stabilization is a stabilization is 9-to-free formation provides Subgrade improvement as directed in site. Approved Subgrade –Mn C.b.r Required for 1. ALL DIMENSIONS ARE IN METER
2. CONLY WRITTEN DIMENSIONS SHALL BE FOLLOWED.
DO NOT SCALE THE DRAWING
3. DRAWING NOT TO SCALE HIGHWAY ROW WIDTH 60.00m CARRIAGE WIDTH 25,00m HDD CROSSING LENGTH SECTION A-A Fig.R A A MIN 3.0 M -Base Course, 20mm F.C.R NOTES: 89 mm OD HDPE OFC Cable AUTHORITE SIGNATORY FOR INDIAN OIL CORPORATION LIMITED SECTION E Entry PIt (2m X 2m) Proposed Steel Gas P/L Ground Profile NHROW RDW 1,51 9 Legends:

SHEET NO. 84 OF 90 TITLE:

Proposed Steel Gas Pipeline
GROSS SECTION DRAWING OF NH44 ROAD CROSSING AT KM 144/338 BY HDD METHOD Exit Pit (2m X 2m) J'2W ROW INDIAN OIL CORPORATION LIMITED CITY CAS DISTRIBUTION PROJECT, PHONE NO. 91-120-2448844, 2448889. METHUL MITED TUTICORIN CORPORA -Surface Course 50mm Hotmlx 710 图× PROJECT DIMECTOR NHAI, PIU, Nagercoil 138/478 4.5" dia Carbon steel Pipe (API 5L-X 52 grade) 6.4 mm wall thickness prequired for metal statement shown without stabilization is 9-2 stabilization in 9-2 stabilization in 9-2 stabilization in 9-2 stabilization for metal of stabilization stabilization stabilization provide Subgrade improvement as directed in site. Approved Subgrade -Mn C.b.r Required for 1. ALL DIMENSIONS ARE IN METER
2. ONLY WRITTEN DIMENSIONS SHALL BE FOLLOWED.
DO NOT SCALE THE DRAWING
3. DRAWING NOT TO SCALE. HIGHWAY ROW WIDTH 60,00m CARRIAGE WIDTH 20.00m HDD CROSSING LENGTH SECTION A-A F.C.R Base 1 Course 200mm,4M -Base Course, 20mm F.C.R NOTES: 89 mm OD HDPE DFC Cable AUTHORITE SIGNATORY FOR INDIAN OIL CORPORATION LIMITED SECTION Entry Pit (2m X 2m) Proposed Steel Gas P/L Ground Profile NHROW КПМ 1,5, 5 Legends:

SHEET NO. 85 OF 90 RANJITH KUMAR N TITLE: Proposed Steel Gas Pipeline
CROSS SECTION DRAWING OF NALA CROSSING AT NH 44 CH 157/555 BY HDD METHOD
CALINIT: INDIAN OIL CORPORATION LIMITED
STEELTRY PURSTOR - 1, WORDAN MARK,
RECTOR - 1, MOTHAN OIL (V.P.) 1987 PR Senior Manager (CGD) SRPL, Tuticorin. Exit Point 1,5 m2,1 INDIAN OIL CORPORATION LIMITED REPEATER INVESTOR: A-1, WINDIA (V. 2.7) ENDRE NO. 91-110-2446844, 2446889. PROJECT DIRECTOR 10.75" dia Carbon steel Pipe (API 5L-X 52 grade) 6.4 mm wall thickness NHAI, PIU, Nagercoil 1. ALL DIMENSIONS ARE IN METER
2. ONLY WRITTEN DIMENSIONS SHALL BE FOLLOWED.
DO NOT SCALE THE DRAWING
3. DRAWING NOT TO SCALE HDD CROSSING LENGTH RIVER MO.E NOTES: 89 mm OD HDPE OFC Cable AUTHORITE SIGNATORY FOR INDIAN OIL CORPORATION LIMITED Entry Pit (2m X 2m) Entry Point Pospinged Steel Gas P/L Ground Profile Ħ Legends:

RANJITH KUMAR N Senior Manager (CGD) SRPL, Tuticorin. SHEET NO. 86 OF 90 Exit Point ws I Exit Pit (2m X 2m) PROJECT DIRECTOR 10.75" dia Carbon steel Pipe (API 5L-X 52 grade) 6.4 mm wall thickness NHAI, PIU, Nagercoil 1. ALL DIMENSIONS ARE IN METER
2. ONLY WRITTEN DIMENSIONS SHALL BE FOLLOWED.
DO NOT SCALE THE DRAWING
3. DRAWING NOT TO SCALE HDD CROSSING LENGTH RIVER MO'E NOTES: 89 mm OD HDPE OFC Cable AUTHORITE SIGNATORY FOR INDIAN OIL CORPORATION LIMITED Entry Pit (2m X Pm) En.try Point Pospinged Steel Gas P/L Ground Profile 5 Legends:

RANJITH KUMAR N Senior Manager (CGD) SRPL, Tuticorin. SHEET NO. 87 OF 90 TITLE: Proposed Steel Gas Pipeline
CROSS SECTION DRAWING OF RIVER CROSSING AT NH 44 CH 1537/01 BY HDD METHOD
CLEMT: INDIAN OIL CORPORATION LIMITED SHEET NO
EVERTINE VINTENDE A.T., USEDO NAVA, USED N Exit Point MG'I Exit Pit (2m X 2m) O. P.C INDIAN OIL CORPORATION LIMITED PLERLINE DIVISION: A-1, UDBIOG HARG, SECRE-1, NOIDA-201 301 (V.P.)
PROME NO. 21 2120-2448844, 2448888. PROJECT DIRECTOR NHAI, PIU, Nagercoil 10.75" dia Carbon steel Pipe (API 5L-X 52 grade) 6.4 mm wall thickness 1. ALL DIMENSIONS ARE IN METER
2. ONLY WRITTEN DIMENSIONS SHALL BE FOLLOWED.
3. DRAWING NOT SCALE THE DRAWING
3. DRAWING NOT TO SCALE HDD CROSSING LENGTH RIVER MO'E 89 mm 0D HDPE OFC Cable AUTHORITE SIGNATORY FOR INDIAN OIL CORPORATION LIMITED Entry Pit (2m X 2m) Entry Point Foreignged Steel Gas P/L Ground Profile 15 Legends:

RANJITH KUMAR N Senior Manager (CGD) SRPL, Tuticorin. SHEET NO. NOTES:
Proposed Steel Gas Pipeline
CROSS SECTION DRAWING OF CANAL CROSSING AT NH 44 CH 140/322 BY HDD METHOD
2. ONLY WRITTEN DIMENSIONS SHALL BE FOLLOWED.
DO NOT SCALE THE DRAWING
3. DRAWING NOT TO SCALE
4. DRAWING NOT TO SCALE
4. DRAWING NOT TO SCALE
5. DRAWING NOT TO Exit Point Exit Pit (2m X 2m) INDIAN OIL CORPORATION LIMITED PEPRLARE DIVISION: A-1, UNEXON MANG, BECTON-1, WOIDA-COL 301 (U. P.)
Phone No. 91-120-246864, 2448889. PROJECT DIRECTOR NHAI, PIU, Nagercoil 10.75" dia Carbon steel Pipe (API 5L-X 52 grade) 6.4 mm wall thickness HDD CROSSING LENGTH RIVER 3'0W 89 mm OD HDPE OFC Cable AUTHORITE SIGNATORY FOR INDIAN OIL CORPORATION LIMITED E Entry Pit (2m X 2m) Entry Point Programmed Steel Gas P/L Ground Profile 5 Legends:

RANJITH KUMAR N Senior Manager (CGD) SRPL, Tuticorin. SHEET NO. 89 OF 90 TITLE: Proposed Steel Gas Pipeline
CROSS SECTION DRAWING OF NALA CROSSING AT NH 44 CH 139391 BY HDD METHOD
CHEW! INDIAN OIL CORPORATION LIMITED SHEET NG
PRETRONG - 1, NOTHER - 20, 1 502 U.V.P.) 89 OF 99 Exit Point Exit Pit (2m X 2m) 리 제요,1 INDIAN OIL CORPORATION LIMITED PAPELINE DEVIATION 2013 St. (10.12.)
Phode No. 91-120-246864, 244888. PROJECT DIRECTOR NHAI, PIU, Nagercoil 10.75" dia Carbon steel Pipe (API 5L-X 52 grade) 6.4 mm wall thickness 1. ALL DIMENSIONS ARE IN METER
2. ONLY WRITTEN DIMENSIONS SHALL BE FOLLOWED.
3. DON'S YOLLE THE DRAWING
3. DRAWING NOT'TO SCALE HDD CROSSING LENGTH RIVER MIN MIN 89 mm 0D HDPE OFC Cable AUTHORITE SIGNATORY FOR INDIAN OIL CORPORATION LIMITED Entry Pit (2m X 2m) Entry Point Pospinged Steel Gas P/L Ground Profile 15 Legends:

