


भारतीय राष्ट्रीय राजमार्ग प्राधिकरण

(सड़क परिवहन और राजमार्ग मंत्रालय, भारत सरकार)

National Highways Authority of India

(Ministry of Road Transport & Highways, Govt. of India)



NHAI/12013/1/PIU-Jhansi/OFC- Km. 91.100 to 97.100 /2023/223 | Dated

18 September, 2023

Invitation of Public Comments

Sub: Request for grant of Right of Way Permission to lay Optical Fiber Cable along the route from Km. 91.100 to Km. 97.100 (between Shivpuri Bypass- Athodana GP FPOI) and 01 Road Crossing total length 06 km on NH-27 Jhansi-Orai Section in District-Jhansi Uttar Pradesh.

The Authorized Signatory M/s.Bharat Sanchar Nigam Limited (A ·Government of India Enterprises), Jhansi has submitted the proposal for grant of Right of Way Permission to lay Optical Fibre Cable along the route from Km. 91.100 to Km. 97.100 - Total Length 06 Km with 01 Road Crossing on NH-27, Jhansi-Orai Section in District- Jhansi U.P.

- 2. As per the guidelines, issued by the Ministry vide OM No. RW/NH-33044/29/2015/S&R (R) dated 22.11.2016, the application shall be put out in the public domain for 30 days for seeking claims and objections (on grounds of public convenience, safety and general public interest).
- 3. In view of the above, comments of the public on the above application is invited to the below mentioned address, which should reach by this office within 30 days from the date of publication beyond which no comments shall be entertained.

The Project Director National Highway Authority of India Project Implementation Unit House No. N 43/1 A, Infront of Govt. Mahila Polytechnic, Gwalior Road, Jhansi - 284003 (U.P.)

This is issued with the direction of NHAI, RO, (West)-UP, Lucknow.

Encl: As Above.

(Sunil Kumar Jain) Project Director

Copy to:-

1. Web Admin, NHAI-HQ- with request for uploading on the NHAI website.

2. The Technical Director, NIC, Transport Bhawan, New Delhi- with request for uploading on the Ministry's website.

3. The Authorized Signatory, M/s. Bharat Sanchar Nigam Limited (A Government of India Enterprises), Office of the General Manager, Telecom District- Jhansi for information.

क्षेत्रीय कार्यालय : पश्चिम (उ.प्र.), 3/248, विशाल खण्ड, गोमती नगर, लखनऊ-226010 (उ.प्र.) Regional Office : West (U.P.), 3/248, Vishal Khand, Gomti Nagar, Lucknow-226010 (U.P.)

मुख्यालय : जी ५-६, सेक्टर-१०, द्वारका, नई दिल्ली - ११००७५

Head Office: Plot No.: G-5 & 6, Sector-10, Dwarka New Delhi - 110075

दूरभाष/Phone :

0522-4960291

फेक्स/Fax : 0522-4950680 दुरभाष/Phone : 91-11-25074100/200

फैक्स/Fax :91-11-25093507/514

CHECK-LIST

Guidelines for Project Director for processing the proposal for laying of OFC cable etc. in the land along national Highways vested with NHAI

Relevant circulars of Ministry of Road Transport and Highway

- 1) circular no. RW/NH/33044/17/2000-S&R dated 29.9.2000
- 2) circular No. NHAI/OEC/2k/Vol-II dated 7.11.2000
- 3) circular No. RW/NH/33044/17/2000/S&R dated 23.7.2003
- 4) circular No.RW/NH/33044/27/2000-S&R(r)dated 23.03.2006

Check list for getting approval for laying of OF cable on NH land (to be filled by the PIU)

The permission for laying of OFC cable shall be considered for approval/rejection based on the ministry circular mentioned as above.

S.	No.	Item		
	1	General information	Information/Status	Remarks
	1.1	name and address of the applicant/agency	NH-27	
	1.2	National Highway number	BSNL JHANSI	
	1.3	state	27	
			Uttar pradesh	
	1.4	Location	Shivpuri Bypass to Athodana	
1	1.5	(chainage in KM)	GPPPOI	
1	L.6	Length in meters	91.1 to km 97.1 Km	
1	7		6000 M	
-	L.7 ———	Width of available ROW	30M	
		(a) Left side from center line towards increasing chainage/km direction	30M	
		(b) Right side from center line towards increasing chainage/km direction	30M	
1	.8	Proposal to lay the OFC cable		
		(a) Left side from center line towards increasing chainage/km direction	91.1 to km 97.1 Km	
		(b) Right side from center line towards increasing chainage/km direction		
1.		Proposal to acquire land	NA.	
		(a) Left side from center line	NA	
		(b) Right side from center line		
1.:	1	Whether proposal is in the same side where land is not to be acquired	Yes	
		f not then where to lay the cable		
1.1		Details of already laid services if any , along the proposed route		
1.1	2 1	Number of lanes (2/4/6/8 lanes) existing	4	

Asstt. Highway Maintenance Engineer Lion Engineering Consultants Pvt. Ltd. Jhansi-Orai Section, NH-27

Team Leader (Acr.)
Lion Engineering Consultants Pvt. Ltd.
Jhansi-Orai Section, NH-27

A.G.M. (A & P) O/o GMTD, BSNL JHANSI

E	Proposed number of lanes (2 lane with paved shoulders 2/4/6/	8	
1.13	lanes)	NA	
1.14	Service road existing or not	Yes	
F	If yes then which side	103	
-	(a) Left side from center line	Yes	
4.45	(b) Right side from center line	Yes	
1.15	Proposed service road	No	
	(a) Left side from center line	, and	
	(b) Right side from center line		
1.15	Whether proposal to lay cable is after the service road or		
1.16	between the service road and main carriageway	after the service road	
	The permission for laying OFC shall be considered for		
1.17	approval/rejection		
	(i)where the ROW is more than 45 m then the duct cable shall be laid at the edge of right of way within the utility corridor of 2 m width, duly keeping in view the future widening.	Ofe Co extr Yes Rou	able laid on enerolged - 28 to 307 Dan
	(ii) where land is yet to be acquired for 4 laning and the position of new carriageway has been decided then the cable shall be laid at the edge of right of way within the utility corridor of 2m width, on that side of existing carriageway where extra land is not proposed to be acquired for 4 laning.	NA *)	
	(iii) whether the widening plan for naning is not yet decided and available ROW is around 30m or less, a judicious decision would need to be taken for permitting the laying OF cable/duct. This could be within 1.5 m to 2m of utility corridor at the edge of existing ROW, duly keeping in view the possible widening plans.	NA	
	(iv) where ROW is restricted and adequate only to accommodate the carriageway, central verge, shoulders and drains (e.g. highway in cutting through hilly/rolling terrain), the cable shall be laid clear of the drain.	Yes	
	(v) where laid strip for utility corridor cannot be conveniently earmarked (available ROW restricted to the toe of the embankment) for laying OF cable/ducts, the permission may be refused.	NA	
1.18	No. of applicants on the same stretch	one	
	whether the case of multiple licenses	No	
	If crossing of the road involved		
	If YES, it shall be either encased in pipes or through structure or	VEC	41 D. 461 T
	conduits specially built for that purpose	YES	
- 6	at the expense of the agency owning the line		
á	a) whetner the existing drainage structures are allowed to carry		
t	he utility pipeline	NO	
	(/VL)		

Team Leader (Act)
Lion Engineering Consultants Pvt. Ltd.
Jhansi-Orai Section, NH-27

A.G.M. (A& P) O/o GMTD, BSNL JHANSI

bis it on aline normal to the NH CIWhat is the distance of crossing the utility pipe (lines from the existing structures on the national highway. All the casing pipe carrying the utility line shall be of steel cast iron pr reinforced cement concrete and have adeouate srength and be large enough to permit ready withdrawl of carrier pipe/cable Mention type of casing e)Ends of the casing /Conduit pipe shall be sealed from the outside so that it doesnot act as a drainage patn (Fifthe casing/conduit pipe should as minimum extend from drain to drain in cuts and toe of slope n fills g) The top of the casing /conduit pipe should as minimum extend from drain to drain in cuts and toe of slope n fills g) The top of the casing /conduit pipe should be atleast 1.2 meter below the surface of the road subject to being at least 0.3 meter below the drain inverts mention the proposed details h)Mention the methodology proposed for crossing of road for the proposed sewage /Gas pipe line c.crossing shall be by boring method HDD.speci III, where the existing road pavement is of cement concrete or dense bituminolus concrete type. i)The casing/conduit pipe shall be installed with an even bearing throughout its length and in such a manner as to prevent the formation of a water way along it. If so furnish a joint implementation programme to lay their respective ducts within stipulated time frame If crossing of the road involved fif Yes it shall only be through trench-less technology Documents/Drawing enclosed with the proposal Cross section showing the size of trench for open trenching method (is it normal size of 1.65 m deep x 0.45 m wide) should not be greater than 1.2 m in width in multiple ducts Cross section showing the size of pit and location OF cable for Yes Strip plan? Route plan showing the OFC, chainage, width of ROW, distance of proposed, cable from the edge of ROW, important mile stone, cross farinage works etc.				
c)What is the distance of crossing the utility pipe pipe (ines from the existing structures or the national highway. All of the casing pipe carrying the utility line shall be of steel cast iron preinforced cement concrete and have adeouate srength and be large enough to permit ready withdrawl of carrier pipe/cable Mention type of casing Mention type of casing Mention type of casing Pipe casing conduit pipe shall be sealed from the outside.so that it doesnot act as a drainage path Fig. 1 he casing/conduit pipe should as minimum extend from drain to drain in cuts and toe of slope in fills g) The top of the casing /conduit pipe should be atleast 1.2 meter below the surface of the road subject to being at least 0.3 meter below the drain inverts mention the proposed details h)Mention the methodology proposed for crossing of road for the proposed sewage /Gas pipe line Crossing shall be by boring method HDD.speci III, where the existing road pavement is of cement concrete or dense bituminous concrete type. JiThe casing/conduit pipe shall be installed with an even bearing throughout its length and in such a manner as to prevent the formation of a water way along it. If so furnish a joint implementation programme to lay their respective ducts within stipulated time frame ff crossing of the road involved Cross section showing the size of trench for open trenching method (is it normal size of 1.65 m deep x 0.45 m wide) should not be greater than 1.2 m in width in multiple ducts Cross section showing the size of pit and location OF cable for HDD method Strip plan/ Route plan showing the OFC, chainage, width of ROW, distance of proposed, cable from the edge of ROW, important mile stone, intersection, cross drainage works etc.	1	b)is it on aline normal to the NH		
pipe(ines from the existing structures on the national highway. d)The casing pipe carrying the utility line shall be of steel cast iron pr reinforced cement concrete and have adeouate srength and be large enough to permit ready withdrawl of carrier pipe/cable Mention type of casing e)Ends of the casing /Conduit pipe shall be sealed from the outside.so that it doesnot act as a drainage path f)The casing/conduit pipe should as minimum extend from drain to drain in cuts and toe of slope in fills g) The top of the casing /Conduit pipe should be atleast 1.2 meter below the surface of the road subject to being at least 0.3 meter below the drain inverts mention the proposed details h)Mention the methodology proposed for crossing of road for the proposed sewage /Gas pipe line c. crossing shall be by boring method HDD.speci inv where the existing road pavement is of cement concrete or dense bituminous concrete type. i)The casing/conduit pipe shall be installed with an even bearing throughout its length and in such a manner as to prevent the formation of a water way along it. If so furnish a joint implementation programme to lay their respective ducts within stipulated time frame ff crossing of the road involved fressite of the road involved Cross section showing the size of trench for open trenching method (is it normal size of 1.65 m deep x 0.45 m wide) should not be greater than 1.2 m in width in multiple ducts Cross section showing the size of pit and location OF cable for HDD method Strip plan/ Route plan showing the OFC, chainage, width of ROW, distance of proposed, cable from the edge of ROW, important mile stone, laters of the cable from the edge of ROW, important mile stone, laters of the cable for HDD method 2.4 Methodology for laying of OFC And the definition of the top of the cable for HDD method of OFC.		c)What is the distance of crossing the utility		
srength and be large enough to permit ready withdrawl of carrier pipe/cable Mention type of casing e]Ends of the casing /Conduit pipe shall be sealeo from the outside.so that it doesnot act as a drainage patn YES f)The casing/conduit pipe should as minimum extend from drain to drain in cuts and toe of slope n fills g] The top of the casing /conduit pipe should be atleast 1.2 meter below the surface of the road subject to being at least 0.3 meter below the drain inverts mention the proposed details h)Mention the methodology proposed for crossing of road for the proposed sewage /Gas pipe line .Crossing shall be by boring method HDD.speci 150 where the existing road pavement is of cement concrete or dense bituminols concrete type. i)The casing/conduit pipe shall be installed with an even bearing throughout its length and in such a manner as to prevent the formation of a water way along it. If so furnish a joint implementation programme to lay their respective ducts within stipulated time frame If crossing of the road involved 1.21 if yes it shall only be through trench-less technology Documents/Drawing enclosed with the proposal Cross section showing the size of trench for open trenching method (is it normal size of 1.65 m deep x 0.45 m wide) should nethod (is it normal size of 1.65 m deep x 0.45 m wide) should nethod (is it normal size of proposed, cable from the edge of ROW, internal content of the proposal of the cost of 1.65 m deep x 0.45 m wide) should nethod (is it normal size of proposed, cable from the edge of ROW, internal content of the proposal of the cost of 1.65 m deep x 0.45 m wide) should not proposal of 1.65 m deep x 0.45 m wide) should not proposal of 1.65 m deep x 0.45 m wide) should not proposal of 1.65 m deep x 0.45 m wide) should not proposal of 1.65 m deep x 0.45 m wide) should not proposal of 1.65 m deep x 0.45 m wide) should not proposal of 1.65 m deep x 0.45 m wide) should not proposal of 1.65 m deep x 0.45 m wide) should not proposal of 1.65 m deep x 0.45 m wide) should not propo		pipe(ines from the existing structurescrOssing shall not be too near the existing structures on the national highway.	NA	
e)Ends of the casing /Conduit pipe shall be sealed from the outside.so that it doesnot act as a drainage patn f)The casing/conduit pipe should as minimum extend from drain to drain in cuts and toe of slope n fills g] The top of the casing /conduit pipe should be atleast 1.2 meter below the surface of the road subject to being at least 0.3 meter below the drain inverts mention the proposed details h)Mention the methodology proposed for crossing of road for the proposed sewage /Gas pipe line .Crossing shall be by boring method HDD.speci in where the existing road pavement is of cement concrete or dense bituminoLls concrete type. i)The casing/conduit pipe shall be installed with an even bearing throughout its length and in such a manner as to prevent the formation of a water way along it. If so furnish a joint implementation programme to lay their respective ducts within stipulated time frame If crossing of the road involved if Yes it shall only be through trench-less technology Documents/Drawing enclosed with the proposal Cross section showing the size of trench for open trenching method (is it normal size of 1.65 m deep x 0.45 m wide) should not be greater than 1.2 m in width in multiple ducts Cross section showing the size of pit and location OF cable for 4.2.4 HDD method 2.3 important mile stone, intersection, cross drainage, width of ROW, distance of proposed, cable from the edge of ROW, important mile stone, intersection, cross drainage works etc.		srength and be large enough to permit ready withdrawl of carrier pipe/cable		
from the outside.so that it doesnot act as a drainage patn f)The casing/conduit pipe should as minimum extend from drain to drain in cuts and toe of slope n fills g] The top of the casing /conduit pipe should be atleast 1.2 meter below the surface of the road subject to being at least 0.3 meter below the drain inverts mention the proposed details h)Mention the methodology proposed for crossing of road for the proposed sewage /Gas pipe line .Crossing shall be by boring method HDD.speci inv where the existing road pavement is of cement concrete or dense bituminoLls concrete type. i)The casing/conduit pipe shall be installed with an even bearing throughout its length and in such a manner as to prevent the formation of a water way along it. if so furnish a joint implementation programme to lay their respective ducts within stipulated time frame if crossing of the road involved if Yes it shall only be through trench-less technology Documents/Drawing enclosed with the proposal Cross section showing the size of trench for open trenching method (is it normal size of 1.65 m deep x 0.45 m wide) should not be greater than 1.2 m in width in multiple ducts Cross section showing the size of pit and location OF cable for Yes Strip plan/ Route plan showing the OFC, chainage, width of ROW, distance of proposed, cable from the edge of ROW, inportant mile stone, intersection, cross drainage works etc.	-	Iviention type of casing	HDPF Pipo	
g! The top of the casing /conduit pipe should be atleast 1.2 meter below the surface of the road subject to being at least 0.3 meter below the drain inverts mention the proposed details h)Mention the methodology proposed for crossing of road for the proposed sewage /Gas pipe line . Crossing shall be by boring method HDD.speci ;iii, where the existing road pavement is of cement concrete or dense bituminoLis concrete type. l)The casing/conduit pipe shall be installed with an even bearing throughout its length and in such a manner as to prevent the formation of a water way along it. If so furnish a joint implementation programme to lay their respective ducts within stipulated time frame If crossing of the road involved if Yes it shall only be through trench-less technology Documents/Drawing enclosed with the proposal Cross section showing the size of trench for open trenching method (is it normal size of 1.65 m deep x 0.45 m wide) should not be greater than 1.2 m in width in multiple ducts Cross section showing the size of pit and location OF cable for LDD method Strip plan/ Route plan showing the OFC, chainage, width of ROW, distance of proposed, cable from the edge of ROW, important mile stone, intersection, cross drainage works etc. Jet of the casing /conduit pipe should be atleased and the drain involved in the greater than 1.2 m in width of ROW, distance of proposed, cable from the edge of ROW, important mile stone, intersection, cross drainage works etc.		from the outside.so that it doesnot act as a drainage path		
atteast 1.2 meter below the surface of the road subject to being at least 0.3 meter below the drain inverts mention the proposed details h)Mention the methodology proposed for crossing of road for the proposed sewage /Gas pipe line Crossing shall be by boring method HDD.speci inverted the existing road pavement is of cement concrete or dense bituminouls concrete type. i)The casing/conduit pipe shall be installed with an even bearing throughout its length and in such a manner as to prevent the formation of a water way along it. If so furnish a joint implementation programme to lay their respective ducts within stipulated time frame if crossing of the road involved if Yes it shall only be through trench-less technology Documents/Drawing enclosed with the proposal Cross section showing the size of trench for open trenching method (is it normal size of 1.65 m deep x 0.45 m wide) should not be greater than 1.2 m in width in multiple ducts Cross section showing the size of pit and location OF cable for Yes Strip plan/ Route plan showing the OFC, chainage, width of ROW, distance of proposed, cable from the edge of ROW, important mile stone, intersection, cross drainage works etc.		urain to drain in cuts and toe of slope n fills	•	
h)Mention the methodology proposed for crossing of road for the proposed sewage /Gas pipe line .Crossing shall be by boring method HDD.speci !!! where the existing road pavement is of cement concrete or dense bituminoLls concrete type. i)The casing/conduit pipe shall be installed with an even bearing throughout its length and in such a manner as to prevent the formation of a water way along it. If so furnish a joint implementation programme to lay their respective ducts within stipulated time frame If crossing of the road involved if Yes it shall only be through trench-less technology NA Documents/Drawing enclosed with the proposal Cross section showing the size of trench for open trenching method (is it normal size of 1.65 m deep x 0.45 m wide) should not be greater than 1.2 m in width in multiple ducts Cross section showing the size of pit and location OF cable for HDD method Strip plan/ Route plan showing the OFC, chainage, width of ROW, distance of proposed, cable from the edge of ROW, important mile stone, intersection, cross drainage works etc. 2.4 Methodology for laying of OFC		atleast 1.2 meter below the surface of the road subject to being at least 0.3 meter below the drain inverts	YES	
the proposed sewage /Gas pipe line . Crossing shall be by boring method HDD.speci IIIV where the existing road pavement is of cement concrete or dense bituminoLls concrete type. I)The casing/conduit pipe shall be installed with an even bearing throughout its length and in such a manner as to prevent the formation of a water way along it. If so furnish a joint implementation programme to lay their respective ducts within stipulated time frame If crossing of the road involved 1.21 if Yes it shall only be through trench-less technology Documents/Drawing enclosed with the proposal Cross section showing the size of trench for open trenching method (is it normal size of 1.65 m deep x 0.45 m wide) should not be greater than 1.2 m in width in multiple ducts Cross section showing the size of pit and location OF cable for HDD method Strip plan/ Route plan showing the OFC, chainage, width of ROW, distance of proposed, cable from the edge of ROW, important mile stone, intersection, cross drainage works etc. 2.4 Methodology for laying of OFC		mention the proposed details		
existing road pavement is of cement concrete or dense bituminoLls concrete type. i)The casing/conduit pipe shall be installed with an even bearing throughout its length and in such a manner as to prevent the formation of a water way along it. If so furnish a joint implementation programme to lay their respective ducts within stipulated time frame If crossing of the road involved if Yes it shall only be through trench-less technology Documents/Drawing enclosed with the proposal Cross section showing the size of trench for open trenching method (is it normal size of 1.65 m deep x 0.45 m wide) should not be greater than 1.2 m in width in multiple ducts Cross section showing the size of pit and location OF cable for HDD method Strip plan/ Route plan showing the OFC, chainage, width of ROW, distance of proposed, cable from the edge of ROW, important mile stone, intersection, cross drainage works etc. 2.4 Methodology for laying of OFC		.Crossing shall be by boring method HDD.speci where the		
even bearing throughout its length and in such a manner as to prevent the formation of a water way along it. If so furnish a joint implementation programme to lay their respective ducts within stipulated time frame If crossing of the road involved if Yes it shall only be through trench-less technology Documents/Drawing enclosed with the proposal Cross section showing the size of trench for open trenching method (is it normal size of 1.65 m deep x 0.45 m wide) should not be greater than 1.2 m in width in multiple ducts Cross section showing the size of pit and location OF cable for 4DD method Strip plan/ Route plan showing the OFC, chainage, width of ROW, distance of proposed, cable from the edge of ROW, important mile stone, intersection, cross drainage works etc. 2.4 Methodology for laying of OFC		existing road pavement is of cement concrete or dense bituminoLls concrete type.	TIDD METHOD	
If crossing of the road involved If crossing of the road involved If Yes it shall only be through trench-less technology Documents/Drawing enclosed with the proposal Cross section showing the size of trench for open trenching method (is it normal size of 1.65 m deep x 0.45 m wide) should not be greater than 1.2 m in width in multiple ducts Cross section showing the size of pit and location OF cable for HDD method Strip plan/ Route plan showing the OFC, chainage, width of ROW, distance of proposed, cable from the edge of ROW, important mile stone, intersection, cross drainage works etc. Methodology for laying of OFC		even bearing throughout its length and in such a manner as to prevent the formation of a water way along it.	NA	
1.21 if Yes it shall only be through trench-less technology Documents/Drawing enclosed with the proposal Cross section showing the size of trench for open trenching method (is it normal size of 1.65 m deep x 0.45 m wide) should not be greater than 1.2 m in width in multiple ducts Cross section showing the size of pit and location OF cable for HDD method Strip plan/ Route plan showing the OFC, chainage, width of ROW, distance of proposed, cable from the edge of ROW, important mile stone, intersection, cross drainage works etc. 2.4 Methodology for laying of OFC	1.2	respective ducts within stipulated time frame	NA	
Cross section showing the size of trench for open trenching method (is it normal size of 1.65 m deep x 0.45 m wide) should not be greater than 1.2 m in width in multiple ducts Cross section showing the size of pit and location OF cable for HDD method Strip plan/ Route plan showing the OFC, chainage, width of ROW, distance of proposed, cable from the edge of ROW, important mile stone, intersection, cross drainage works etc. 2.4 Methodology for laying of OFC	1.21	if Yes it shall only be through trench-less technology	NA	
Cross section showing the size of trench for open trenching method (is it normal size of 1.65 m deep x 0.45 m wide) should not be greater than 1.2 m in width in multiple ducts Cross section showing the size of pit and location OF cable for HDD method Strip plan/ Route plan showing the OFC, chainage, width of ROW, distance of proposed, cable from the edge of ROW, important mile stone,intersection, cross drainage works etc. 2.4 Methodology for laying of OFC	2	Documents/Drawing enclosed with the proposal		
Cross section showing the size of pit and location OF cable for HDD method Strip plan/ Route plan showing the OFC, chainage, width of ROW, distance of proposed, cable from the edge of ROW, important mile stone,intersection, cross drainage works etc. Methodology for laying of OFC Yes Yes	2.1	method (is it normal size of 1.65 m deep x 0.45 m wide) should	The state of the s	
2.3 important mile stone,intersection, cross drainage works etc. 2.4 Methodology for laying of OFC	2.2	Cross section showing the size of pit and location OF cable for	Yes	
2.4 Methodology for laying of OFC		important mile stone, intersection, cross drainage works etc	Yes	
	2.4	Methodology for laying of OFC	NDD.	

Team Leader (M)
Lion Engineering Consultants Pvt. Ltd.
Jhansi-Orai Section, NH-27

A.G.M. (A & P)
O/O GWTD, BSNL JHANSI

-			
/241	open trenching method , if yes methodology of refilling of		
242	trench	NA	
1 242	Horizontal Directional Drilling (HDD)Method	Yes	
2.4.3	laying OFC through CD works and method of laying (whether to	N	
3	be hung outside parapet)	No	
-	Draft License agreement signed by two witness	Yes	
1	Performance hank Current in Comments in Co		
	Performance bank Guarantee in favour of NHAI has to be		
	obtained @rs 50/- per running meter (parallal to NH) and		
	1,00,000/- per crossing of NH, for a period of one year initially		
	(extendable if required till satisfactory completion of work) as		
	asecurity for ensuring / making good the excavated trench for		
	laying OF cable/ducts by proper filling and compaction, clearing		
	debris/loose earth produced due to excution of trenching	•	
	atleast 50 m away from the edge of the right way . no payment		
4	shall be payable by the nhai to the licensee for clearing debris/loose earth.		
<u> </u>			
4.1	confirmation of BG has been obtained or not as per NHAI guidelines		
5	Affidavet/Undertaking from the applicant for the following is to be furnished	Yes	
5.1	Not to damage to other utility, if damage then to pay the losses either to NHAI or to the concerned agency	Yes	
5.2	Renewal of Bank Guarantee	103	
5.3		Yes	
5.4	Confirming all standard condition of NHAI's guideline	Yes	
5.5	Shifting of OFC as and when required by NHAI shifting due to 6 laning/widening of NH	Yes	
5.6	Indempity against all demonstrated in the state of the st	Yes	
3.0	Indemnity against all damages and claims clause (xxiv)	Yes	
5.7	Traffic movement during laying of OFC to be managed by the applicant	Yes	
3.7		163	
5.8	If any claim is raised by the concessionaire then the same has to	Yes	
3.0	be paid by the applicant	163	
	Cortificate for Claring formula		
	Certificate for 6 laning from the applicant in the following format-		
	CONTRACTOR OF CO		
	"we do undertakethat I will relocate service road/ approach	Yes	
	road/ utilities at my own cost notwithstanding the permission		
5.9	granted within such time as will be stipulated by NHAI" for		
	future six laning or any other development.		
	Power of attorney in favour of authorized signatory	Yes	
	Copy of DOT licence	yes	
8	Certificate from the Project director		

Team Leader (Activ)
Lion Engineering Consultants Pvt. Ltd.
Jhansi-Orai Section, NH-27

AGM. (A&P) O/o GMTD, BSNL JHANSI

8.1	Certificate for confiming of all standard condition issued vide Ministry circular no. RW/NH/33044/17/2000-S&R dated 29.9.2000 and NHAI's guidelines issued vide No. NHAI/OEC/2k/Vol-II dated 7.11.2000 and Ministry's circular No.RW/NH/33044/27/2000-S&R(r)dated 23.03.2006	Yes
8.2	certificate for 6 laning from PD in the following	NA
	(a) Where feasibility is available "I do clearify that there will be no hindrance to proposed 6 laning based on the feasibility report considering proposed structures at the said locations"	Yes -
	(b)In case feasibilty report is not available "I do certify that sufficient ROW is available at site for accommodating proposed six laning"	
9	The agreement of fee of Rs. 1 shall be charged	Yes
10	If NH section proposed to be taken up by NHAI on BOT basis-clause in para 17 to be inserted in the agreement. "the permitted highway on which licensee has been granted the right to lay cable/duct has also been granted as aright of way to the consessionaire under the concession agreement for upgradation of (Shivpuri Bypass-Athodana GP FPOI km 91.1 to km 97.1 of NH no.27 build, operate and transfer basis) and therefore, the licensee shall honour the same."	Yes i
11	Who will supervise the work of laying OFC	Bharat Sanchar Nigam Limited
12	Who will ensure that the defects in the road portion after laying of OFC are corrected and if not corrected then what action will be taken.	Bharat Sanchar Nigam Limited
13	Who will pay the claims for damages done/disruption in working of concessionaire if asked by the concessionaire.	Bharat Sanchar Nigam Limited from performance Bank Guarantee
14	A certificate from PD that he will enter the proposed permission in the register of records of the permission in the prescribed proforma (copy enclosed) issued vide Ministry circular No. RW/NH/33044/17/2000/S&R dated 23.7.2003	Yes
15	If any previous approval is accorded for laying of cable then photocopy of register of records of permission accorded as maintained by PD (as per ministry circular no. RW/NH/33044/17/2000/S&R dated 23.7.2003) as referred in para 13 above enclosed or not.	NO

Team Leader (Actual Lion Engineering Consultants Pvt. Ltd.
Jhansi-Orai Section, NH-27

OIO GMTD, BSNL JHANSI