

भारतीय राष्टीय राजमार्ग प्राधिकरण

(सड़क परिवहन एवं राजमार्ग मंत्रालय, भारत सरकार)

National Highways Authority of India (Ministry of Road Transport & Highways, Govt. of India)

क्षेत्रीय कार्यालय-पश्चिम उ०प्र०, लखनऊ

Regional Office - West UP, Lucknow.

3/248, विशाल खण्ड, गोमती नगर, लखनऊ—226010 (उ.प्र.)

3/248, Vishal Khand, Gomti Nagar, Lucknow-226010 (UP)

19001/1/RO-W-UP/NH-9/Km. 136.480-km.149.800/CSPL/669

दूरभाष / Phone : 0522-4960291

टेलीफैक्स / Fax : 0522-4950680 ई-मेल / E-mail : rowestup@nhai.org

rowestup@gmail.com

वेबसाइट / Website : www.nhai.gov.in

Dated: 18.03.2021

Invitation of Public Comments

Proposal for permission for laying proposed 6 Inch Carbon Steel Sub: Pipeline with 125mm dia MDPE Pipeline along NH-9 (Old NH-24) from Stoneman Craft (Ch. 136+480 to CL Gupta (Ch. 141+220).

Permission for laying proposed 125mm dia MDPE Pipeline along NH-9 (Old NH-24) from CL Gupta (Ch. 141+220) to Holiday Regency (Ch. 149+800).

Permission for laying proposed 04 Nos. Carbon Steel Pipeline crossing across NH-09 (Old NH-24) at Pakbara (Ch. 147+100), Lodhipur IFTM (Ch. 145+720), Budhanpur (Ch. 138+180) & Dhakiya (Ch. 137+550) to develop CGD Network in Moradabad District of Uttar Pradesh.

The Assistant General Manager M/s Torrent Gas Moradabad Limited has submitted the aforesaid proposal through PD, PIU-Moradabad for NOC approval of the Competent Authority.

- From the submitted proposal, it is seen that as per checklist the Gas Pipe line 2. is proposed 6" Carbon Steel Pipeline with 125mm dia MDPE Pipeline along NH-9 (Old NH-24) from Stoneman Craft (Ch. 136+480 to CL Gupta (Ch. 141+220) (length=4740m on LHS, 0.6m width and 1.2m depth) and from CL Gupta (Ch. 141+220) to Holiday Regency (Ch. 149+800) (length=8580m on RHS, 1.0m width and 1.4m depth) (total length=13.32km). Further, pipeline proposed at 04 No. locations for crossing across NH-09 (Old NH-24) with 4" dia at Pakbara (Ch. 147+100), Lodhipur IFTM (Ch. 145+720), Dhakiya (Ch. 137+550) (1.6m depth for above locations) & Budhanpur (Ch. 138+180) (1.9m depth). Both (Left & Right) sides from centre line towards increasing Chainage/km direction is 30m. Applicant has proposes laying work through open cut/trench and crossing through HDD method. Laying/crossing work will be allowed only through Horizontal Directional Drilling (HDD) method.
- As per the guidelines issued by the Ministry vide OM No.RW/NH-33044/29/ 3. 2015/S&R(R) dated 22.11.2016, the application shall be put out in the public domain for 30 days for seeking claims and objections (on grounds of public inconvenience, safety and general public interest).

Contd....2/-

"Building a nation, not just Roads."

::2::

In view of the above, comments of the public on the above application is invited to the below mentioned address, which should reach by this office within 30 days from the date of publication beyond which no comments shall be entertained

> The General Manager cum Regional Officer, National Highways Authority of India Regional Office, UP-West, Lucknow 3/248, Vishal Khand, Gomti Nagar Lucknow-226 010

This issues with the approval of RO-UP (West), Lucknow.

Encl: As above.

(Anuj Kumar Singh) Manager (Tech.) For RO-UP (West)

Copy to:

- 1. Web Admin, NHAI, HQ with a request for uploading on the NHAI website.
- 2. The Technical Director, NIC, Transport Bhawan, New Delhi with a request for uploading on Ministry's website.
- 3. PD, PIU-Moradabad for information.
- 4. The Assistant General Manager M/s Torrent Gas Moradabad Limited for information.

CHECK - LIST

Check list for getting approval for laying of Gas pipeline on NH Land

Sr. No.	Item	Information / Status	Remarks
1	General Information		
1.1	Name and Address of the Applicant / Agency	As per Annexure - A	
1.2	National Highway Number	NH-24	
1.3	State	Uttar Pradesh	
1.4	Location	Moradabad	
1.5	(Chainage in Km)	Along the Road: 1) Along with NH-24 Moradabad Between CH- 141.220 to 149.800 Km (Left Side)- as per the attached Trench layout -I 2) Along with NH-24 Moradabad Between CH- 136.480 to 141.220 Km (Right Side) as per the attached Trench layout -II	
1.6	Length in Meters	Along the Road: 1. Between Km Stone	
1.7	Width of available ROW (a) Left side from center line towards	60 m	
	increasing chainage / km direction (b) Right side from center line towards increasing chainage / km direction	30 m	
1.8	Proposal to lay underground Gas pipeline (a) Left side from center line towards increasing chainage / km direction (b) Right side from center line towards	Yes (CH- 141.220 to CH-149.800) Yes	
	increasing chainage / km direction	(CH- 136.480 to CH-141.220)	



परियोजना निर्देशक। Project Director भारतीय राष्ट्रीय राजमार्ग प्राधिकरण National Highway Authority of India मुरादाबाद /Moradabad

1

1.9	Proposal to acquire Land	N.A.
	(a) Left side from center line	
	(b) Right side from center line	
1.10	Whether proposal is in the same side where	N.A.
	land is not to be acquired	
	If not, then where to lay the cable	THE COURSE IN CONTRACT PARTY.
1.11	Details of already laid services, if any, along	N.A.
	the proposed route	
1.12	Number of lanes (2/4 /6/8 lanes) existing	6 Lane
1.13	Proposed Number of lanes (2 lane with	N. A
	paved shoulders/4 / 6/8 lanes)	
1.14	Service Road existing or not	N.A.
	If yes, then which side	
	(a) Left side from center line	
	(b) Right side from center line	
1.15	Proposed Service Road	N.A.
	(a) Left side from center line	
	(b) Right side from center line	Secretary of the second second second
1.16	Whether proposal to lay Gas pipeline is after	N.A.
	the service road or between the service	
	road and main carriageway	
1.17	The permission for laying of Gas pipeline	Yes
	shall be considered for approval / rejection	
	based on the Ministry Circulars mentioned	
	as above.	
	(a) Carrying of sewage / Gas pipelines on	For Natural Gas pipeline
	highway bridges shall not be permitted	
	as Fumes / Gas pipes can accelerate	
	the process of corrosion or may cause	
	explosions, thus, being much more	
	injurious than leakage of Gas.	
	(b) Carrying of Gas pipelines on bridges	N/A
	shall not be discouraged. However, if	
	the Gas authorities seem to have no	
	other viable alternative and approach	
	the highway authority well in time	
	before the design of the bridge is	
	finalized, they may be permitted to	
	carry the pipeline on independent	
	superstructure, supported on extended	
	portions of piers and abutments in such	
	a manner that in the final arrangement	
	enough free spade around the	
	superstructure of the bridge remains	
	available for inspection and repairs etc.	
	(c) Cost of required extension of the	N/A
	substructure as well as that of the	
	supporting superstructure shall be	
	borne by the agency-in-charge of the	
	4:11:4:	CONTROL OF A CONTR
	utilities. (d) Services are not being allowed	N/A



पारबोजना एक्सेना Project Director भारतीय राष्ट्रीय राजमार्ग प्राधिकरण National Highway Authority of India मुरादाबाद /Moradabad

	part of the bridges; Safety of the bridges has to be kept in view while permitting various services along bridge. Approvals are to be accorded in this regard with the concurrence of the Ministry's Project Chief Engineers only.	
1.18	If crossings of the road involved If Yes, it shall be either encased in pipes or through structure or conduits specially built for that purpose at the expenses of the agency owning the line	Yes
	 (a) Existing drainage structures shall not be allowed to carry the lines. 	Agree
	(b) The utility services shall cross the National Highway preferably on a line normal to it or as nearly show as practicable. Torrent gas Moradabad Limited shall be permitted to cross the National Highway either through structure or conduits specially built for that purpose. The casing / conduit pipe should, as minimum, extend from drain to drain in cuts and toe of slope to toe of slope in the fills and shall be designed in accordance with the provision of IRC and executed following the Specifications of the Ministry.	Yes
	(c) The casing pipe may be installed under the route embankment either by boring or digging a trench. Installation by boring method shall prefer.	Yes
	(d) The casing pipe (or conduit pipe in the case of electric cable) carrying the utility line shall be of steel, cast iron, or reinforced cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe / cable.	Yes
	(e) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path.	Yes
	(f) The casing / conduit pipe should, as minimum extend from drain to drain in cuts and toe of slope toe of slope in the fills.	Yes
	(g) The top of the casing / conduit pipe should be at least 1.2 meter below the surface of the road subject to being at least 0.3 meter below the drain inverts.	Yes
	(h) Crossing shall be by boring method (HDD) specially where the existing	Yes



परियोजना निर्मिक । Exoject Director भारतीय राष्ट्रीय राजमार्ग प्राधिकरण National Highway Authority of India मुरादाबाद /Moradabad


	road pavement is of cement concrete or dense bituminous concrete type.	
	(i) The casing / conduit pipe shall be installed with an even bearing throughout its length and in such a manner as to prevent the formation of a Gas way along it.	Yes
2	Document / Drawings enclosed with the proposal	Enclosed
2.1	Cross section showing the size of trench for open trenching method (Is it normal size of 1.3 meter deep X 0.5 meter wide)	Enclosed
	 (i) Should not be greater than 60 cm wider than the outer diameter of the pipe (ii) located as close to the extreme edge of the right-of-way as possible but the utility services shall cross the National Highway preferably on a line normal to it or as nearly so as practicable. (iii) The casing pipe shall be installed under the road embankment either by boring or digging a trench. Installation by boring method shall be preferred. (iv) These should be so laid that their top is at least 0.6 meter below the ground level so as not to obstruct drainage of the road land. 	
2.2	Cross section showing the size of pit and location of cable for HDD method	Enclosed
2.3	Strip plan / Route plan showing Gas pipeline, Chainage, width of ROW, distance of proposed cable from the edge of ROW, important milestone, intersections, cross drainage works etc.	Enclosed
2.4	Methodology for laying of Gas pipeline	Enclosed (Open Cut)
2.4.1	Open trenching method. (May be allowed in utility corridor only where pavement is neither cement concrete nor dense bituminous concrete type. If yes, Methodology of refilling of trench	Agree
	(a) The trench width should be at least 30 cm, but not more than 60 cm wider than the outer diameter of the pipe.	Agree
	(b) For filling of the trench, Bedding shall be to a depth of not less than 30 cm. It shall consist of granular material, free of lumps, clods and cobbles and graded to yield a firm surface without sudden change in the bearing value.	Agree
	Unsuitable soil and rock edged should be excavated and replaced by selected	Agreed






	material.	
	(c) The backfill shall be completed in two stages (i) side – fill to the level of the top of the pipe and (ii) overfill to the bottom of the road crust.	Agreed
	(d) The side fill shall consist of granular material laid in 15 cm layers each consolidated by mechanical tampering and controlled addition of moisture to 95% of the Proctor's Density. Overfill shall be compacted to the same density as the material that had been removed. Consolidation by saturation or ponding will not be permitted.	Agreed
	(e) The road crust shall be built to the same strength as the existing crust on either side of the trench. Care shall be taken to avoid the formation of a dip at the trench.	Agreed
	(f) The excavation shall be protected by flagman, signs and barricades and red lights during night hours.	Agreed
	(g) If required, a diversion shall be constructed at the expense of agency owning the utility line	Agreed
2.4.2	Horizontal Directional Drilling (HDD) Method	Yes
2.4.3	Laying of Gas pipeline through CD works and method of laying	
	(a) The utility services shall cross the National Highway preferably on a line normal to it for as nearly so as practicable and subject to all other stipulations contained in this Ministry's guidelines issued with letter No. RW/NH-33044/29/ 2015/S&R(R) – Dtd. 22nd November, 2016	Yes
3	Draft License Agreement signed by two witnesses	Enclosed
4	Performance Bank Guarantee in favour of NHAI has to be obtained @ Rs per running meter (parallel to NH) and Rs per crossing of NH, for a period of one year initially (extendable if required till satisfactory completion of work) as a security for ensuring / making good the excavated trench for laying the cables / ducts by proper filling and compaction, clearing debris / loose earth produced due to execution of trenching at least 50 meters	Will obtain at the time of receipt of permission
	away from the edge of the right of way. No payment shall be payable by the NHAI to the licensee for clearing debris / loose earth.	





4.1	Performance BG as per above is to be obtained.	Yes
4.2	Confirmation of BG has been obtained as per NHAI guidelines	No
5	Affidavit / Undertaking from the Applicant for	
5.1	Not to Damage to other utility, if damaged then to pay the losses either to NHAI or to the concerned agency	Enclosed
5.2	Renewal of Bank Guarantee	Enclosed
5.3	Confirming all standard condition of NHAI guideline	Enclosed
5.4	Shifting of Gas Pipeline as and when required by NHAI at their own cost	Enclosed
5.5	Shifting due to 6 lanning / widening of NH	Enclosed
5.6	Indemnity against all damages and claims clause (xxiv)	Enclosed
5.7	Traffic movement during laying of Gas pipeline to be managed by the applicant	Enclosed
5.8	If any claim is raised by the Concessionaire, then the same has to be paid by the applicant	Enclosed
5.9	Prior approval of the NHAI shall be obtained before undertaking any work of installation, shifting or repairs or alterations to the showing Gas Pipeline located in the National Highway right-of-ways.	Enclosed
5.10	Expenditure, if any, incurred by NHAI for repairing any damage caused to the National Highway by the laying, maintenance or shifting of the Gas Pipeline will be borne by the agency owning the line.	Enclosed
5.11	If the NHAI considers it necessary in future to move the utility line for any work of improvement or repairs to the road, it will be carried out as desired by the NHAI at the cost of the agency owning the utility line within a reasonable time (not exceeding 60 days) of the intimation given.	Enclosed
5.12	Certificate from the applicant in the following format	Enclosed
	Laying of Gas Pipeline will not have any deleterious effects on any of the bridge components and roadway safety for traffic.	
	(ii) for 6 – lanning "We do undertake that I will relocate service road / approach road / utilities at my own cost notwithstanding the permission granted within such time as will be stipulated by NHAI" for future Six – lanning or any other development."	





6	VAMP a will aim the amount on behalf of	
6	Who will sign the agreement on behalf of	Satish Chandra Verma
	Gas Pipeline agency	(Assistant General manager)
	Power of attorney to sign agreement available or not	Torrent Gas Moradabad Ltd.
7	Certificate from the Project Director	
7.1	Certificate for confirming of all standard	V
1.1	condition issued vide Ministry Circular No. – NH-	Yes
	41(58)/68 dated – 31.1.1969, Ministry Circular	
	No. – NH-III/P/66/76 dated 18/19.11.1976.	
	Ministry Circular No NH-RW/NH-III/P/66/76	
	dated - 11.5.1982, Ministry Circular No RW /	
	NH-11037 / 1 / 86 - DOI (ii) dated - 28.7.1993,	
	Ministry Circular No RW / NH-11037 / 1 /	
	86/DOI dated – 19.1.1995, Ministry Circular No.	
	- RW / NH-34066 / 2 / 95 S&R dated -	
	25.10.1999, Ministry Circular No. – RW / NH-	
	34066 / 7 / 2003 S&R (B) dated – 17.9.2003 and RW/NH-33044/29/2015/S&R(R) – Dated 22nd	
	November, 2016	
7.2	Certificate from PD in the following format	Yes
	(i) "It is certified that any other location of	
	the Gas Pipeline would be extremely	
	difficult and unreasonable costly and the	
	installation of Gas Pipeline within ROW	
	will not adversely affect the design,	
	stability & traffic safety of the highway	
	nor the likely future improvement such as	
	widening of the carriageway, easing of	
	curve etc".	
	(ii) for 6 – lanning	
	(a) Where feasibility is available "I do certify that there will be no hindrance to	
	proposed six-laning based on the	
	feasibility report considering proposed	
	structures at the said location".	
	(b) In case feasibility report is not available	
	"I do certify that sufficient ROW is	
	available at site for accommodating	
	proposed six-laning".	
8	If NH section proposed to be taken up by NHAI	Enclosed
	on BOT basis – a clause is to be inserted in the	
	agreement. "The permitted Highway on which	
	Licensee has been granted the right of lay cable	
	/ duct has also been granted as a right of way to	
	the concessionaire under the concession agreement for up-gradation of [section	
	from Km to Km of NH No – on	
	Build, Operate and Transfer Basis] and	
	therefore, the licensee shall honour the same."	
9	Who will supervise the work of laying of Gas	Torrent Gas Moradabad
	Pipeline	Ltd.
10	Who will ensure that the defects in road	NHAI
	portion after laying of Gas Pipeline are	
	corrected and if not corrected then what	
	action will be taken.	



भारतीय राष्ट्रीय सर्जमार्न प्राधिकरण National Highway Authority of India मुरादाबाद /Moradabad

11	Who will pay the claims for damages done / disruption in working of Concessionaire if asked by the Concessionaire	Torrent Gas Moradabad Ltd.
12	A certificate from PD that he will enter the proposed permission in the register of records of the permissions in the prescribed proforma (copy enclosed).	
13	If any previous approval is accorded for laying of underground Gas Pipeline, then Photocopy of register of records of permissions accorded as maintained by PD then copy be enclosed	

For Torrent Gas Moradabad Ltd.

Date: 11\09\2020 Place: Moradabad

> Satish Chandra Verma Assistant General Manager

परियोजना चिक्रिके Project Director प्राचिकरण प्राचिकरण प्राचिकरण प्राचिकरण प्राचिकरण प्राचिकरण भारतीय प्राचिकरण Authority of India National Highway Authority of Moradabad