



GOVERNMENT OF INDIA MINISTRY OF ROAD TRANSPORT & HIGHWAYS

REGIONAL OFFICE; Quality Control Building, Errum Manzil, Hyderabad-500082 Dated: 21.08.2019

No.RW/HYD/Misc-24(D)/utility services/2/2—

Sub: Proposal for permission for laying of Optical Fiber cable along and across the NH-09 Hyderabad- Vijayawada Section from the Km 112.800 to Km 115.600 for a total length of 2.80 Km in the State of the Telanagana-Reg.

Ref: i) The Project Director, PIU NHAI, Hyderabad letter No. NHAI/PIU-HYD/Hyd-Vij/BSNI/2018/722 dated 16.08.2018

The Project Director, PIU NHAI, Hyderabad vide letter cited under reference i) has submitted therewith a Proposal for permission for laying of Optical Fiber cable along and across the NH-09 Hyderabad- Vijayawada Section from the Km 112.800 to Km 115.600 for a total length of 2.80 Km in the State of the Telanagana.

- 2. The proposal has been broadly examined as per Ministry's Guidelines issued vide letter no.RW/NH-33044/29/2015/S&R(R) dated 22.11.2016 and are generally found in order
- 3. In view of above, as per Ministry's guideline Para 4, public comments is invited on the above proposal for seeking claims and raising objections (on grounds of public inconvenience, safety and general public interest) for 30 days on public portal i.e. website of Ministry of Road Transport and Highways (www.morth.nic.in) as per Form-A (copy enclosed) for "Accommodation of Public and Industrial Utility Services along and across National Highways" by.

The Chief-Engineeer-Regional Officer
Regional Office Hyderabad
Quality Control Building, 2nd floor,
Errum Manzil Colony
Hyderabad - 500082
Email Id: rohyd-morth@nic.in

Yours faithfully

G R Choudhary

Executive Engineer

For Chief Engineer-Regional Officer cum Highway Administrator

Copy to:-

Senior Technical Director, NIC, Transport Bhawan, New Delhi- 110001 for uploading on Ministry's website.

Ž,

FORM-A


Form for seeking claims and objections (on grounds of public inconvenience, safety and general public interest) on the application for Accommodation of Public and Industrial Utility Services along and across National Highways

Sub: Proposal for permission for laying of Optical Fiber cable along and across the NH-09 Hyderabad- Vijayawada Section from the Km 112.800 to Km 115.600 for a total length of 2.80 Km in the State of the Telanagana-Reg.

The claims and objections (on grounds of public inconvenience, safety and general public interest) by the general public needs to be given within 30 days of uploading the online application for comments

SI. No	Item	Details
1	Name of the person who is desiring to give claims and objections (on grounds of public inconvenience, safety and general public interest)	
2	Address of the person	
	Details of the application for Accommodation of Public and Industrial Utility Services along and across National Highways against which claims and objections are being given (name of applicant and other details like site address etc.)	
3	j) Application No.	
	k) Name of applicant (who applied to Accommodation of Public and Industrial Utility Services along and across National Highways)	
	l) Details of Application	
4	The claims and objections (on grounds of public inconvenience, safety and general public interest)	

LINE DIAGRAM OF NHAI SECTIO OF NALGONDA-NAKREKAL OFC ROUTE



Yah DIVISIONAL ENGINEER BSNL OFC PROJECTS HYDERABAD

meneral **Project** Director NHAI, PIU HYDERABAD

As per 2E Report date 3/8/2018, the details from per 112/800 to km 115/600 is as follows Note:

Row width of available - 60m (i)

Avenue Mantalion from median to 240 Rew - 2500

Ettethen drain from median centre 15 al 26-27m,

Utility area avoilable for laying OFC from media.
Centre vis 28-30 m

As four at laying of one cause meal will more to lay only at entreme edge of Row.

marana

c) . HDD METHOD for Road Crossing : **Ground Level** ound Level 165 Cms 40 mm dia PLB Pipe Optical Fibre Cable 50 mm dia. DWC Pipe **OFC PROJECTS HYDERABAD**

. Page and a	CHI	ECK LIST	-		
Na	me of the work: OFC scheme from Nalg	onda - Nakrekal OFC Route of NALGOND	SSA		
	Check List for getting approval for laying of OFC line on NHAI Land				
Sl. No.	Item	Information / Status	Remark		
1	General Information				
1.1	Name and Address of the Applicant / Agency	Divisional Engineer, OFC Project, BSNL, Hyderabad			
1.2	National Highway Number	NH-65			
1.3	State	Telangana	7 S E 35 77		
1.4	Location	Nalgonda - Nakrekal OFC Route of NALGONDA SSA			
1.5	(Chainge in Kms)	Km.112.800 to Km.115.600 as a part			
		of Nalgonda - Nakrekal OFC Route			
1.6	Length in Meters	2800 Mtrs.			
1.7	Width of available RoW	60 Mtrs.			
(a)	Left Side from center line towards increasing chainage / Kms. direction				
(b)	Righ side from center line towards	Km.112.800 to Km.115.600= 2.8 Kms.			
ν,	increasing chainage / Kms. direction	as a part of Nalgonda - Nakrekal OFC Route			
1.8	Proposal to lay under jound OFC line				
(a)	Left Side from center line towards increasing chainage / Kms. direction				
(p)	Righ side from center line towards increasing chainage / Kms. direction	28 to 30 Mtrs.			
1.9	Proposal to acquire land	4			
(a)	Left side from center Line	NA			
(b)	Right side from center Line	NA			
1.10	Whether proposal is in the same side where land is not to be acquired. If not then where to lay the cable	NA			
1.11	Details of already laid services, if any, along the proposed route	Utilities are laid			
1.12	Number of lanes (2/4 /6/8 lanes) existing	4 Lane			
1.13	Proposed Number of lanes (2 Lanes with paved shoulders /4 / 6/8 lanes)	4 Lane			
1.14	Service road existing or not if yes then which side	Existing (s.d.)			
(a)	Left side from center line	-	i		
(b)	Right side from center line	-			
	B 10 1				

Contd..2

DIVISIONAL ENGINEER BSNL OFC PROJECTS HYDERABAD

1.15

1.16

5 Proposed Service road
(a) Left side from center line
(b) Right side from center line

carriageway

Whether proposal to lay OFC Line is after

the service road or between the service road

Monlard Project Director NHAI, PIU HYDERABAD

_

After the Service Road

			
1.17	The permission for laying of OFC Line shall		
	be considered for approval / rejection	Approval	
	Ministry Circulars mentioned as above.	He to the second	
7.		<u> </u>	
(a)	Carrying of sewage / gas pipe lines on		
1	highway bridges shall not be permitted as		i
	Furmes / gasses pipes accelerate the process	NA	1
9	of corrosion or may Explosions, thus, being		
	much more injurious of water	N 1480	
(b)	Carrying of OFC lines on bridges shall		
	discouraged. However, if the water supply		1
	seem to have no other viable alternative and		
	bridge is finalized, they may be permitted to		
	pipe line on independent superstructure,	Drawing given	
	extended portions of piers and abutments in		
	manner that in the final arrangement enough		
	around the superstructure of the bridge for		Į.
			1
	inspection and repairs, etc.,		
(c)	Cost of required extension of the substructure		ì
	as that of the supporting superstructure shall	NA	
	the agency-in-charge of the utilities.		
- (1)		**************************************	+
(d)	Services are not being allowed parapet / any		
	part of the bridges, safety of the to be kept in		į.
	view while permitting various bridge.	77.4	
	Approvals are to be accorded in this the	NA	1
	concurrence of the Ministry's Project		
	Engineers Only.		
1.18	If crossing of the road involved.		
	If Yes, it shall be either encased in pipes or	10 10 60 27010 0	l .
		Kms. 115/600	
	structure or conduits specially built for that		
	expenses of the agency owning the line		
(a)	Existing drainage structures shall not be	V	
(-7	allowed to carry the lines	Yes	1
(1.)		Yes	
(b)	Is it on a line normal to NH	168	
(c)	Crossing shall not be too near the structures		
(c)	Crossing shall not be too near the structures	Yes	
(c)	Crossing shall not be too near the structures on the National Highway, the distance being	Yes	
	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures.	Yes	
(c) (d)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the	Yes	
	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall		
	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall	Yes	
	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete		
	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to		
	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable.		
	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be	Yes	
(d)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be		
(d)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as	Yes	
(d)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path.	Yes	
(d)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend	Yes	
(d)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in	Yes	
(d)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in	Yes	
(d) (e)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in the fills.	Yes	
(d)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in the fills. The top of the casing / conduit pipe should	Yes	
(d) (e)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in the fills. The top of the casing / conduit pipe should least 1.2 Meter below the surface of the road	Yes Yes	
(d) (e)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in the fills. The top of the casing / conduit pipe should	Yes	
(d) (e)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in the fills. The top of the casing / conduit pipe should least 1.2 Meter below the surface of the road	Yes Yes	
(d) (e) (f)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in the fills. The top of the casing / conduit pipe should least 1.2 Meter below the surface of the road subject to being at least 0.3 M below the drain inverts.	Yes Yes	
(d) (e)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in the fills. The top of the casing / conduit pipe should least 1.2 Meter below the surface of the road subject to being at least 0.3 M below the drain inverts. Crossing shall be by boring method (HDD)	Yes Yes Yes 1.65 Mtrs	
(d) (e) (f)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in the fills. The top of the casing / conduit pipe should least 1.2 Meter below the surface of the road subject to being at least 0.3 M below the drain inverts. Crossing shall be by boring method (HDD) specially where the existing road pavement	Yes Yes	
(d) (e) (f)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in the fills. The top of the casing / conduit pipe should least 1.2 Meter below the surface of the road subject to being at least 0.3 M below the drain inverts. Crossing shall be by boring method (HDD)	Yes Yes Yes 1.65 Mtrs	
(d) (e) (f)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in the fills. The top of the casing / conduit pipe should least 1.2 Meter below the surface of the road subject to being at least 0.3 M below the drain inverts. Crossing shall be by boring method (HDD) specially where the existing road pavement cement concrete or dense bituminous	Yes Yes Yes 1.65 Mtrs	
(d) (e) (f) (g)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in the fills. The top of the casing / conduit pipe should least 1.2 Meter below the surface of the road subject to being at least 0.3 M below the drain inverts. Crossing shall be by boring method (HDD) specially where the existing road pavement cement concrete or dense bituminous concerte type.	Yes Yes Yes 1.65 Mtrs	
(d) (e) (f)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in the fills. The top of the casing / conduit pipe should least 1.2 Meter below the surface of the road subject to being at least 0.3 M below the drain inverts. Crossing shall be by boring method (HDD) specially where the existing road pavement cement concrete or dense bituminous concerte type. The casing / conduit pipe shall be installed	Yes Yes Yes 1.65 Mtrs	
(d) (e) (f) (g)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in the fills. The top of the casing / conduit pipe should least 1.2 Meter below the surface of the road subject to being at least 0.3 M below the drain inverts. Crossing shall be by boring method (HDD) specially where the existing road pavement cement concrete or dense bituminous concerte type. The casing / conduit pipe shall be installed even bearing throughout its length and in	Yes Yes Yes 1.65 Mtrs	
(d) (e) (f) (g)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in the fills. The top of the casing / conduit pipe should least 1.2 Meter below the surface of the road subject to being at least 0.3 M below the drain inverts. Crossing shall be by boring method (HDD) specially where the existing road pavement cement concrete or dense bituminous concerte type. The casing / conduit pipe shall be installed	Yes Yes Yes 1.65 Mtrs	
(d) (e) (f) (g)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in the fills. The top of the casing / conduit pipe should least 1.2 Meter below the surface of the road subject to being at least 0.3 M below the drain inverts. Crossing shall be by boring method (HDD) specially where the existing road pavement cement concrete or dense bituminous concerte type. The casing / conduit pipe shall be installed even bearing throughout its length and in	Yes Yes Yes 1.65 Mtrs	
(d) (e) (f) (g) (h)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in the fills. The top of the casing / conduit pipe should least 1.2 Meter below the surface of the road subject to being at least 0.3 M below the drain inverts. Crossing shall be by boring method (HDD) specially where the existing road pavement cement concrete or dense bituminous concerte type. The casing / conduit pipe shall be installed even bearing throughout its length and in manner as to prevent the formation of a along it.	Yes Yes Yes 1.65 Mtrs HDD	
(d) (e) (f) (g)	Crossing shall not be too near the structures on the National Highway, the distance being 15 Meter. What is the existing structures. The casing pipe (or conduit pipe in the electric cable) carrying the utility line shall cast iron, or reinforcedcenment concrete adequate strength and be large enough to ready withdrawal of the carrier pipe / cable. Ends of the casing / conduit pipe shall be from the outside, so that it does not act as path. The Casing / conduit pipe should, as extend from drain to drain in cuts and toe of slope in the fills. The top of the casing / conduit pipe should least 1.2 Meter below the surface of the road subject to being at least 0.3 M below the drain inverts. Crossing shall be by boring method (HDD) specially where the existing road pavement cement concrete or dense bituminous concerte type. The casing / conduit pipe shall be installed even bearing throughout its length and in manner as to prevent the formation of a along	Yes Yes Yes 1.65 Mtrs	

Contd..3

DIVISIONAL ENGINEER BSNL OFC PROJECTS HYDERABAD Project Director NHAI, PIU HYDERABAD

2.1	Cross section showing the size of trench for	Depth 1.65 Mtr x Width 0.45	
İ	open trenching method (is it normal size of	Mtr.	
	1.2 M deep X 0.3 M wide)		<u></u>
(i)	Should not be greater than 60 Cms wide than	Yes	
(ii)	diameter of the pipe		
(ii)	Located as close to the extreme edge of the as	08 4 20 14	
	possible but not less than 15 Meter from	28 to 30 Mtrs.	Ì
GEEN	centre –lines of the nearest carriageway		
(iii)	Shall not be permitted to run along the		
	Highways when the road formation is	NA	
	situated cutting. Nor shall these be laid over	- Contract of Cont	
(i- a	the and birdges		
(iv)	These shouldbe so laid that their top is at 0.6	10.10	
	Meter below the ground level so as not	1.2 Mtr	
2.2	drainage of the road land.		
4.4	Cross section showing the size of pit and	Yes	
0.2	location of Cable for HDD method		
2.3	Strip plan / route plan showing OFC line,		
8	Chainage, width of RoW, distance of from the	Yes	
3	edge of RoW important mile stone,	3.55.	
	intersections, cross drainage works etc.		- 22
2.4	Methodology for laying of showing OFC	Open Trench Method	
2.4.1	Open trenching method. (May be allowed in		
	utility corridor only where pavements is	Yes, the trench would be filled in	
	neither nor dense bituminous concrete type.	layers and compacted	
(a)	If yes of refilling of trench)		40,000
(a)	The trench width should be at least 30 Cms,	• • • • • • • • • • • • • • • • • • • •	
	more than 60 Cms. Wider than the outer pipe.	Yes	
(h)			
(b)	For filling of the trench, Bedding shall be to a not less than 30 Cms. It shall consist of free		
	of lumps, clods and cobbles and graded firm surface without sudden change in the	Yes	
ı	unsuitable soil and rock edged should be	**************************************	
	replaced by selected material.		
(0)	The backfill shall be completed in tow stages		
(c)	fill to the level of the top of the pipe and (ii)	V	
	bottom of the road crust.	Yes	
(d)	The sidefill shall consist of granular material		
(u)	cm layers each consolidated by mechanical		
	and controlled addition of moisture to 95% of		
	proctor's Density. Overfill shall be compacted	Yes	
	same density as the material that had been	ics i	
	consolidation by saturation or ponding will		
	not permitted.		
(e)	(e)The road crust shall be built to the same		
(~)	the existing crust on either side of the trench.	option of the state of the stat	
	be taken to avaoid the formation of a dip at	Yes	
	the		
(f)	(f) The excavation shall be protected by and	100 March 100 Ma	
1-1	barriecades, and red lights during night	Yes	
(g)	(g) If required, a diversion shall be		
101	constructed at the expense of agency owning	Yes	
	the utility line		
2.4.2	Horizontal Directional Drilling (HDD) Method	HDD for Crossings	
2.4.3	Laying of OFC Line through CD works and		
weeks 41 - 2014 (Tell l)	method of laying		
(a)	(a) On approaches, the water mains/ cables		
1.3	carried along a line as close to the edge of the		
	way as possible up to a distance of 30 m from		
	and subject to tall other stipulations	Yes	
	contained Ministry's guidelines issued with		
	Letter No. NH-dated 19-11-1976.		
260	20000 1.0. IIII dated.15-11-1510.	<u> </u>	

Yab gol

Contd..4

Project Director NHAI, PIU HYDERABAD

	I TO COLLEGE		
. 3	Draft License Agreement signed by two witnesses	Yes	900,700 cm
4	Performance Bank Guarantee in favour of NHAI has to be obtained @ 100/- per running meter NH) and One year initially (extendable if required satisfactory completion of work) as a ensuring / making good the excavated the cables / ducts by propoer filling and clearing debris / loose earth produced due to of trenching at least 50 m away from the right of way. No payment shall be payable NHAI to the licensee for clearing.		
4.1	Performance BG as per above is to be obtained.	Yes	
4.2	Confirmation of BG has been obtained as per NHAI guidelines	Yes	
5	Affidavit / undertaking from the applicant for		5-314
5.1	Not to damage to other utility, if damged then to pay the losses either to NHAI or to the concerned	Yes undertaking given	
5.2	Renewal of Bank Guarantee	Yes undertaking given	
5.3	Confirming all standard condition of NHAI's guidelines	Yes undertaking given	
5.4	Shifting of OFC Line as and when required NHAI at their own cost	Yes undertaking given	
5.5	Shifting due to 6 lanning / widening of NH	Yes undertaking given	
5.6	Indemnity against all damages and claims clauses (xxiv)	Yes undertaking given	
5.7	Traffic movement during laying of OFC line	Yes undertaking given	
5.8	If any claim is raised by the concessionaire then the same has to be paid by the applicant	Yes undertaking given	
5.9	Prior approval of the NHAI shall be obtained before undertaking any work of installation, shifting or alternations to the showing OFC in the National Highway right-of-ways.	Yes undertaking given	
5.10	Expenditure, if any, incurred by NHAI for repairing any damage caused to the National Highway by maintenance or shifting of the Water supply be borne by the agency owning the line	Yes undertaking given	
5.11	If the NHAI considers it necessary in future to move the utility line for any work of improvement or road, it will be carried out as desired by the cost of the agency owning the utility line within reasonable time (not exceeding 60 days) of the intimation given.	Yes undertaking given	
5.12	Certificate from the applicant in the following	4 2	
(i)	(i) Laying of OFC line will not deleterious effects on any of the bridge and roadway safety for traffic.	Certificate enclosed	
(ii)	(ii) for 6 - lanning "We do undertake that I will service road / approach road / utilities at my own notwithstanding the permission granted within as will be stipulated by NHAI" for future six laning any other development"	Certificate enclosed	
6	Who will sign the agreement on behalf of OFC	Divisional Engineer, OFC Proect,	0.000
	line agency	BSNL, Hyderabad	
7	Certificate from the Project Director	Yes / No	

Contd..5

DIVISIONAL ENGINEER BSNL OFC PROJECTS HYDERABAD

Project Director
NHAL, PIU
HYDERABAD

٤