7520.33



GOVERNMENT OF INDIA MINISTRY OF ROAD TRANSPORT & HIGHWAYS

Indian Academy of Highway Engineers (campus), A-5, Sector-62, Noida – 201301.

No RW/NH-34072/1/2015-S&R(B)

Dated: 21.06.2016

OFFICE MEMORANDUM

Sub: Circulation of recommendations of the Expert Committee on "Best Practices in Road Construction" for action and compliance - reg.

Sir,

Please find enclosed herewith the approved recommendations of the Expert Committee on "Best Practices in Road Construction" for further necessary action and compliance. The concerned zones, who are requested to take necessary actions or to issue requisite circulars, make amendments in the relevant documents etc. as the case may be within a month of issue of this O.M. However, the Standing Panel of Experts will be set up by June, 2016 by S&R(B) zone itself. The full report of the Expert Committee is already available on Ministry's website.

Yours faithfully,

(Sanjay Garg), Superintending Engineer (B) SR&T, For Director General (RD) &SS.

Τo,

- **1.** DG(RD)&SS,
- Chairman, NHAI
- 3. MD-NHIDCL
- 4. ADG-I
- 5. Coordinator-I/II/III
- CVO of MORT&H
- JS(LA)/JS(T)/JS(Admin.)
- C.E. S&R(B)/ C.E. S&R(R)/ C.E. (EAP)/ C.E. (Planning zone), and C.E. (Road Safety cell).

Copy also forwarded to:-

- 1. PS to Hon'ble Minister(RTH&S)
- PS to Hon'ble Minister of State(RTH&S)
- PPS to Sccrelary(RT&H).

Encl.: As above

Page 1 of 32

Annex "A"

Best Practices in Road Construction: Report of the Expert Committee

Chapter 2 - Measures to promote Innovative Technologies, Materials and Equipment

Cl. 9.2.2 Cons and Cl. 2.5.1 to 1 techn 2.5.3 altern Engir provi Panel and g The a provi expection Authintern	Cl. 9.2.1 Princ and Cl. The c 2.4.1 object <i>in the C</i> clear the co design questi to the	Ref. clause
Constitution of standing Panel of Experts: The Committee recommends that a standing Panel of Experts needs be constituted at the national level to facilitate expeditious approvals to the proposals of using innovative technologies/materials etc. The concessionaires or contractors, who seek approval of alternative technologies or materials from the Independent Engineer / Authority's Engineer (as the case may be) and meet with disapproval or where the response is not provided in a definite time frame, should have the liberty to take these matters with this Panel of Experts. The Panel of Experts would be expected to examine such proposals and give their approval/ refuse approval within a definite time frame (e.g. one month). The arrangement of such a Panel of Experts would, in the opinion of this Committee, provide for a method of collective decision at the national level and help achieve expeditious approvals and promote the use of appropriate technologies/ alternative materials. Dispute between the concessionaire/ contractor and the Independent/ Authority's Engineer regarding technical matters (e.g. Design methodology, interpretation of code etc.) should also be referred to the above panel for giving decision.	Principle of DBFOT and EPC Contracts: The committee feels that there is need for the Government to declare firmly the objective and spirit of the DBFOT and EPC contracts viz.: <i>"the principle of allowing the Contractor the complete liberty to design the projects; within the limits set forth in the concession agreements/ contracts/manuals/specifications"</i> . It must be made clear that the drawings accompanying the tender documents are only indicative and the contractor/concessionaire is free to design the project components such that the design meets the parameters prescribed in the tender documents and that there is no questionof asking for a rebate or paying extra for the alternative designs conforming to the requirements.	Recommendation of Expert Committee
Agreed in principle, however, recommendation of Standing panel of experts should be approved by competent authority.	Agreed. For PPP projects, the manual generally provides for design and construction as per IRC codes/Ministry's specifications. Where the concessionaire intends to use an alternative material or technology to these Standards and Guidelines for delivering an equal or better product, he shall be permitted to use such alternative subject to certain conditions.	Ministry's Decision
S&R (B) and EAP zone	S&R (B) and EAP zone	Action to be taken by

-

Page 2 of 32

			by
	Composition of standing Panel of Experts: The chairman of the Panel of Experts should be a reputed	Agreed in	S&R(B)
 and Cl. professional with proven experience/background in construction and designs of high members one member of the Panel of Experts could be an expert in Highway Technology, another could be drawn from the field of structural / bridge engineser of the MORT 	professional with proven experience/background in construction and designs of highways. Out of the other members one member of the Panel of Experts could be an expert in Highway Engineering / Pavement Technology, another could be drawn from the field of structural / bridge engineering and the member secretary should be drawn from the Government e.g. Chief Engineer of the MORTH/ NHAI.	principle.	zone
Cl. 9.2.2 Functioning of standing Panel of Experts:	n	All are	S&R(B)
۲.	The Panel of Experts should meet frequently preferably once a month to deliberate on the matters referred to it.	agreed in principle.	zone
2.5.8 ii. The Panel of Experts should have the power to decide on the matter r Engineer/ Concessionaire (or Authority's Engineer/ contractor in EPC any, arising out of the decision of the Independent Engineer in technologies, materials, equipment in accordance with the above clause	The Panel of Experts should have the power to decide on the matter referred to it by the Independent Engineer/ Concessionaire (or Authority's Engineer/ contractor in EPC contracts) as regards dispute if any, arising out of the decision of the Independent Engineer in implementation of innovative technologies, materials, equipment in accordance with the above clause.		
iii. The Concessionaire/ Contractor who v the above clause should have the lib details e.g. specifications, applicable c	iii. The Concessionaire/ Contractor who wishes to adopt a new, innovative technology in accordance with the above clause should have the liberty to refer the matter to this Panel of Experts with adequate details e.g. specifications, applicable codes/ guidelines, laboratory results, field experience, literature on		
Experts. The committee should hear the Independent Engineer also.			
iv. The Panel of Experts should have the liberty to seek advice from other experts be required. The expenses towards such expert advice should be borne from fur Panel of Experts and the Chairman should have the freedom to approve and in	The Panel of Experts should have the liberty to seek advice from other experts (e.g. tunnels etc.) as may be required. The expenses towards such expert advice should be borne from funds made available to the Panel of Experts and the Chairman should have the freedom to approve and incur these expenses. The		

.

1

Chapter 2 - Measures to promote Innovative Technologies, Materials and Equipment

Page 3 of 32

Chapter	Chapter 2 - Measures to promote innovative i echnologies, matching and Equipment		
Ref. clause	Recommendation of Expert Committee	Ministry's Decision	Action to be taken by
Cl. 9.2.2	Functioning of standing Panel of Experts contd.:		S&R
and Cl.	v. Being in the realm of highly technical matters, the Panel of Experts should enjoy the	A mod in principle	EAP
2.3.9	Act. This arrangement would enable the Panel of Experts to take decisions swiftly and purely conforming to its professional mandate.	Agreed III principie.	zone
Cl. 9.2.2 and Cl.	vi. The Panel of Experts would have the power to decide disputes relating to the technical matters (including interpretation of code, design procedure etc.) pertaining to the	Agreed in principle which requires a	S&R (B) and
2.5.10	operation and implementation of the above clause. The decision of the Panel of Experts should be binding on all the parties	change in existing contract agreement.	EAP zone
Cl. 9.2.2 and Cl.	vii. The Committee wishes to reiterate the importance of speedy decision making and recommends that the Panel of Experts should provide their decision within a definite time frame (e.g. one month) from the time the matter is referred to them. The time	Agreed in principle.	S&R (B) and EAP
	could be extended suitably only in exceptional cases.		
CL 9.2.2 and Cl.	viii. The Panel of Experts should also provide guidance to the authorities in the approvals and implementation of the research schemes of the Government.	Agreed in principle.	S&R (B) and EAP
E.J.1.E			zone
Cl. 9.2.2	ix. Besides according approvals to the proposals of innovative technologies/ materials (under Clause 1.9 of the Manual as referred in the Paragraph above), the Panel of	Agreed in principle subject to approval	S&R (B) and
2.5.13	Experts as above should also be entrusted to examine various alternative technologies when individual proposals from proponents of technology/ alternative materials/	of competent authority.	EAP
	equipment are placed before them. The Panel of Experts should be empowered to approve the technologies/materials to be used either on trial stretches in appropriate cases or approve them for use in construction of highways solely based on their assessment. The technologies/ alternative materials approved by the Panel of Experts for use in construction of highways should be permissible.		

1

-

,

Chapter 2 - Measures to promote Innovative Technologies, Materials and Equipment

Page 4 of 32

Chapter 3 - Implementation Issues

Cumpier o			
Ref. clause	Recommendation of Expert Committee	Ministry's Decision	Action to be taken by
Cl. 9.3.1 and Cl. 3.2.2	 Government Officials in Charge of Implementation: It is necessary that project implementation is decentralized to the extent possible so that matters do not get prolonged in a to and fro movement of correspondence between project officials on the field and those in the headquarters. The Committee feels that a well thought out system based on decentralization of powers and responsibilities backed up by monitoring from the headquarters to verify and remove bottlenecks in the project implementation would be in order. 	Agreed.	Planning zone and JS(admin.)
Cl. 9.3.1 and Cl. 3.2.3	The Committee felt that project decisions often get delayed due to the fear in the minds of project officials about being hounded even for bona fide decisions. Genuine or bona fide decisions should not result in penal actions as they tend to create and perpetuate a system based on inaction or aversion to speedy decisions. The Committee recommends appropriate amendments to vigilance procedures so that officials taking swift decisions in the bona fide interest of the project are protected. This will benefit project implementation immensely.	Agreed. Not in MORTH mandate. Will have to refer.	CVO and JS(admin.)
Cl. 9.3.2 and Cl. 3.2.4	Performance assessment of the officials in charge of implementation should be carried out among other things, their result orientation, in terms of the achievement of the targets set. The system should acknowledge officers who perform towards realization of project targets in the timelines set with a view to facilitate the larger objective of expeditious implementation of highway projects. It is suggested to consider a system of awards to acknowledge outstanding performances.	Agreed.	JS(admin.) and S&R(B) zone
Cl. 9.3.3 and Cl. 3.2.5	A systematic periodical monitoring/reviews at higher levels within the governmental authorities to identify and resolve issues that plague project implementation would help enhance speed of implementation. These reviews should set apart projects severely lagging behind their targets and appropriate measures taken to remove bottlenecks and to expedite them.	Agreed.	Planning zone and JS(admin.)
Cl. 3.2.6	The committee recommends that in case of a collapse of a structure either during construction or later on, before taking any penal action like arrests across the board of everyone even remotely connected with the work, there should be an inquiry through a technical committee of independent experts, to determine the probable cause of the collapse to determine the responsibility. The readiness to adopt innovative designs and methods in construction in the country will otherwise receive a great setback if action is taken without such an inquiry.	Agreed. Will have to set up and publish an SOP for this.	S&R(B) zone

(n. 10)

•

.

σ
a
0
e
σ
of
ω
N

Ch
napter
er
1
Im
iple
em
ementation
Ita
tic
n
Issues
S

			» ()	<u>သ ခ ႐</u>	<u>c</u>
Cl. 3.4(3)	Cl. 3.4(2)	Cl. 3.4(1)	Cl. 9.3.5 and Cl. 3.3.5	Cl. 9.3.4 and Cl. 3.3.2 to 3.3.4	Ref. clause
Consultants have pointed out that the CVs are provided for the various positions in the consultancy assignment. The current procedure stipulates that in case of false/incorrect information supplied in the CV, the consultant is liable to be debarred. It is suggested that menal actions should be taken against individual officials rather than the consultants.	The current eligibility criterion involves annual turnover from consultancy assignments in the past. It is suggested that a certificate by the statutory auditor about annual turnovers of the respective years flowing from consultancy assignments should feature in the format.	l action (including criminal proceedings) may be taken instead of present approach	The Committee recommends that the Engineers Bill comprising licensing of professional engineers and governing their professional conduct needs to be given due importance, and the Ministry of Road Transport and Highways may take up the matter with the Ministry of Human Resources for further action in this regard.	Consultants: The consultants will be selected based on Quality and Cost Based Selection (QCBS) with weightage for the technical score of the consultants at 80% or more. In exceptional cases where the projects demand a high level of innovation, the Quality Based Selection (QBS) may also be resorted to. The Committee has made some recommendations towards procurement procedure regarding consultancy assignments as per Paragraph 3.4 in Chapter 3. The committee also recommends that track record of consultants in previous assignments should be kept in view in evaluation of their consultancy proposals.	Ref. Recommendation of Expert Committee clause Recommendation of Expert Committee
Agreed, but action will be taken against both i.e. defaulting officials as well as the consultant.	Agreed to the extent that a certificate by the statutory auditor for consultancy work only.	Agreed, but action may be taken against both i.e. defaulting officials as well as the consultant.	A matter of policy and will be taken up with M/o Human Resources & Development.	Agreed. QCBS is already in practice. QBS system for exceptional cases may also be considered, as required. The evaluation of consultant's track records can also be made as part of INFRACON by Ministry. This should be incorporated in to bid documents.	Ministry's Decision
S&R(B) and EAP zone	S&R(B) and EAP zone	S&K(B) and EAP zone	Planning zone and JS(admin.)	S&R(B) and EAP zone	Action to be taken by

Page 6 of 32

Chapter 3 - Implementation Issuescontd.

Ref. clause	Recommendation of Expert Committee	Ministry's Decision	Action to be taken by
Cl. 3.4(4)	Qualification demanded for the Team Leader's position contemplates his having worked on a team leader's position in a previous assignment. How would a person get his first assignment of the team leader in view of such a requirement? Consultants have suggested that adequate experience in a Deputy Team Leader's position should also be stipulated. This is worthy of being considered.	Agreed.	S&R(B) and EAP zone
CI. 3.4(6)	The consultancy assignment demands experience of six/ eight laning for such projects. Since there have not been many projects of this type, adequate experience of two/four/six laning may also be allowed	Agreed.	S&R(B) and EAP zone
CI. 3.4(7)	Experience certificates from the projects have to be produced. It is regarded that this takes long. Consultants have suggested that the officials should be allowed to certify their experience with the rider that cases of experience found to be fake/incorrect, would entail penal action against the individuals. The Committee finds this worthy of consideration	Not agreed as the agreement is entered between the consultant and the client	S&R(B) and EAP zone
Cl. 3.4(8)	Experience of construction supervision is usually demanded from individuals for the various positions. Experience of construction should also be considered admissible in addition to that of construction supervision.	Agreed in principle.	S&R(B) and EAP zone
Cl. 3.4(9)	RFPs usually ask for experience in developed countries. This could be made applicable to the top few (one or two) of technical personnel only. Experience in developing countries should be admissible for the remaining members of the team.	Agreed in principle.	S&R(B) and EAP zone
Cl. 3.4(10)	Sometimes individual positions which are not required for projects are stipulated, e.g. two-three financial analysts for EPC projects when one is enough etc. This anomaly needs to be corrected.	Agreed in principle.	S&R(B) and EAP zone
Cl. 3.4(11)	The newly introduced provision of Infracon website where CVs of individual officials are uploaded is a welcome measure. However, a person who has experience in multiple assignments e.g. highway engineer or bridge engineer should be allowed to upload his CV for multiple positions based on experience.	Agreed in principle.	S&R(B) and EAP zone

- - -

• •

1

Page 7 of 32

Chapter 3 - Implementation Issues

Chapte	Chapter 3 - Implementation Issuescontd.		
Ref. clause	Recommendation of Expert Committee	Ministry's Decision	Action to be taken by
Cl. 9.3.6 and Cl. 3.5	Indian Roads Congress Drafting of IRC codes be assigned to experienced consultants and academicians on payment basis as in several advanced countries. The Committee also recommends that dedicated and adequate fund be made available to the IRC to meet its expenses.	Agreed in principle. Viewpoint of IRC will be obtained. A separate budget line for IRC may be opened.	S&R(R) zone
Cl. 9.3.7 and Cl. 3.5.3	Revision of existing manuals for highways (two, four and six laning) at a frequency of at least once in two years based on experiences in project implementation, new developments in technology, materials and equipment etc.	Agreed as it is already in practice.	S&R(R) zone
Cl. 9.3.8 & Cl. 3.5.4	IRC publications may be available online and amenable for downloading from the website of IRC on payment basis.	Agreed and IRC will be instructed, accordingly.	S&R(R) zone
Cl. 9.3.9 and Cl. 3.6	 Pre- Construction Activities and Permits Mechanism for expeditious approval of environmental clearances and evolution of well-defined policy toward cutting of trees and transfer of Government lands need to be created. The Committee also recommends delegation of powers/authority (with placement of funds) to the local project officials to enable them take decisions regarding utility shifting, land acquisition payments etc. The Committee recommends easing of quarry permits, review of Gram Panchayat NOCs to expedite project implementation. The concessionaire may be allowed to retain income out of advertisement rights in the road land, on toll structures, under passes as may be permissible as per IRC standards, avenue and median plantations, car parking and road side facilities created by him. The Committee was of the view that the condition of not allowing well water for construction needs to be changed with a view to facilitate speedier implementation of projects. 	Agreed in principle and the matter may be looked into by LA & Establishment zone of Ministry. Agreed subject to safety of road users. Local issue. Links with drinking water	JS(LA) S&R(R) zone, S&R(B) zone and EAP zone JS(LA)

1

. .

age 8 of		L	,
-		õ	
-	1	P	
of	1	Ø)
-	1	0)
	ľ		h
	l	Ň	ر

Cl. 9.3.10	Cl. 9.3.9 and 3.7.3	Cl. 9.3.9 and Cl. 3.6.6	Ref. clause	Chapter 3 -
Construction completion Issue: The Committee feels that unless safety and reliability issues are involved, withholding of COD by the Independent Engineer should not be allowed. COD need not be withheld for issues such as compliance of conditions etc. for which a bank guarantee of an appropriate value for timely compliance of conditions could be obtained from the concessionaire and the COD approved. The matter of compensation if any could be settled in due course. This will help avoid adverse financial consequences to the concessionaires (and prevent the possibility of projects turning into NPAs).	ble for addressing local roject officials. rojects could be used for local needs; developing parking lots for vehicles parking lots for vehicles . Funds could be placed would accord financial blic representatives. The blic representatives. The vat 0.25% of the project such local needs	Transfer of Government Lands: The Committee was informed that several projects have been delayed for want of Government land. The Committee suggests change in the present business rules. The Committee recommends that a high-power committee under Chairmanship of retired Chief Secretary of the state or a retired High Court Judge be constituted at the state level. The committee should be equipped with powers to hear the parties, i.e., authority constructing the roads and the government department in control of the land. Based on needs of both organizations and noting the viewpoints presented by affected about expeditious transfer of government lands for the project, so that the project progress is not hampered. The matter of compensation should be separately decided by the Committee later and not linked to the process of transfer of the government land.	ecomme	Chapter 3 - Implementation Issuescontd.
Agreed as it is already in practice.		This is not a major problem. A committee will not be useful. Has to be done case by case.	Ministry's Decision	
and EAP zone	S&R(B) and EAP zone	JS(LA)	Action to be taken by	×

Page 9 of 32

Chapter 3 - Implementation Issuescontd.

Ref. clause	Recommendation of Expert Committee	Ministry's Decision	Action to be taken by
Cl. 9.3.11 and Cl. 3.8(1)	The Committee recommends suitable amendments to provisions of concession agreements/ issue of circulars to improve implementation of projects as under- The independent Engineer should be appointed early in the development period as a Condition Precedent.	Agreed. All efforts are made to appoint the independent Engineer well in advance. But, it cannot be made as a Condition Precedent. However it may be ensured to appoint the independent Engineer well in advance.	S&R(B) and EAP zone
Cl. 3.8(3)	It could be seen from the interaction with representatives of concession/ contracting	DC hands to be issued	S&R(B) and
	agreements are to be interpreted towards freedom allowed to the individual concessionaires/contractors. To avoid multiple interpretations at variance with each other, it would be suitable if the Government issues a circular clarifying the rational of the DBFOT/EPC to enable all appreciate the underlying philosophy of DBFOT/EPC in this regard. This would facilitate uniform interpretation on this aspect in the field		2
Cl. 3.8(4)	Concessionaires pointed out that steel railings are stipulated on the footpaths. These are prone to thefts and a suggestion was made that concessionaires/contractors should be allowed to use concrete for railings since these have to be maintained during the operations period. Even in case of EPC projects authority might find concrete railings suitable in view of this. The Committee recommends this suggestion for consideration	are Agreed. be he ngs	S&R(B) and EAP zone
Cl. 9.3.11.2 and Cl. 3.8(2)	The Committee felt that having due regard to the freedom allowed to the Concessionaire/Contractor in the DBFOT/EPC contracts, the Schedule B should mention clearly the mandatory scope allowing the concessionaire/contractor to design the project in accordance with these mandatory requirements. The recommendation of the Committee arose since the Committee was informed of instances where there was insistence in following the FRL mentioned in the typical cross sections circulated in the Draft Concession Agreements negating spirit of freedom for design in DBFOT.	he Agreed. For DBFOT on contracts, it is already ect in practice. tee aft	S&R(B) and EAP zone

••

•,•

•

3	v
2	U
2	2
(D
ŀ	
¢	0
C	2
	h
(ω
	U

	1
-	1
2	
napter 3	
Ξ	
-	
2	
7	8
	3
-	•
х.	
Implementation	1
	1
7	È.
2	<u>_</u>
2	
0	2
F	
1	>
1	
-	
5	
5	2
-	٠
	•
C	2
-	1
-	1
ISSUES	-
1	2
1	5
-	
F	
0	5
Ù	5
٠	
٠	

3 - Implementation Issues contd. Recommendation of Expert Committee Recommendation of Expert Committee The Committee was informed about the non-uniformity in practice of reference to especially in non-flood zone areas. HFL refers to water bodies, streams, rivers etc. only cannot be applicable beyond the flood zone. For areas beyond the flood zone, the bottom o subgrade could be kept sufficiently above, say 0.6 m above ground level. The Committee was informed that load tests of superstructure of one span, exceeding 15m all new structures is obligatory as per the terms of Concession Agreement. The Commit suggests that load test could be made mandatory only for unusual structural arrangement where any doubt exists about quality of construction or any other problem is apprehended. Clause 20.1 of IRC SP 13 requires bed protections at culvert / minor bridge locations on structure just because type drawings incorporate the same without any reference to a provision. Erosion of stratum depends on amount of flow, Velocity of the flow and istratum. Balancing culverts, culverts with very small or undefined catchment like in plane with hard soil as bed stratum, with very weak or better rock as bed stratum do notrequire a protection. In such eases bed protection could be dispensed with. The Committee recon that the drawings should make a reference to this provision in IRC SP 13 and designs necessarily be done accordingly and suitable to the site conditions of culverts/ minor bridge incluse to the site conditions of culverts/ minor bridge incluses the project should be dispensed with. The Committee reconserve the site or mites and project should be reconserved with the suggestion that the project milestones and project should be reconserved by the suggestion that the project milestones and project should be thered. <th>3 - Implementation Issues contd. Recommendation of Expert Committee Ministry's Decision Recommendation of Expert Committee Ministry's Decision The Committee was informed about the non-uniformity in practice of reference to HFL specially in non-flood zone areas. HFL refers to water bodies, streams, rivers etc. only and stretches beyond the flood zone. For areas beyond the flood zone, the bottom of the flood zones, ground evel. Agreed partially. For stretches beyond the flood zone, the bottom of the flood zones, ground level. The Committee was informed that load tests of superstructure of one span, exceeding 15m, for all new structures is obligatory as per the terms of Concession Agreement. The Committee any doubt exists about quality of construction or any other problem is apprehended. Agreed in principle and the flood zone is repercussion to amend the contract areangements or structure just because type drawings informed that this is generally insisted upon for all structure just because type drawings informed that the signerad with. The Committee any bed stratum, Balancing culverts, with very weak or better rock as bed stratum do notrequire any bed stratum do notrequire any bed protection, in such case the protection could be dispensed with. The Committee recommends that the drawings should make a reference to this provision in IRC SP 13 and design should Agreed in principle. The Committee agreed with the suggestion that the project milestores and project schedule Agreed in principle. Agreed in principle.</th>	3 - Implementation Issues contd. Recommendation of Expert Committee Ministry's Decision Recommendation of Expert Committee Ministry's Decision The Committee was informed about the non-uniformity in practice of reference to HFL specially in non-flood zone areas. HFL refers to water bodies, streams, rivers etc. only and stretches beyond the flood zone. For areas beyond the flood zone, the bottom of the flood zones, ground evel. Agreed partially. For stretches beyond the flood zone, the bottom of the flood zones, ground level. The Committee was informed that load tests of superstructure of one span, exceeding 15m, for all new structures is obligatory as per the terms of Concession Agreement. The Committee any doubt exists about quality of construction or any other problem is apprehended. Agreed in principle and the flood zone is repercussion to amend the contract areangements or structure just because type drawings informed that this is generally insisted upon for all structure just because type drawings informed that the signerad with. The Committee any bed stratum, Balancing culverts, with very weak or better rock as bed stratum do notrequire any bed stratum do notrequire any bed protection, in such case the protection could be dispensed with. The Committee recommends that the drawings should make a reference to this provision in IRC SP 13 and design should Agreed in principle. The Committee agreed with the suggestion that the project milestores and project schedule Agreed in principle. Agreed in principle.
	Ministry's Decision Agreed partially. Agreed partially. stretches beyond flood zones, gre level or ponding I needs to beconsid for deciding HFL. Agreed in principle the issue needs to carefully reviewed its repercussion amend the con agreement. Agreed. Agreed.

Page 11 of 32

Chapter 3 - Implementation Issuescontd.

Cl. 9.3.13	Cl. 3.9.3	Cl. 9.3.12 & 3.9.2	Cl. 3.8(11)	Cl. 3.8(10)	Ref. clause
Need for Vocational Training of Skilled Workmen: The Committee recommends that construction related National institutes e.g. Central Institute of Mining and Fuel Research, Roorkee and National Institute of Construction Management and Research be encouraged to conduct courses for development of multi-trade skills.	The Committee suggests that the use of such equipment for medium and large national highway projects is easily affordable in view of the size of the project and recommended so that the construction is carried out using such equipment capable of achieving impeccable quality and durability. Use of such equipment would also necessitate change in specifications to incorporate the benefits flowing from such use (e.g. increased layer thickness for embankment/pavement construction etc.). In some cases, such special equipment may not be in the list of approved equipment of MORTH or in the specifications. However, the same should be allowed on the basis of such proposal from the concessionaire.	Equipment: The Committee recommends mandating the use of automated construction using latest equipment for concrete and bituminous works.Reimbursement of royalty charges should be considered. In any case changes in royalty rates should be reimbursed.	The Committee was informed of cases where the concessionaire/contractor demanded some trial stretch to adopt a new technology. The approval to such trial stretch was delayed defeating the very purpose of trial stretch in a work to complete in a short period say 30 months. The Committee feels that there should be no objection to approve such trial stretches for adoption of new technologies since construction risk/responsibility are with the concessionaire/contractor only. Further the withholding of permissions for trial stretches for new technologies would work against development of new and modern technologies in construction of highways.	It was informed that the cost estimates for the projects were found to be unrealistic, especially when the cost estimates are not revised to account for a time gap between the DPR preparation and the bids. Sometimes many of the activities insisted from the concessionaire/contractor as part of specification/contract conditions are not costed in the estimate. This resulted in significant variance with the estimated costs creating subsequent problems in acceptance. The Committee felt that such situations should be avoided.	Recommendation of Expert Committee
Agreed & ne under "I Developm Ministry of S and Entr	tional highway ded so that the ble quality and s to incorporate ment/pavement st of approved allowed on the	struction using charges should	emanded some layed defeating 0 months. The for adoption of naire/contractor nologies would ghways.	c, especially preparation ontractor as resulted in ptance. The	
Agreed & need to be included under "National Skill Development Mission" of Ministry of Skill Development and Entrepreneurship.	Agreed.	Agreed.	Agreed.	Agreed in principle.	Ministry's Decision
Planning zone and JS(admin.)	S&R(B) and EAP zone	S&R(B) and EAP zone	S&R(B) and EAP zone	S&R(B) and EAP zone	Action to be taken by

...

σ
a
Q
qe
цц,
N
of
-
ω
N

CI. 3.11.7	Cl. 3.11.6	Cl. 3.11.5	Cl. 3.11.4	CI. 3.11.3	CI. 3.11.2	Cl. 3.11	Ref. clause	Chapte
d be allowed in the median or anywhere near lities in case of a vehicle hitting them.	Proper pier protection for piers in median prevents fatalities in case a vehicle loses control and heads for the piers. One type is shown in the photo above. Another can be seen in the photo below. The committee recommends that a suitable pier protection be provided.	Protective mesh on the overpasses provided for cross roads over the high speed roads help prevent objects falling from the cross road on the high speed road with a potential of causing serious accidents. The Committee recommends provision of such protective meshes.	The design of concrete anti crash barriers with pipe railing on top should be such as to provide a smooth sliding surface without obstruction to avoid damage to a vehicle which crashes and slides along the crash barrier. The arrangement in use presently is deficient from this angle (Fig A). The accompanying photograph (Fig B) also shows the desirable arrangement (which should be adopted to take this aspect into account).	The Committee felt that some measures such as providing anti crash barriers along the approaches to a tunnel to lead traffic into the carriageway inside the tunnel should be scrupulously ensured to avoid vehicles crashing against ends of the tunnels/footpaths/ kerbs. The photograph below shows an arrangement of such anti crash barriers, whose face should be flush with the face of the crash barriers/wall in tunnel.	The Committee, concerned with the increasing number of accidents and fatalities on the highways in this country, realized that rash driving was one of the chief reasons contributing to accidents. The Committee felt that introduction of CCTV cameras at frequent intervals on the highways and monitoring of speedy driving and levying deterrent fines could be considered to reduce accidents due to over-speeding. The deployment of drone technology involving drones with cameras to carry out surveillance of the highways could also be considered. The Committee also recommends that the Highway authorities should provide funds to the police authorities to procure equipment such as speed guns etc. to enforce traffic discipline. The income received out of imposing fines can be retained by Highway Authority.	I Issues pertaining to Road Safety	Recommendation of Expert Committee	Chapter 3 - Implementation Issuescontd.
Agreed. A circular needs to be issued.	Agreed. A circular needs to be issued.	Agreed. A circular needs to be issued.	Agreed. A circular needs to be issued.	Agreed. A circular needs to be issued.	Agreed in principle. JS(T) and Road safety Zone may take appropriate action in the matter.		Ministry's Decision	
zone	Road Safety	Road Safety and EAP zone	Road Safety and EAP zone	Koad Safety and EAP zone	JS(T), Road Safetyan d EAP zone		Action to be taken by	

•

Page 13 of 32

Chapter 3 - Implementation Issuescontd.

	Agreed.	National highways should be subjected to road safety audit periodically.	Cl. 3.11.18
Koad Safety and EAP zone	Agreed.	National Highways should be made "forgiving roads", so that injuries and fatalities in case of accidents are minimized.	Cl. 3.11.17
Dood		Liquor shops along the highways should be discouraged.	Cl. 3.11.16
		Distance markers i.e. kilometers should be displayed prominently so that drivers of high speed vehicles can read them easily. A sample photograph below illustrates the point	Cl. 3.11.15
		At every Y junctions prominent marking and signage as well as impact attenuators should be provided. Photographs below illustrate the point.	Cl. 3.11.14
		Every hard object in the median or by the roadside must be provided with impact attenuators or crash barrier to prevent instant deaths for passengers of vehicle hitting them.	Cl. 3.11.13
		Name of a flyover, under which there is a cross road or a U turn, should be displayed at least 120 m before the start of the flyover so that a driver who has to take the turn has sufficient weaving distance to move to the side road.	Cl. 3.11.12
		While designing signage and information boards for national highways [in fact for any high speed roads], it must be remembered that they are meant to be read by the elderly driver of a very fast moving vehicle. [not by the passenger]. Too much information or too many destinations on a single board should be avoided for the same reason.	Cl. 3.11.11
		In ghat sections [hilly roads] it is advisable to provide an extra lane for climbing side of the carriageway where the traffic is heavy.	Cl. 3.11.10
EAP zone	needs to be issued.	At every median break for a right turn or a U turn, an extra waiting lane of adequate length must be provided to keep the fast right lane in the carriageway obstruction-free.	Cl. 3.11.9
Road Safety and	Agreed. A circular	At every median break for U turns or right turns or pedestrian crossings, where plantation is carried out, the height of such plantation in the median should not exceed 600 mm above the road surface for distance of 20 metres from the break. This is to ensure clear visibility for the drivers.	Cl. 3.11.8
be taken by	Decision	Recommendation of Expert Committee	Ref. clause
Action to	Ministry's		Chapter 2

....

2

Page 14 of 32

Chapter 4 - Rigid (Concrete) Pavements

Cl. 9.4.2 and Cl. 4.4	Cl. 9.4.2 and Cl. 4.3	Cl. 9.4.1 and Cl. 4.2	Ref. clause
Prestressed Concrete Panels (PCP) The technology is successfully used in many countries and the Committee recommends adoption of this technology in India. However, the Committee recommends that the large scale adoption of this technology could be taken up after a trial stretch of about 15 km is taken up and constructed preferably in a National Highway project to be taken up in immediate future. The Committee interacted with the research scholars and academicians from the Visvesvaraya National Institute of Technology, Nagpur who are engaged in research on this subject. The Committee suggests therefore, that a stretch in Maharashtra near Nagpur which is already proposed/about to be proposed in the immediate near future for execution could be identified for this trial. The performance of the PCP could be observed for a period of 2 years and the technology taken up for large scale adoption in the National Highways. The Committee recommends constitution of a technical committee to guide the Ministry to prepare the consultancy document and guide the performance monitoring. The Committee suggests that the same consultant be appointed for the pre-construction / construction and post construction stages.	Continuously Reinforced Concrete Pavements (CRCP) CRCP technology with designs based on the AASHTO software should be used instead of IRC:118-2015, since AASHTO has brought out a design methodology based on the Mechanistic Empirical (ME) approach, which also results in the thickness of CRCP working out to about 20% lower in comparison to the conventional jointed pavement/CRCP design as per IRC:118-2015. The AASHTO design software based on the ME approach is based on extensive research and the Committee recommends that the funds should be provided to enable procurement of this software by institution such as the IIT Kharagpur with in-house capacity of research in concrete pavement. This software could then be used by the construction industry with the help of IIT Kharagpur for the design of the CRCP. The Committee recommends to evaluate the performance of the CRCP near Pune.	Concrete pavements should be a preferred option in high density corridors A and for highways in high rainfall zones, where bituminous pavements, prone R to damage in such conditions, involve high maintenance costs and efforts.	Recommendation of Expert Committee
nmends adoptio ption of this tec preferably in a ith the research our who are eng in Maharasht ar future for ey 1 for a period of 1 ways. The Co ways. The Co repare the consu		Agreed. Vide Ministry's circular no. RW/NH-3044/31/2014/ S&R(R)(Pt.) dated 04.08.2014, concrete pavement is made a default pavement option.	М
	agr ant ant din din atic	finistry's cii 2014/ S& concrete pa vement optio	Ministry's Decision
Agreed.	eed unless it is iated by the field conducted under conditions. A study needs to carried out gly which also the performance on of CRCP near	circular no. S&R(R)(Pt.) pavement is ption.	cision
S&R(R) zone	S&R(R) zone	S&R(R) zone	Action to be taken by

•••

•

σ
a
ā
Ð
н
S
of,
ω
N

Chapter 4 - Rigid (Concrete) Pavements

r

Ref. clause	Recommendation of Expert Committee	Ministry's Decision	Action to be taken by
Cl. 9.4.2 and Cl. 4.5	 Concrete Overlay over Existing Bituminous Surface The Committee is of the view that a systematic performance assessment study should be instituted by the Ministry for the NECE road to quantify the riding quality, noise levels, traffic and axle loads etc. The Committee is of the view that concrete overlays on the existing bituminous pavements (where the thickness of the bituminous pavement is adequate) should be considered for adoption where eminently suitable e.g. in urban areas etc. New Guidelines also allow use of this technology for new roads wherein instead of flexible pavement appropriate sub base, base and concrete overlay in such panels is proposed. 	Agreed. Agreed. A circular needs to be issued in view of IRC:SP:76-2015 or else.	S&R(R) zone S&R(R) zone
	 four-laning project etc. The Committee feels that stretches at the toll plazas on the national highways or truck lay byes could be provided with such panel pavements. 	Agreed in principle.	S&R(R) zone
Cl. 9.4.2 and Cl. 4.6.4	Use of open graded friction course (OGFC) The Committee has noted that advanced countries follow the practice of providing such open graded friction courses on concrete pavements and there should be no objection to provide such overlays on high speed concrete roads to derive the advantages referred above. The Committee therefore recommends adoption of this technology with immediate trials on some trial stretches on the existing National Highways to validate the specifications and to enable adoption of this technology on a large scale.	Agreed. A circular needs to be issued.	S&R(R) zone
Cl. 9.4.2 and Cl. 4.7	Self-Compacting Concrete for Pavements The Committee recommends that the technology should be deployed using trial stretches followed up by its use where suitable.	Agreed.	S&R(R) zone

...

.

Page 16 of 32

Chapter 5 - Flexible (Bituminous) Pavements

		· · · ·	
Ref. clause	Recommendation of Expert Committee	Ministry's Decision	be taken by
Cl. 9.5.1 and	Large scale use of Gap Graded Wearing Coursewith	Agreed in view of IRC:SP:107 - 2015. To	S&R(R)
Cl. 5.2	Rubberized bitumen binder for achieving reduced noise, reduced	promote its use, a circular needs to be	20116
	wear of tyres, enhanced skid resistance and significantly issued.	issued.	
	improved riding quality.		
Cl. 9.5.1 and	Use bituminous Concrete with Polymer Modified Bitumen.		S&R(K)
Cl. 5.3		RW/NH-33041/3/2001-S&R(K) dated	20110
		22.09.2011, Modified bitumen need to be	
		used in bituminous concrete as well as in	
		dense bituminous concrete.	
Cl. 9.5.1 and	Bituminous Overlay over Jointed Rigid Pavement		S&R(R)
Cl. 5.5	The conventional jointed rigid pavement usually faces criticism		20110
		Agreed and a circular need to be issued.	
	and the pavement surface. These problems can be addressed by		
	providing a bituminous overlay. The technology needs to be		
	studied on trial stretches to validate the specifications followed by		
	large scale implementation of this technology which has been		
	extensively used in several countries.		

....

Page 17 of 32

Chapter 5 - Flexible (Bituminous) Pavements

-	Recommendation of Expert Committee	Ministry's Decision	Action to be taken by
Cl. 9.5.1 and CSI Cl. 5.5 add pert the (IR) (IR) (IR) (IR) (IR) (IR) (IR) (IR)	CSIR-CRRI has evaluated this technology with various types of warm mix additives available in the country and have studied in detail, the performance of WMA technology in comparison to HMA. On the basis of the work done by the scientists of CSIR-CRRI, the Indian Road Congress (IRC) has brought out the interim-specification for the use of Warm Asphalt Mix in India (IRC SP 101: 2014). Some field evaluation studies of WMA and also some comparisons of carbon emissions of WMA with HMA have demonstrated encouraging results. However, the use of this technology has been very limited in our country. The Committee feels that the use of environment-friendly technologiesshould be encouraged on the lines of many advanced countries. This Committee, therefore, recommends incorporation of environment friendly technologies in all the road works, which can save our non-renewable energy resources and in that light recommends that the use of WMA technology be included in the Ministry's specifications so that the technology is adopted on a large scale for road construction in India. The Committee recommends the use of this technology where the bituminous mixes have to be hauled over long distances (e.g. in urban areas with plants located outside city limits) resulting in lower laying temperatures. WMA technology would eminently suit such situations besides providing environmental benefits mentioned above.	Agreed as it is already in practice in view of IRC:SP:101 – 2014. It needs to be included in Ministry's Specification and meanwhile, a circular needs to be issued.	S&R(R) zone
-			
und	nalized polyethylene modifiers for modified bitumen (equivalent to	Not agreed as per IS:73-2013,	S&R(R) and EAP
Cl. 5.7 VG 40).		bitumen shall be prepared by	zone
		by suitable methods	

.

4

Page 18 of 32

Chapter 5 - Flexible (Bituminous) Pavements

Cl. 9.5.3 and Mo Cl. 5.4.4 Dr. nee con stud bitt per be o levy say fact thr	Cl. 9.5.1 and Col Cl. 5.10, 5.11 rec pav	Cl. 5.9 Use limi adop	Cl. 9.5.1 & Gla Cl. 5.8	Ref. clause
Modified Bitumen Dr. Veerraghavan at IIT Madra need to carry out field perfor conditions to supplement and studies. The Committee felt t bitumen is used could be monit performance of pavements usin be developed. Test sections con in different climatic regions of levels, rainfall etc. Monitoring c say twice/thrice every year for a factors to predict the field per would help evolve appropriate of binders using mechanistic – e centre of national the sof National CRRI to fulfill this objective. T	Cold-in-situ and hot-in-situ recycling of asphalt pavements.	Use of nano-technology for technologies are cost effective and limited trials of this technology hadopted after laboratory evaluation.	ass fibre polyester hybrid geo	Recomm
Modified Bitumen Dr. Veeraghavan at IIT Madras presented a viewpoint to the Committee that there is a need to carry out field performance under actual traffic, climate and environmental conditions to supplement and confirm the observations in the laboratory performance studies. The Committee felt that performance of national highways where modified bitumen is used could be monitored periodically, so that calibration factors to predict the performance of pavements using mechanistic-empirical pavement design procedure can be developed. Test sections constructed with different modified binders are to beselected in different climatic regions of the country catering to different magnitudes of traffic levels, rainfall etc. Monitoring of structural and functional condition of these test sections say twice/thrice every year for a minimum period of three years would help develop shift factors to predict the field performance from the laboratory test results which in turn would help evolve appropriate calibration factors for design of pavements with modified binders using mechanistic – empirical pavement design procedure. The Committee recommends that research studies should be carried out by networking different reputed institutes of National Importance in different regions of the country and the CRRI to fulfill this objective. This will result in a large scale use of modified bitumen through the availability of a credible methodology of assessing the benefits.	Agreed as it is already in practice in view of the issue need a review and a comprehensive need to be issued for bring the economy in pay	different aspects of road construction:The d are not yet included in the Specifications. The we been found to be encouraging. These may be	Glass fibre polyester hybrid geosynthetic paving mats as per ASTM D 7329.	Recommendation of Expert Committee
a Agreed and a al research scheme need to be included during current ic annual plan. ff ff ff ic ic ic ic ic ic ic ic ic ic ic ic ic	Ministry's specification. However, circular based on IRC:120 – 2015 vement construction.	Agreed in principle.	Agreed.	Ministry's Decision
S&R(R) zone	S&R(R) zone	S&R(R) zone	S&R(R) zone	Action to be taken by

...

.

Page 19 of 32

Chapter 5 - Flexible (Bituminous) Pavements

CI. 5.13 Use be stre geo of a mat use	÷ 6	6
Use of Geo-Synthetic Materials in Pavement There is a shortage of aggregate in several parts of the country and good quality aggregate have to be hauled over long distances. In the north east region, the aggregate does not have adequate strength and get crushed under the load of roller. Geosytentic materials such as geogrids, geocomposites as filter areas or geocells can perform an important role in improving the properties of aggregate due to the confining effects, and use of such materials would help not only reduce material consumption but enable use of the local materials. The Committee recommends that research/ trial stretches based on this technology be taken on priority followed by large scale use of this technology.	 The Committee felt that there was a need to define appropriate criterion for determining the type of renewal and thickness of bituminous concrete. It is suggested that whenever surface roughness exceeds the limit prescribed in IRC 82 renewal coat may be regarded as warranted. In such situations, Benkelman Beam Deflections may be obtained to verify if overlay or strengthening layer is needed, taking into account the existing crust and after assessment of traffic in the intervening period before the next renewal coat. Falling weight deflectometer results could also be used. Based on these, the decision of whether renewal coat is sufficient, or if strengthening overlay is needed could be taken if the pavement surface is otherwise free from cracks rutting etc. If roughness measurements exceed the limits specified in IRC 82, and if the existing crust is adequate for the traffic of 15 years as per above criterion, micro-surfacing may be provided for mm thick BC could be provided if the traffic (before the next wearing coat, 30 MSA. In case the traffic is more than or equal to 50 MSA, a 40 mm thick BC could be provided as per requirement. If in situ cold recycling or hot in situ recycling is adopted in that case the recommended thickness would be thickness of processed layer. 	Recommendation of Expert Committee
Agreed as it is already in practice as per Ministry's Specification.	A comprehensive Maintenance guidelines needs to be framed and issued by Ministry for corrective and proactive (preventive) maintenances of pavement structures.	Ministry's Decision
S&R(R) zone	S&R(R) zone	Action to be taken by

11 11

Page 20 of 32

Chapter 5 - Flexible (Bituminous) Pavements

Ref. clause Cl. 5.14
Imported bitumen • Experts have pointed out to the Committee that the quality of bitumen produ country does not always meet the stipulated (IS) standards. The Committee suggests holding of a high level meeting with petroleum ministry to bring into focus so as to take suitable corrective steps.
ointec ot alv ng of to ta

a
D
0
N
1
0
-
ω
N

Chapter 6 - Tunnels

Ref. clause Cl. 9.6.1	Provision of tunnels should be made on the basis of another of the state of tunnels should be made on the basis of tunnels should be made on tunnels should be made on tunnels
Cl. 9.6.1 and Cl. 6.3.1.7(i)	Provision of tunnels should be made on the basis of assessment of benefits and costs. The benefits could be direct like saving in travel distance or climbing up and down or indirect such as easing of traffic or creating shortcuts in public interest. It is suggested that while framing every DPR, the possibilities of providing tunnels as an alternative to detours/ circuitous routes in hilly areas should be explored.
Cl. 9.6.2 and Cl. 6.3.1.7 (ii)	The provision of artificial Cut and Cover Tunnels of adequate lengths at the location of deep open cuts, outside excavated portals at entrances of bored tunnels and potential slip zones along the alignment of roads will help to avoid blockage due to landslides and resultant hindrance to traffic (e.g. in the Himalayas). The length of such a cut and cover tunnel beyond the bored tunnel will depend on the local geotechnical conditions. The cut and cover tunnel could be in cast-in-situ concrete or prefabricated steel frames. (or corrugated steel plates). In locations where due to geological conditions, it is not feasible to provide cut and cover tunnel in front of a slip zone, a tunnel going below the slip should be provided.
Cl. 6.3.1.7 (iii)	Alignment of the roadway going into and coming out of a tunnel should merge smoothly with the contour. For achieving such smooth merging, curves should be introduced in the horizontal alignment of the tunnel.
Cl. 6.3.1.7 (iv)	Surface drainage above the portal and along the two sides of open cuts should be so designed that rain water running down the mountain slopes does not drain into the open cut. If possible, invert of the open cuts should be made to slope down away from the portal to prevent rain water from flowing into the tunnel.
Cl. 9.6.3 and Cl. 6.3.2.5.1	Procurement of Land required for muck disposal and temporary Excluding temporary construction construction camps, licenses and permits for storage of explosives and camps, agreed for other arrangements for construction power should be arranged before award of preconstruction activities as their contracts, so as to avoid delays during execution on this score.

Pag
e
22
of,
32

Chapter 6 – Tunnels			
Ref. clause	Recommendation of Expert Committee	Ministry's Decision	Action to be taken by
Cl. 9.6.4 and Cl. 6.3.3	Adoption of controlled blasting for tunnels (with appropriate noise abatement measures and monitoring during execution) should be considered even in the reserved forest areas, and special permission from the Ministry of Environment and Forests should be obtained preferably before the award of work of such tunnels.	Agreed in principle. Issue may be taken up with Ministry of Environment and Forests.	JS(LA)
Cl. 9.6.5 and Cl. 6.5	Bidding Stage DPR should be made available to the bidders with all the details of investigations/ geotechnical data for bidders to base their bids. A method should be provided for adjustment to the contract price due to the difference between the lengths of tunnel in the strata encountered and that expected on the basis of geotechnical data available in the DPR/ bid documents. The adjustment could be in monetary form in case of item-rate and EPC contracts and monetary form or suitable adjustment in concession period in case of the DBFOT concessions.	Not agreed, as it is against the spirit and philosophy of the EPC contracts. In item rate contracts, it can be accepted.	S&R(B) and EAP zone
Cl. 9.6.6 and Cl. 6.6	Tunnel Excavation by Drill and Blast Method is the cheapest and attempt should be made to use it wherever possible. Tunnels under populated areas and sensitive structures should be excavated by Road Headers provided, the UCS of the rock is below 120 MPa, if feasible. Tunnels under populated areas and sensitive structures may have to be excavated by Tunnel Boring Machines only if the UCS of the rock is above 120 MPa, even at a prohibitive cost, as there is no other practical method of excavation. Use of Tunnel Boring Machines should also be considered for tunnels longer than 10 km and where high speed tunneling is called for.	Not agreed, as it is against the spirit and philosophy of the EPC contracts. Under the framework of contract agreement, the contractor will decide the Tunnel Excavation method. However, the suggestion will keep in EPC agreements as reference guidance.	S&R(B) and EAP zone

Page 23 of 32

Chapter 6 – Tunnels

elscontd.

Ref. clause	Recommendation of Expert Committee	Ministry's Desision	
			ACUOII to De taken
CI 0 67	Though and it is a true to		by
and Cl. 6.7	Inough provision of cladding is not an absolute necessity, Agreed as it will enhance the cladding should be considered to make long tunnels user- comfort levels of drivers during friendly.	Agreed as it will enhance the comfort levels of drivers during traversing of tunned	S&R(B) zone
		and or fulliel.	
and CI 6.8	inclusion and main a strety and comfort, stricter supervision of Agreed as they are already in	Agreed as they are already in	S&R(B) zone
AIIU CI. 0.0	"	practice in view of IRC:SP:91 -	
	adhered specially in long tunnels and it should not be 2010. A circular will be issued to	2010. A circular will be issued to	
	compromised for achieving economy, since it affects safety.	address the concern of expert	21
		committee.	
CI. 9.0.92nd CI. 6.9	Cl. 5.9 Mobile phone service providers should be encouraged to install Agreed. Cl. 6.9 transponders inside long tunnels to create connectivity.	Agreed.	S&R(B) zone

-
σ
a
qe
Ð
24
0
-h
ω
N

Chapter 7 - Bridges

-	_		^				1
Cl. 9.7.4 and Cl. 7.3.8 to 7.3.10	Cl. 9.7.3 and Cl. 7.3.5 to 7.3.7	Cl. 9.7.2 and Cl. 7.3.3	Cl. 9.7.1 and Cl. 7.3.1, 7.3.2, 7.3.4		CL 7.2.1	Ref. clause	
Corrosion resistant steel bars such as weathering steel or 'Corten' steel and "Ready to use Rebar" technology will be used.	For steel bridges, High Strength Structural Steel & high strength friction grip boltsshould be used.	Use Spherical Bearingin place of POT bearings which are not only more efficient in load transfer but also occupy less space on the pier cap.	Material The Committee recognized the need to innovative materials, processes and construction techniques that can provide economical, durable and fast construction of bridges. Therefore, use of concrete with cementitious additives & admixtures e.g. blast furnace slag, fly ash pozollanas, plasticizers, super- plasticisers etc.should be encouraged along with the use of Self- Compacting Concrete and High Performance Concrete (HPC).	Although most advanced bridge technologies are already in use in India, their use has been mainly on some selected projects. The Committee felt the need to go to an advanced level of bridge technologies for use in national highway projects. In the view of the Committee, this would mean use wherever required, of larger spans, bigger elements and more sophisticated and heavier plant and equipment for their casting, transport and erection.	Need for Advanced Technologies	Recommendation of Expert Committee	
Agreed.	Agreed as they are already in practice.	Agreed as use of Spherical Bearing is already in practice in view of IRC:83 (part IV) – 2014. Choice of bearing is site specific and needs.	Agreed. Use of High Performance Concrete is already in practice in view of IRC:SP:70 – 2005. To initiate the use of Self-Compacting Concrete in India, necessary guidelines and specifications need to be developed.	Agreed, as it is the need of hour.		Ministry's Decision	
S&R(B) zone	S&R(B) zone	S&R(B) zone	S&R(B) zone	S&R(B) zone		Action to be taken by	

Page 25 of 32

Chapter 7 - Bridgescontd.

Ref. clause	Recommendation of Expert Committee	Ministry's Decision	Action to be taken by
Cl. 9.7.5 and Cl. 7.3.11, 7.3.12	Fiber Reinforced Polymers (FRP) composites will be used in new construction, repairs and rehabilitation of bridge structures.	Agreed. A research scheme to develop the design philosophy & implementation of FRP decks and FRP composites for using in bridge structures need to be carried out and included in current annual plan.	S&R(B) zone
Cl. 9.7.6 and Cl. 7.3.13	Waterproofing of concrete decks is necessary especially when segmental construction is to be deployed.	Agreed. In fact, waterproofing of each bridge deck is essential and it should form an integral part of wearing coat system for all types of bridges. Ministry's Specification need to be modified.	S&R(B) zone
Cl. 9.7.7 and Cl. 7.3.14	High damping Rubber (HDR) bearings need to be introduced.	Agreed. A circular for seismic isolators, arrestor devices and associated bearings need to be issued.	S&R(B) zone
Cl. 9.7.8 and Cl. 7.4	 Codes and Standards Various IRC bridges codes (IRC 78, 83, 112 etc.) need a comprehensive review and revision to synchronised them with International standards and current knowhow. 	Agreed. IRC will be advised accordingly. The work was assigned to IRC. Current status will be obtained from IRC.	S&R(B) zone and IRC
-	 Ministry's standard drawings and plans need to be revised immediately. IRC codes will be prepared on paid basis through academicians or expert consultants instead of voluntary basis. Ministry keep a dedicated fund for it. 	Otherwise, Min standard drawings suitable manpow which will be bene department's ex thousand crores of Agreed in principle	

Se bar

•

,

Page 26 of 32

Chapter 7 - Bridgescontd.

Ref. clause	Recommendation of Expert Committee	Ministry's Decision	Action to be taken by
Cl. 9.7.9 to	Superstructure:	Agreed in principle.	S&R(R) zone
9.7.11 and Cl. 7.5	 Continuous or jointless bridges requiring minimum bearings and expansion joints should be encouraged as they are more durable and more aesthetic. Ground supported staging should be avoided as far as possible. Steel and steel-concrete composite bridges will be used in ROBs. 		
Cl. 7.7.3	For wide decks (greater than 15m), single cell box girders with struts supporting the tips of the deck cantilevers or breaking the deck span by introducing internal struts are useful tools that can obviate the necessity of multi-cell box girders which are more difficult to construct. Such design geometry should be encouraged in design of wide deck bridges.	Agreed.	S&R(R) zone
Cl. 7.7.6	Steel and steel-concrete composite bridges can be advantageously used in many instances. ROBs are one example where Indian Railways have clear preference for such bridges because of reduced block time for train movements during their construction.	Agreed.	S&R(R) zone
Cl. 7.7.7	Pedestrian bridges across highways, with no support at median verge of the highway (Fig. 6 and 22) are excellent examples of safe and aesthetic bridges when the selected bridge form is the arch, which can readily span upto 90-100m economically and without difficulty. The Committee recommends adoption of this approach for construction of pedestrian bridges especially in urban areas where adequate pier protection in the median is considered to be difficult.	Agreed.	S&R(R) zone
Cl. 7.7.8	Long bridges over perennial water require special technique for construction. "End-on" construction and large bridge segments floated into position and erected by floating cranes are some of the special techniques that should be considered before finalizing the actual technique for such bridges.	Agreed.	S&R(R) zone

....

σ
aq
Q
Ð
N
V
0
-
ω
N

Chapter 7 - Bridgescontd.

Ref. clause	Recommendation of Expert Committee	Ministry's Decision	Action to be taken by
Cl. 9.7.12/ 9.7.14 and Cl. 7.8.6	Pre-casting factories should be encouraged to be set up in all major states. Precast products from such factories e.g. girders, box structures for culverts etc. can be used for construction of various highway structures. Standard designs of these standard components can be got approved from MORTH for use in bridges, cross drainage structures etc., so that further design checks during construction may not be needed. A scheme for approval of design from MORTH after paying the necessary charges should be established. If these approved designs are used, then there should be no further	Agreed in principle subject to structural safety and overall	S&R(B) zone
	scrutiny of structural design by either Independent Engineer or authority.		
CI. /.8.0.1	Exemption may be provided from Excise duty for these factories in order to not increase the cost of the projects. In any case the precasting facilities specific to a project are exempt from Excise duty, hence there would be no loss of revenue to the Government anyway	Agreed in principle. Issue may be taken up with M/o Finance.	S&R(B) zone
Cl. 7.6.1	Aesthetics	Agreed.	S&R(B) zone
с	Special attention should be paid to aesthetics in bridge construction. The design life of bridge construction is 100 years and what we build today would last for generations.Bridges are amongst the largest and most visible man-made structures. The form and surface finishes, both play a part in the overall appearance of the structure. Slim structures, keeping in mind the scale and proportion in relation to the surroundings and of different parts of the same structure contribute to its aesthetics.		
Cl. 7.6.3	Construction of arch bridges where they fit into the landscape or urban environment need to be encouraged.	Agreed.	S&R(B) zone
Cl. 7.6.4	Medium span bridges in the form of extradosed bridges need to be encouraged as they enhance aesthetics without much additional cost in the span range 75m to 150m. Long span structures like cable stayed bridges where required functionally, i.e., long span, or to provide a landmark which is visible from a long distance need to be encouraged where necessary.	Agreed.	S&R(B) zone

.

Page 28 of 32

Chapter 7 - Bridges	1	Ministry's Decision
Cl. 9.7.15 to 9.7.18 and Cl. 7.9	 Pile Foundation Use large diameter piles such as 2.0 m/2.5m (or larger diameters) for speedy and reliable construction. Use of mono piles with large diameter piles (2.0 m and above) where appropriate. Low strain (Integrity testing) and high strain testing after proper calibration and Ultrasonic Pulse Velocity tests through pre-installed tubes for larger diameter piles should be mandatory to ensure soundness of concrete in piles. Use of advanced piling equipment which are now available (with the capability to carry out boring into hard rock and which make it possible to install large diameter deep foundations in such strata) should be encouraged in preference to well foundations which are not suitable for 	le Agreed in principle subject to their structural feasibility, stability & durability & durability and overall pr economy.
Cl. 7.10.2	Well Foundations, where used, should preferably be installed with Jack-down techniques (Fig. 30) which can improve speed of construction, reduce steining thickness and result in better control during well-sinking operations.	3. Agreed.
Cl. 9.7.13 and Cl. 7.12.1	Miscellaneous Not Cross drainage and Animals Crossings are required to be provided at frequent intervals along highway construction. The Committee recommends that such crossings should be provided at about 500 m. so that a crossing is available in a distance of 250 m from any point. Crossings for smaller vehicles are also required to be provided at some places. Not	Not agreed. They will be provided as per site requirement instead of proposed general consideration.
Cl. 9.7.13 and Cl. 7.12.2	Use innovative technologies e.g. Corrugated Steel Plate Arches (thin steel plate arches) or thin precast concrete arches as economical and speedy alternative for small bridges or cross drainage structures.	ge Agreed.
Cl: 7.12.5	Safety and security during construction needs special attention as most accidents, collapses and casualties happen at this stage. The design as well as construction procedures should be proof checked not only of the structure at the service stage but also during construction stage when the structure, being partially complete, is at its most vulnerable stage.	nd Agreed as it is of already in he practice.

σ
a
ā
Ð
N
õ
0
Ť
ω
Ň

Chapter 7 - Bridgescontd.

Cl. 7.13.11.10	Cl. 9.7.19 and Cl. 7.13	Cl. 7.12.6	Ref. clause
Typical contract conditions should be modified where required, to encourage alternate design of bridges with particular reference to Accelerated Bridge Constructions. The contract conditions should prescribe requirements for speedy review, approval and execution of ABC designs. Since ABC typically requires large investment in construction equipment, the same should also be factored in the terms and conditions of contract so that larger mobilization or equipment advances are provided. A strong incentive package will further help meet the objectives of ABC. Government also has to play a major role in giving required facilities such as land for casting yard, labour camp, quick power connections, setting up high power interdepartmental coordination committee to address administrative issues, etc.		Long circuitous road lengths, many times going up and down can be avoided especially in hilly sections by increased use of viaducts hopping across valleys and is recommended since it increases road safety and decreases road lengths	Recommendation of Expert Committee
Agreed in principle.	Agreed. A guideline for design of structural elements and their joints used in ABC need to be developed along with creating facilities for the construction methodology, erecting system & equipments and transportation facilities etc.	Agreed subject to structural & safety feasibility; and overall economy.	Ministry's Decision
S&R(B) zone	S&R(B) zone	S&R(B) zone	Action to be taken by

Page 30 of 32

Chapter 7 - Bridgescontd.

.2	0
7.13.11. 12	Ref. clause
 Construction of ROBs Railways do not permit concrete girders on railway span and require only steel girders. However, it is noted that due to construction of several metro projects as well as several bridges where precast girders have been used, very good, safe and efficient launching systems are readily available. The use of precast concrete girders, that is produced in controlled environment and hence of assured quality should be permitted. If required, the Railways may evolve the criteria for empanelment of agencies that own good aunching system and prequalify them. The Railways may also make it mandatory for the ROB contractor Composite girder as analternative to precast prestresseed girders. By insisting on only Steel subtantially and nationally could amount to hundreds of crores. The Railways our of the empanelled agencies for launching of girders. By insisting on only Steel subtantially and nationally could amount to hundreds of crores. The Railways own 60m land to accommodate signal man quarters, etc. In such cases also they insist on construction of ROB spanning the entire 1 and the entire 1 and there is need of future tracks, the same can be provided by creating opening in the construction. The RDSO has prepared standard structural designs for various spans to accommodate two tracks, four tracks and sta tracks. In the RDSO standard designs, stiffeners are not provided in the steel plate girder webs, resulting in increase in web plate thickness compared to the thickness required from laak to est of a subtract design s differers in a be provided using friction bot to stiffener plate their quality can be subtracted from load dia considerable encores the quality of structural designs for various spans to accommodate two tracks, four tracks and sta tracks. It is well as severed that the saving could much budged working environment in a factory and thus considerable increase in cost of future tracks and structural design requirement. The use of lower thickness of	Recommendation of Expert Committee
Agreed and may be taken up with M/o Railway.	Ministry's Decision
S&R(B) zone	Action to be taken by

D
b
9
Ð
ω
μ
0
-
ω
N

(
22
-
Ä
0
-
0
-
hapter 8 - Research in J
-
0
S
0
22
-
0
þ
n
-
Highway
<u>ua</u>
D.
5
00
5
5
Sector
0
3
H

Ref. clause	Item	Recommendation of Expert Committee	Ministry's Decision	Action to be
				taken by
Cl. 9.8.2 and Cl. 8.2	Materials	The Committee recommends upgradation of laboratories in the academic institutions through earmarking of funds for this purpose on an annual basis.	Agreed. Ministry need to establish a dedicated and exclusive research organisation similar to NCHRP# functioning in USA for providing practical, ready-to-implement solutions to all issues pertaining to Highway Sector	S&R(R) zone
CI. 8.3	Selection of	Recearch cohomon will be called a start	r	
	research scheme	transparent mechanism similar to as used in Deptt. of Science & Technology or Deptt. of Biotechnology.	Agreed in principle. The selection procedure will be studied and a policy need to framed for the selection of research	S&R(R) zone and S&R(B) zone
Cl. 9.8.3 and Cl. 8.4	Annual fund allocation	Annual research funding provided by MORTH should be significant and at least in the range of Rs. 150-200 crores.	Agreed in principle subject to availability of funds.	Planning zone
Cl. 9.8.4	APT	h	Not agreed, as CRRI is functioning as a	S&R(R) zone
	¢	annual budgetary provision be made available to CRRI to operate the accelerated pavement testing equipment.	constituent of CSIR with primary objective of sustained development of Science and Technology Human Resources. The testing facilities at CRRI may be used by anyone as per norms of CRRI in order to comply with contract agreement conditions.	S&K(K) Zone
Cl. 9.8.5 and Cl. 8.5	Indicative list of Research Schemes	The Committee recommends that research projects on problems as per the indicative list given in Chapter 8 may be taken up through the ministry.	Agreed. A detailed road map need to be prepared and implemented.	S&R(R) zone and S&R(B) zone

Page 32 of 32

state departments of transportation), American Association of State Highway and Transportation Officials (AASHTO), in cooperation with sector. The NCHRP is administered by the Transportation Research Board (TRB) and sponsored by the member departments (i.e., individual #National Cooperative Highway Research Program (NCHRP) is a forum for coordinated and collaborative research which addresses the Federal Highway Administration (FHWA). Individual research projects are conducted by a panels of expert stakeholders. issues integral to the state Departments of Transportation (DOTs) and transportation professionals at all levels of government and the private