भारत सरकार सडक परिवहन एवं राजमार्ग मन्त्रालय

क्षेत्रीय कार्यालय न्यू एरिया दत्ता विला रोइ नियर एन०टी०सी० मोराबादी रॉॅंची-834008.



Ph.: (0651) - 2550279, 2550183 (Tele-Fax) **GOVERNMENT OF INDIA** Ministry of Road Transport & Highways Regional Office New Area Datta Villa Road Near N.T.C. Morabadi Ranchi – 834008. E-Mail- roranchi03@gmail.com

No RW/Ranchi/OFC/15/2018-19/JHR/584

Dated: 15 October, 2018

Invitation of public comments

Sub: Proposal for seeking permission for laying water supply pipe line along and across the NH-23.

The Project Director, NHAI, PIU, Dhanbad vide letter no. 11015/5/PD/DHN/UL-OFC/1297 dated 22.09.2018 has forwarded therewith a proposal in this office for laying water supply pipe line along and across the NH-23, submitted by the Executive Engineer, Drinking Water & Sanitation Division, Ramgarh, vide letter no. 862 dated 06.07.2018 i.e. the applicant on above mentioned subject.

- As per Ministry OM vide no. 33044/29/2015/S&R(R) dated 22.11.2016, the Highway 2. Administration will make available the proposal seeking permission for utility services for public comments for 30 days on ground of public interest.
- In view of the above, the comments of public are invited on captioned proposal and the same should reach to below mentioned address till 15.11.2018 beyond which no comments will be considered.

The Regional Officer, Regional Office, MoRT&H, Government of India, New Area, Dutta Villa Road, Antu Chowk, Morabadi, Ranchi, Jharkhand-834008 Email Id: roranchi03@gmail.com

This is issued with the approval of Highway Administrator cum Regional Officer, 4.

MoRT&H, Ranchi.

Encl. As above

(Amit Kumar Singh) Asst, Executive Engineer,

For, Regional Officer.

Copy to:

The Technical Director, NIC, Transport Bhawan, New Delhi-110001 for uploading on (i)

The Project Director, PIU-Dhanbad, NHAI, NHAI Complex, Kandra, P.O Bhitia, P.S -

(ii) Govindpur, Dhanbad-828109 (Jharkhand).

The Executive Engineer, Drinking Water & Sanitation Ramgarh Division. (iii)



भारतीय राष्ट्रीय राजमार्ग प्राधिकरण

(सड़क परिवहन और राजमार्ग मंत्रालय, भारत सरकार) परियोजना निदेशक का कार्यालय, परियोजना कार्यान्वयन इकाई, एन.एच.ए.आई. कॉम्प्लेक्स, कान्ड्रा, पोस्ट भीतीया, थाना गोविन्दपुर, धनबाद-८२८,१०६ (झाररखण्ड)

National Highways Authority of India (Ministry of Road Transport & Highways, Govt. of India)

Office of the Project Director, Project Implementation Unit, NHAI Complex Kandra, P.O. Bhitia, P.S. Govindpur, Dhanbad-828109 (Jharkhand)

Ref: 11015/5/PD/DHN/UL-OFC/ 1291

दूरभाष / Ph. : 06540-283089 06540-283090

फैक्स / Fax : 06540-283184 ईमेल ∕ E-mail : dhan@nhai.org

nhaidhanbad@yahoo.in

To Shri Amit Kumar Singh Asst. Executive Engineer Ministry of Road Transport & Highways Regional Office New Area Datta Villa Road Near N.T.C. Morabadi, Ranchi - 834008

Proposal of permission for laying water supply pipe line along & across the NH-23 Sub: for Gola Water Supply Scheme.

Ref: (i) EE, DW&SD, Ramgarh letter No. 862 dated 06.07.2018

- (ii) MoRTH, RO-Ranchi letter No. RW/Ranchi/OFC/15/2018-19/JHR/264 dated 09.07.2018
- (iii) This office letter No. 11015/5/PD/DHN/UL-OFC/1032 dated 20.08.2018
- (iv) EE, DW&SD, Ramgarh letter No. 1138 dated 05.09.2018

Sir,

The proposal of permission for laying water supply pipe line along & across the NH-23 for Gola Water Supply Scheme Ramgarh submitted by the Executive Engineer, DW&S Division, Ramgarh has been scrutinized by this office in light of MoRTH Circular dated 22.11.2016 & found in order.

Further, as per Minutes of the Meetings dated 28.06.2018 in the Chairmanship of Hon'ble Chief Minister, Govt. of Jharkhand, the submission of Bank Guarantee is not required by DW&S Division! However, as per MoRTH Circular dated 22.11.2016, the charges for granting licence for use of highway land is pending.

Accordingly, the cited proposal is hereby recommended for according necessary permission for laying of water supply pipe line.

Thanking you,

Yours faithfully,

Encl: As above (2 sets).

Project director

Copy to:

Executive Engineer, DW&SD, Ramgarh - With request to please deposit the desired licence fee for use of highway land.

> (R. B. Jha) Project director

Office of the Executive Engineer D.W. & S. Division Ramgarh (Jharkhand)

LetterNO - 1138, Dated - 05/09/2018.

From.

Executive Engineer

D.W. & S. Division Ramgarh (Jharkhand)

To,

The Project Director,

Project Implementation Unit, NHAI Complex

Kandra, P.O. Bhiitia, P.S. Govindpur, Dhanbad 828109

Sub. :-

Proposal of permission for laying water supply pipe line along & across the

NH-23 for Gola Water Supply Scheme.

Ref. :-

Sir,

Yours Ref. No.-11015/5/PD/DHN/UL-OFC/1032 Date 20.08.2018

With refrence to the above letter the required documents/ informations is hereby submitted.

1. Drawing showing the size of open trench is attached and it is as below -

for laying of 100 mm dia pipe, size of Trenche will be 500 mm.

250 mm dia pipe, size of Trenche will be 600 mm.

300 mm dia pipe, size of Trenche will be 700 mm.

- 2. We will not require drilling by HDD method but we have to cross the pipe line at two locations. First through existing culvert at chainage 22.575 K.M. Ramgarh to Bokaro and second through existing bridge at chainage 24.870 K.M from Ramgarh to Bokaro (shown in attached drawing).
- 3. Route Plan is attached with chainage.
- 4. As per proceding of Honourable Chief Minister of Jharkhand meeting held on 28.06.2018. Para (ठ) के तिसरे नंबर के अनुसार NHAI योजनाओं में जलापूर्ति पाईपलाइन / विद्युत लाईन / अन्डरग्राउण्ड केबलिंग इत्यादि की अनुमति हेतु बैंक गारण्टी के बदले राज्य सरकार के अन्डरटेकिंग को NHAI द्वारा िट निर्मत करने हेतु Accept किया जायेगा। Submission of Performance Bank Guarantee is not required for Government Department (Proceding of C.M. meeting attached). All undertakings are already submitted by Letter No. 862, dated 06.07.2018

Encl:- as above.

Your's faithfully

Executive Engineer D.W. & S. Division Ramgarh

1-059

From:

Reduce Till From

Executive Engineer
Drinking Water & Sanitation
Division Ramgarh,

Regional Officer
Ministry of Road Transport & Highways
Government of india
Regional office
New Area Datta Villa road, Near N.T.C
Morabadi, Ranchi- 834008

Sub:

Seeking Permission for laying water supply pipe line along and across the NH-23

Project:

Re- Organisation of Gola Rural water supply scheme under D.W.& S. Division Ramgarh on turnkey bssis,

Ref:

Discussion with project Director, NHAI and Executive Engineer, MORTH at Ranchi on 27.06.18

Dear sir,

This has reference to the subject and Subsequent discussion with proect Director, NHAI and Executive Engineer, MORTH at Ranchi on 27.06.18 on the Subject.

As advised we are pleased to submit our proposal for seeking permission for laying water supply pipe line along and across the NH- 23 for the above mentioned water supply project under DMFT Scheme.

Proposed Water supply pipeline alignment along NH -23 (North side): Ramgarh To Bokaro (Left Side)

- 1. 300 mm dia pipeline between Km 21.50 to Km 24.30 2800.0 Mtr (Rising Main)
- 2. 100 mm dia pipeline between Km 24.30 to Km 24.80 500.0 Mtr (Distribution Pipe Main)
- 3. 100/250 mm dia pipeline between Km 24.30 to Km 24.80 500.0 Mtr
- 4. 100 mm dia pipeline between Km 24.80 to Km 26.50 1700.0 Mtr

Ramgarh To Bokaro (Right Side) (South side)

- 1. 100 mm dia pipeline between Km 21.70 to Km 22.950 1250.0 Mtr
- 150 mm dia pipeline between Km 23.60 to Km 24.80 1200.0 Mtr
- 3. 100 mm dia pipeline between Km 24.80 to Km 25.10 300.0 Mtr (Rising Main)
- 200/150 mm dia pipeline between Km 24.80 to Km 25.10 300.0 Mtr
- 5. 100mm dia pipeline between Km 25.10 to Km 25.90 800.0 Mtr

Our proposal constitutes the following documents as per the NHAI guideline along with necessary drawings showing the chainage locations as well as the cross sections at the crossing locations:

- Check list duly filled in
- Undertakings
- 3. License Deed
- Certificate
- 5. Drawings

We would like to mention that being a Government department under State Government of Jharkhand it would not be feasible to submit Bank Guarantee by us. However, we are agreeable to submit an Undertaking as per draft attached.

Trust above would meet your requirement.

We would earnestly request you to accord your approval at the earliest enabling us to execute the project.

In this regard your cooperation is highly appreciated

Thanking you,

Youre sincerely

Executive Engineer

Drinking Water & Sanitation

Division Ramgarh,

<u>CHECK - LIST</u>

Guideline for Project Direction for processing the proposal for laying of sewer/ water pipe line in the land along National Highway vested with NHAI.

- Relevant Circulars of Ministry of Road Transport and Highways
- 1) Circular No. NH-41(58)/68 dated 31.1.1969.
- 2) Circular No. RW/NH-III/P/66/76 dated 18/19.11.1976
- 3) Circular No. RW/NH-III/P/66/76 dated 11.5.1982
- 4) Circular No. RW/NH-11037/1/86-DOI (ii) dated 28.07.1993.
- 5) Circular No. RW/NH-11037/1/86/DOI dated 19.01.1995.
- 6) Circular No. RW/NH- 34066/2/95/S&R dated 25.10.1999.
- 7) Circular No. RW/NH-34066/7/2003 S&R (B) dated 17.09.2003

Check list for getting approval for lying of Sewer/ Water Pipe line on NH land

The permission for laying for Sewer/water Pipe Line shall considered for approval / rejection based on the Ministry Circulars mentioned as above.

- (a) Carrying of sewage/ water Pipe line on Highway Bridge shall not be permitted as Fumes/gas/water pipes can accelerate the-process of corrosion or may cause explosions, thus, being much more injurious than leakage of water.
- (b) Service are not being allowed criminate on the parapet / any part of the bridge, safety of the bridges has to be kept in view while permitting various service along bridge.

Sr. No.	ITEM	INFORMATION STATUS	REMARKS
1	General Information		7. ·
1.1	Name and Address of the Application/ Company	Executive Engineer Drinking water & sanitation Division, Ramgarh ,Jharkhand	
1.2	National Highway Number	NH 23	
1.3	State	Jharkhand	
1.4	Location	Ramgarh	
1.5	Chainage in KM	Km 21.50 to Km 24.30 – 2800.0 Mtr (Rising Main) 100 mm dia pipeline between Km 24.30 to Km 24.80 – 500.0 Mtr (Distribution Pipe Main) 100/250 mm dia pipeline between Km 24.30 to Km 24.80 – 500.0 Mtr 100 mm dia pipeline between Km 24.80 to Km 26.50 – 1700.0 Mtr Ramgarh To Bokaro (Right Side) (South side) 100 mm dia pipeline between Km 21.70 to Km 22.950 – 1250.0 Mtr 150 mm dia pipeline between Km 23.60 to Km 24.80 – 1200.0 Mtr 100 mm dia pipeline between Km 24.80 to Km 25.10 – 300.0 Mtr (Rising Main) 200/150 mm dia pipeline between Km 24.80 to Km 25.10 – 300.0 Mtr 100mm dia pipeline between Km 24.80 to Km 25.10 – 300.0 Mtr 100mm dia pipeline between Km 24.80 to Km 25.10 – 300.0 Mtr	
1.6	Length of Meter(length in km) including Both side	9350 Mtr	
1.7	Width of Available ROW (a) Left Side from Center line towards increasing Chainage/KM direction (b) Right Side from Center line towards increasing Chainage/KM direction	As per NHAI limit	
1.8	Proposal to lay underground electrical Cable		
1.9	Proposal acquire land	NA NA	
7.5	r roposar acquire lattu	NA NA	

	/h\ District Co.		
	(b) Right Side from Center Line		,
1.10	Whether Proposal is in the same side where land is not to	NA	
-	be acquire	l NA	
-	If not then where to lay the cable		
1.11	Details of already laid service, if any, along the proposed		
	route	NIL	
1.12	Number of Existing lanes (2/4/6/8 lanes).	2	
1.13	Proposed Number of lanes(2 lane with Paved		
1.13	shout/4/6/8 lanes)	4	
1.14	Service road existing or not	No	
	If yes when which side	NO	
	(a) Left side from center side		
	(b) Right side from center side		
1.15	Proposed Service Road		
	(a) Left side from center side	NA NA	
-		-	
	(b) Right side from center side	-	
1.16	Whether Proposal of lay Water/ Sewer Pipe line is after		
1.16	the service road or between the service road or between	NA NA	
	the service road and main carriageway	•	
1	Whether Carrying of Sewage /Lay Water Pipeline has		
1.17	between the closed on highway Bridges,	NA	
	If yes than mention the methodology proposed for		
	Whether carrying of sewage/lay water pipeline has been		
1.18	proposed on parapet/any part of bridges.	NA	
	If yes, then mention the methodology proposed for the	NA NA	
	same.		
	If crossing of the road involved	Yes, it is proposed to cross at 2 nos.	
	If yes, it shall be either encased in pipe or through	location.	
,	structure or conduits specially built for that purpose at	(1) encased by 250 mm dia. MS	
	the expense of the agency owning the line.	Casing pipe for 1 no 150 mm dia	
	- 1 1 2	water line (2) At chainge 24.80 Km	
		Below existing bridge 250mm and	
		100mm dia pipe (Shown in attached	
	2	drawing)	
1		3.36/	
	(a) Whether existing drainage structure are allowed to		,
	carry sewage/ water pipeline	No	
	(b) Is it on a line normal to NH	Yes	
	(c) What is the distance of crossing the sewage /water	4	
1 1	pipeline from the existing structure. Crossing shall not be		
	too near the existing structures on the NH, the maximum	-	
	distance being 15 m.		
	(d) The crossing pipe (or conduit pipe in the case of	(1) encased by 250 mm dia. MS	
	electric cable) carrying the utility line shall be of steel.	Casing pipe for 1 no 150 mm dia	
1 1	electric cable) carrying the utility line shall be of steel,	Casing pipe for 1 no 150 mm dia	,
	cast iron or reinforcement cement concrete and have	water line (2) At chainge 24.80 Km	
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready	water line (2) At chainge 24.80 Km Below existing bridge 250mm and	
	cast iron or reinforcement cement concrete and have	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached	
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready	water line (2) At chainge 24.80 Km Below existing bridge 250mm and	
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable.	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached	
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached	
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path.	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing)	
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path. (F) The Casing /conduit pipe should, as minimum extend	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing)	
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path. (F) The Casing /conduit pipe should, as minimum extend from drain in cuts and toe of slope.	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing)	
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path. (F) The Casing /conduit pipe should, as minimum extend from drain in cuts and toe of slope. (G) The top of the Casing/conduit pipe should be at	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing)	
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path. (F) The Casing /conduit pipe should, as minimum extend from drain in cuts and toe of slope. (G) The top of the Casing/conduit pipe should be at least 1.2 meter below the surface of the road subject to	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing) Yes Yes	•
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path. (F) The Casing /conduit pipe should, as minimum extend from drain in cuts and toe of slope. (G) The top of the Casing/conduit pipe should be at least 1.2 meter below the surface of the road subject to being at least 0.3 m below the drain inverts, Mention the	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing) Yes Yes 1.5 m	•
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path. (F) The Casing /conduit pipe should, as minimum extend from drain in cuts and toe of slope. (G) The top of the Casing/conduit pipe should be at least 1.2 meter below the surface of the road subject to	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing) Yes Yes	•
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path. (F) The Casing /conduit pipe should, as minimum extend from drain in cuts and toe of slope. (G) The top of the Casing/conduit pipe should be at least 1.2 meter below the surface of the road subject to being at least 0.3 m below the drain inverts, Mention the proposed details.	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing) Yes Yes 1.5 m	•
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path. (F) The Casing /conduit pipe should, as minimum extend from drain in cuts and toe of slope. (G) The top of the Casing/conduit pipe should be at least 1.2 meter below the surface of the road subject to being at least 0.3 m below the drain inverts, Mention the proposed details. (H) Mention the methodology proposed for crossing of	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing) Yes Yes 1.5 m	
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path. (F) The Casing /conduit pipe should, as minimum extend from drain in cuts and toe of slope. (G) The top of the Casing/conduit pipe should be at least 1.2 meter below the surface of the road subject to being at least 0.3 m below the drain inverts, Mention the proposed details.	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing) Yes Yes 1.5 m	
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path. (F) The Casing /conduit pipe should, as minimum extend from drain in cuts and toe of slope. (G) The top of the Casing/conduit pipe should be at least 1.2 meter below the surface of the road subject to being at least 0.3 m below the drain inverts, Mention the proposed details. (H) Mention the methodology proposed for crossing of	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing) Yes Yes 1.5 m Drawing enclosed	•
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path. (F) The Casing /conduit pipe should, as minimum extend from drain in cuts and toe of slope. (G) The top of the Casing/conduit pipe should be at least 1.2 meter below the surface of the road subject to being at least 0.3 m below the drain inverts, Mention the proposed details. (H) Mention the methodology proposed for crossing of road for the proposed sewage/pipe line crossing shall be	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing) Yes Yes 1.5 m Drawing enclosed HDD (trench less technology)	
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path. (F) The Casing /conduit pipe should, as minimum extend from drain in cuts and toe of slope. (G) The top of the Casing/conduit pipe should be at least 1.2 meter below the surface of the road subject to being at least 0.3 m below the drain inverts, Mention the proposed details. (H) Mention the methodology proposed for crossing of road for the proposed sewage/pipe line crossing shall be by boring method(HDD) (Trench —less	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing) Yes Yes 1.5 m Drawing enclosed HDD (trench less technology)	
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path. (F) The Casing /conduit pipe should, as minimum extend from drain in cuts and toe of slope. (G) The top of the Casing/conduit pipe should be at least 1.2 meter below the surface of the road subject to being at least 0.3 m below the drain inverts, Mention the proposed details. (H) Mention the methodology proposed for crossing of road for the proposed sewage/pipe line crossing shall be by boring method(HDD) (Trench —less Technology), Specially , where the existing road pavement is of cement concrete or dense bituminous concrete	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing) Yes Yes 1.5 m Drawing enclosed HDD (trench less technology)	•
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path. (F) The Casing /conduit pipe should, as minimum extend from drain in cuts and toe of slope. (G) The top of the Casing/conduit pipe should be at least 1.2 meter below the surface of the road subject to being at least 0.3 m below the drain inverts, Mention the proposed details. (H) Mention the methodology proposed for crossing of road for the proposed sewage/pipe line crossing shall be by boring method(HDD) (Trench —less Technology), Specially , where the existing road pavement is of cement concrete or dense bituminous concrete type.	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing) Yes Yes 1.5 m Drawing enclosed HDD (trench less technology)	•
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path. (F) The Casing /conduit pipe should, as minimum extend from drain in cuts and toe of slope. (G) The top of the Casing/conduit pipe should be at least 1.2 meter below the surface of the road subject to being at least 0.3 m below the drain inverts, Mention the proposed details. (H) Mention the methodology proposed for crossing of road for the proposed sewage/pipe line crossing shall be by boring method(HDD) (Trench —less Technology), Specially , where the existing road pavement is of cement concrete or dense bituminous concrete type. (i) The casing /conduit pipe shall be installed with an	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing) Yes Yes 1.5 m Drawing enclosed HDD (trench less technology) Methodology enclosed	
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path. (F) The Casing /conduit pipe should, as minimum extend from drain in cuts and toe of slope. (G) The top of the Casing/conduit pipe should be at least 1.2 meter below the surface of the road subject to being at least 0.3 m below the drain inverts, Mention the proposed details. (H) Mention the methodology proposed for crossing of road for the proposed sewage/pipe line crossing shall be by boring method(HDD) (Trench —less Technology), Specially , where the existing road pavement is of cement concrete or dense bituminous concrete type. (i) The casing /conduit pipe shall be installed with an even bearing throughout its length and in such a manner	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing) Yes Yes 1.5 m Drawing enclosed HDD (trench less technology)	
	cast iron or reinforcement cement concrete and have adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable. (E) Ends of the casing / conduit pipe shall be sealed from the outside, so that it does not act as a drainage path. (F) The Casing /conduit pipe should, as minimum extend from drain in cuts and toe of slope. (G) The top of the Casing/conduit pipe should be at least 1.2 meter below the surface of the road subject to being at least 0.3 m below the drain inverts, Mention the proposed details. (H) Mention the methodology proposed for crossing of road for the proposed sewage/pipe line crossing shall be by boring method(HDD) (Trench —less Technology), Specially , where the existing road pavement is of cement concrete or dense bituminous concrete type. (i) The casing /conduit pipe shall be installed with an	water line (2) At chainge 24.80 Km Below existing bridge 250mm and 100mm dia pipe (Shown in attached drawing) Yes Yes 1.5 m Drawing enclosed HDD (trench less technology) Methodology enclosed	

Ch.

	Cross section showing the size of trench for open		
	trenching method		
	is it normal size of 1.2m deep x 0.3 wide,		
1	(i) Should not be greater than 60cm wider than the outer	-	
	diameter of the pipe.	Proceedings of the second	
	(ii) Located as close to the extreme edge of the right of		
2.1	way as possible of the nearest carriageway.	Enclosed	
1	(iii) Shall not be permitted to run along the national	Enclosed	
	highway when the road formation is situated in double		
-	cutting .Nor shall these be laid over the existing culverts		
	and bridge.	n x	
	(iv) These should be so laid that their top is at least 0.6		
	meter below the ground level so as not to obstruct drainage of the road land.		
	Cross section showing the size of pit and location of cable		
2.2	for HDD method.	Enclosed	
	Strip plan, Route Plan showing Water Pipe line ,		
	Chainage, width of ROW, distance of proposed water		
2.3	pipe line from the edge of ROW, important mile stone,	Enclosed	
	intersections , cross drainage works etc.		
2.4	Methodology for laying of Water Pipe line	Enclosed	
	Open trenching method (May be allowed in utility	Enclosed	
	corridor only where pavement is neither cement		
2.4.1	concrete nor dense bituminous concrete type.	_	
	If yes, what is the Methodology than the outer diameter	2	
* .	of the pipe?		
	(a) The width should be at least 30 cm, but not more than		
	60 cm wider than outer diameter of the pipe.	· -	
	(b) For filling of the trench, bedding shall be to a depth of	•	
	not less than 30 cm. it shall consist of granular material,	,	
	free of lumps, clods and cobbles and graded to yield a	<i>f</i>	
	firm surface without sudden change in the bearing value.	- v	
	Unsuitable value. Unsuitable soil and rock edged should	7	
	be excavated and replaced be selected materials		
	(c) The backfill shall be completed in two stages (i) side –		
	fill to the level of the top of the pipe and (ii) overfill to	-	
4	the bottom of the road crust.		
2	(d) The side-fill shall of granular material laid in 15 cm	·	
	layers each consolidated by mechanical tampering and		
31	controlled addition of moisture to 95% of the Proctor's Density. Overfill shall be compacted to the same density	-	
	as the material that had been removed. Consolidation by		
İ.	saturation or Ponding will not be permitted.		
	(e) The road crust shall be built to the same strength as		
	the existing crust on either side of the trench. Care shall	<u> </u>	
	be taken to avoid the formation of a dip at the trench.		
	(g)If required, a division shall be constructed at the		
	expenses of agency owning the utility line.		
	Horizontal Direction Drilling (HDD) Method	Vac	
2.4.2		Yes	
	Methodology for laying of Water Pipe Line through CD		
2.4.3	works and method of Laying. In cases where the carrying	_	
2.4.3	of Water pipeline on the bridge becomes inescapable.		
		,	
3	Draft License Agreement signed by two witnesses.	Enclosed /	
5	· · · · · · · · · · · · · · · · · · ·		
	Performance Bank Guarantee in favor of NHAI has to be		
	obtained @ Rs. 100/- per running meter (Parallel to NH)		
	and Rs100000/- per crossing of NH, for a period of one	being a Government department	
	year initially (extendable if required till satisfactory	under State Government of	
	completion of work) as a security for ensuring/ making	Jharkhand, it would not be	
. 4	good the excavated trench for laying the Water pipeline/	feasible to submit Bank	
. 4	ducts by proper filling and compaction, clearing debris/	Guarantee by us. However, we	
,	loose earth produced due to execution of trenching at	are agreeable to submit an	
	least 50m away from the edge of the right way. No	undertaking – draft attached	
	payment shall be payable by the NHAI to the license for		
	clearing debris/ loose earth.		
	Performance BG as per above is to be obtained.		

4.1	Confirmation of BG has been obtained or not as per NHAI guidelines.		
7.1			
5	Affidavit/ Undertaking from the applicant for the following is to be furnished	Yes	
5.1	Not to damage to other utility, if damaged then to pay the losses either to NHAI or to the concerned agency.	Enclosed	
5.2	For Renewal of Bank Guarantee.	PI refer clause no 4 above	
5.3	For Confirming all standard condition of Ministry circulars and NHAI's guideline.	Enclosed	
5.4	For Shifting of Water pipeline as and when required by NHAI at their Owen cost.	Enclosed	
5.5	For Shifting of water pipeline due to 6 lanning/widening of NH	Enclosed	
5.6	For Indemnity against all damages and claims	Enclosed	
5.7	For Traffic movement during laying of water Pipe Line to be managed by the applicant	Enclosed	
5.8	If any claim is raised by Concessionaire then the same has to be paid by the applicant.	NA NA	
5.9	Prior approval of the NHAI shall be obtained before undertaking any work of installation, shifting or repairs, or alterations to the Water Pipe line any other utility located in the National Highway right of ways.	Enclosed	
5.10	Expenditure, if any, incurred by NHAI for repairing any damage cause to the national Highway by the laying, maintenance or shifting of the water pipeline will be borne by the applicant agency owing the line.	Enclosed	
5.11	If the NHAL considers it necessary in future to move the utility line for any work of improvement or repairs to the road, it will be carried out as desired by the NHAL at the cost of the agency owning the utility line within a reasonable time (not exceeding 60 days) of the intimation given.	Enclosed	· · · · · · · · · · · · · · · · · · ·
e e	Certificate from the applicant in the following format (i) Laying of water Pipe Line will not have any deleterious effects on any of the bridge components and roadway safety for traffic.		
5.12	(ii) "We do undertake that I/We will relocate service road/ approach road/ utilities at my/ our own cost notwithstanding the permission granted within such time as will be stipulated by NHAI" for future six-lanning or any other development.	Enclosed	
6	Who will sign the agreement on behalf of water pipeline agency.	Executive Engineer, DW&SD Ramgarh	
	Power of Attorney to sign the agreement is available or not	Available	
7	The Project Director, will submit the following Certificates		
7.1	Certificate for proposal for confirming of all standard condition issued vide Ministry of Road Transport and Highways Circular No. NH-III/P/66/76 dated 18/19.11.1976, RW/NH-III/P/66/76 dated 11.05.1982, RW/NH-11037/1/86-DOI(ii) dated 28.07.1993, RW/NH-11037/1/86/DOI dated 19.01.1995, RW/NH-34066/2/95/S&R dated 25.10.1999 and Circular No. RW/NH- 34066/7/2003S&R (B) dated 17.09.2003		
7.2	Certificate from PD in the following format (i) "it is certified that any other location of water Pipeline would be extremely difficult and unreasonable costly and installation of water pipeline within ROW will not adversely affect the design, stability & traffic safety of the highway nor the likely future improvement such as widening of the carriageway, easing of curve etc." (ii) For 6 – lanning		

7.3	(a) Where feasibility is available "I do certify that there will be no hindrance to proposed six-lanning based on the feasibility report considering proposed structures at the said location." (b) In case feasibility report is not available "I do certify that sufficient Row is available at site for accommodating proposed six-lanning."		
8	If NH section proposed to be taken up by NHAI on BOT basis — a clause is to be inserted in the agreement. "The permitted Highway on which License has been granted the right to lay Water pipeline/duct has also been granted as a right of way to the concessionaire under the concession agreement for up-gradation of Ramgarh To bokaro 21.50Km to 26.0 km at NH-23 (from Ramgarh to bokaro) on Build, Operate and Transfer Basis] and therefore, the licensee shall honour the same."	NA	
9	Who will supervise the work of laying of water pipeline		
	(a) On behalf of the Applicant	Executive Engineer, DWSD, Ramgarh	
	(b) On behalf of NHAI	Manager	
10	Who will ensure that the defects in road portion after laying of water pipeline are corrected and if not corrected then what action will be taken.		
	(a) On behalf of the Applicant	Executive Engineer, DW&SD ,Ramgarh	
	(b) On behalf of NHAI	Project Director	
11	Who will pay the claim for damage done/ disruption in working of Concessionaire if asked by the Concessionaire	NA	
2	On behalf of the Applicant	Executive Engineer, DW&SD ,Ramgarh	
12	A Certificate from PD that he will enter the proposed permission in the register of records of the permission in the prescribed Performa (Copy enclosed).		
13	If any previous approval is accorded for laying of underground water pipeline then Photocopy of register of records of permissions accorded as maintained by PD then copy be enclosed.		•

